

DATA SHEET

TDA8735 PLL frequency synthesizer

Product specification
File under Integrated Circuits, IC01

September 1994

Philips Semiconductors



PHILIPS

PLL frequency synthesizer

TDA8735

FEATURES

- Complete 30 MHz single-chip tuning system
- Loop amplifier included
- 2-level current amplifier (charge pump) for adjusting the loop gain
- A powerful digital memory phase detector
- Programmable reference frequencies of 1 kHz, 10 kHz or 25 kHz
- I²C-bus interface
- Programmable address select input
- Software controlled switch output.

APPLICATIONS

- Satellite sound receiver
- Radio receiver: LW, MW and SW.



GENERAL DESCRIPTION

The TDA8735 is a single-chip PLL synthesizer designed for satellite receivers. The device can be set to two different addresses which can be used in applications where independently tuned VCOs are required.

To adapt to different frequency accuracy, 3 reference frequencies are selectable via the I²C-bus. The charge pump current can be set to 2 values with a ratio of 1 : 100 via the I²C-bus.

A programmable switch (open collector) is integrated to enable mode or normal switching, or other types of application.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V _{CC1}	supply voltage (pin 3)		4.5	5.0	5.5	V
V _{CC2}	supply voltage (pin 16)		V _{CC1}	8.5	12	V
I _{CC1}	supply current (pin 3)	outputs unloaded	12	20	28	mA
I _{CC2}	supply current (pin 16)	outputs unloaded	0.2	0.5	1	mA
f _{i(max)}	maximum input frequency		30	–	–	MHz
f _{i(min)}	minimum input frequency		–	–	512	kHz
V _{i(rms)}	input voltage (RMS value)		30	–	500	mV
P _{tot}	total power dissipation		–	0.14	–	W
T _{amb}	operating ambient temperature		–30	–	+85	°C

ORDERING INFORMATION

TYPE NUMBER	PACKAGE		
	NAME	DESCRIPTION	VERSION
TDA8735	DIP16	plastic dual in-line package; 16 leads (300 mil)	SOT38-1
TDA8735T	SO16	plastic small outline package; 16 leads; body width 3.9 mm	SOT109-1

PLL frequency synthesizer

TDA8735

BLOCK DIAGRAM




Fig.1 Block diagram.

PLL frequency synthesizer

TDA8735

PINNING

SYMBOL	PIN	DESCRIPTION
XTAL1	1	reference oscillator output
XTAL2	2	reference oscillator input
V _{CC1}	3	supply voltage 1
V _{EE}	4	ground
n.c.	5	not connected
DEC	6	prescaler decoupling
VCOF1	7	VCO input frequency
BS	8	band switch output
n.c.	9	not connected
SDA	10	serial data input (I ² C-bus)
SCL	11	serial clock input (I ² C-bus)
AS	12	address select input (I ² C-bus)
n.c.	13	not connected
LOOP _I	14	tuning voltage amplifier input
LOOP _O	15	external loop filter output
V _{CC2}	16	supply voltage 2




Fig.2 Pin configuration.

FUNCTIONAL DESCRIPTION

The TDA8735 contains the following parts and facilities:

- Input amplifier VCO-signal.
- A prescaler with the divisors 3 : 4 and a 2-bit programmable swallow counter.
- A 13-bit programmable counter.
- A digital memory phase detector.
- A reference frequency channel comprised of a 4 MHz crystal oscillator followed by a reference counter; the reference frequency can be 1 kHz, 10 kHz or 25 kHz and is applied to the digital memory phase detector.
- An I²C-bus interface with data latches and control logic; the I²C-bus is intended for communication between microcontrollers and different ICs or modules. Detailed information on the I²C-bus specification is available on request.
- A software-controlled switch output.
- A programmable current amplifier (charge pump) which consists of a 5 μA and a 500 μA current source, this allows adjustment of loop gain, thus providing high-current high-speed tuning and low current-stable tuning. The output at the loop amplifier can deliver a tuning voltage of up to 10.5 V (V_{CC2} – 1.5 V).

Controls

The TDA8735 is controlled via the 2-wire I²C-bus. As slave receiver for programming there is one module address, a logic 0 (R/W bit), a subaddress byte and four data bytes. The subaddress determines which one of the four data bytes is transmitted first. The module address contains a programmable address bit (D1) which with address select input AS (pin 12) makes it possible to operate two TDA8735 in one system.

The auto increment facility of the I²C-bus allows programming of the TDA8735 within one transmission (address + subaddress + 4 data bytes).

The TDA8735 can also be partially programmed. Transmission must then be ended by a stop condition.

The bit organization of the 4 data bytes is illustrated in Fig.3 and is described below.

The divider number is defined by 15-bit words, bits S0 to S14. To calculate the lock frequency, the divider number has to be multiplied by the selected reference frequency.

PLL frequency synthesizer

TDA8735

Table 1 Divider number setting.

ON	DIVIDER NUMBER SETTING	INPUT
0	$(S_0 + S_1) \times 2^1 \dots + S_{13} \times 2^{13} + S_{14} \times 2^{14}$	ON

Where the minimum divider ratio is: $2^6 = 64$ to $2^{15} - 1 = 32761$.

Table 2 Bit CP (used to control the charge pump; DB0: D0).

CP	CURRENT
0	LOW
1	HIGH

Table 3 Bits REF1 and REF2 (used to set the reference frequency applied to the phase detector; DB2: D7 and D6).

REF1	REF2	FREQUENCY (kHz)
0	0	1
0	1	10
1	0	25
1	1	0

Table 4 Bit OPAMP (used to control the switch in the tuning voltage amplifier output circuitry; DB2: D4).

OPAMP	SWITCH
1	on
0	off

Table 5 Bit BS (used to control the open-collector switch output; DB2: D2).

BS	SWITCH OUTPUT
1	sink current
0	floating

The data byte DB3 must be set to 0...0. It is also used for test purposes (see Fig.3).

PLL frequency synthesizer

TDA8735

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	MIN.	MAX.	UNIT
V _{CC1}	supply voltage (pin 3)	-0.3	+5.5	V
V _{CC2}	supply voltage (pin 16)	V _{CC1}	12.5	V
P _{tot}	total power dissipation	-	0.85	W
T _{amb}	operating ambient temperature	-30	+85	°C
T _{stg}	storage temperature	-65	+150	°C

HANDLING

Every pin withstands the ESD test in accordance with "MIL-STD-883C category B" (2000 V).

CHARACTERISTICS

V_{CC1} = 5 V; V_{CC2} = 8.5 V; T_{amb} = 25 °C; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
Supplies						
V _{CC1}	supply voltage (pin 3)		4.5	5.0	5.5	V
V _{CC2}	supply voltage (pin 16)		V _{CC1}	8.5	12	V
I _{CC1}	supply current (pin 3)	no outputs loaded	12	20	28	mA
I _{CC2}	supply current (pin 16)	no outputs loaded	0.2	0.5	1	mA
		TDA8735T only	0.7	1	1.5	mA
I²C-bus inputs (SDA and SCL)						
V _{IH}	HIGH level input voltage		3.0	-	5.0	V
V _{IL}	LOW level input voltage		-0.3	-	+1.5	V
I _{IH}	HIGH level input current		-	-	10	μA
I _{IL}	LOW level input current		-	-	10	μA
SDA output						
V _{OL}	LOW level output voltage	open collector; I _{OL} = 3.0 mA	-	-	0.4	V
AS input						
V _{IH}	HIGH level input voltage	AS = C6	3.0	-	5.0	V
V _{IL}	LOW level input voltage	AS = C4	-0.3	-	+1.0	V
I _{IH}	HIGH level input current		-	-	10	μA
I _{IL}	LOW level input current		-	-	10	μA
RF input						
f _{i(max)}	maximum input frequency		30	-	-	MHz
f _{i(min)}	minimum input frequency		-	-	512	kHz
V _{i(rms)}	input voltage (RMS value)	measured in Fig.4	30	-	500	mV
R _i	input resistance		-	5.9	-	kΩ
C _i	input capacitance		-	2	-	pF



PLL frequency synthesizer

TDA8735

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
Oscillator (XTAL1 and XTAL2)						
R _{xtal}	crystal resonance resistance (4 MHz)	see Fig.5	–	–	150	Ω
Programmable charge pump						
I _{CHP}	output current to loop filter	bit CP = logic 0	3	5	7	μA
		bit CP = logic 1	400	500	600	μA
		bit CP = logic 0; TDA8735T only	3	5	9	μA
Ripple rejection						
RR	$20 \log \frac{\Delta V_{CC1}}{\Delta V_O}$	f _{ripple} = 100 Hz	40	50	–	dB
	$20 \log \frac{\Delta V_{CC2}}{\Delta V_O}$	f _{ripple} = 100 Hz	40	50	–	dB
Band switch output (pin 8)						
V _{OH}	HIGH level output voltage		–	–	12	V
V _{OL}	LOW level output voltage	I _{OL} = 3 mA	–	–	0.8	V
I _{LO}	output leakage current	V _{OH} = 12 V	–	–	10	μA
Tuning voltage amplifier output (pin 15)						
V _{O(max)}	maximum output voltage	I _{source} = 0.5 mA	V _{CC2} – 1.5	–	–	V
V _{O(min)}	minimum output voltage	I _{sink} = 1 mA	–	–	0.8	V
I _{source}	maximum output source current		0.5	–	–	mA
I _{sink}	maximum output sink current		1.0	–	–	mA
Z _{O(off)}	impedance of switched-off output		5	–	–	MΩ
I _{bias}	input bias current (absolute value)		–	1	5	nA

PLL frequency synthesizer


TDA8735



PLL frequency synthesizer

TDA8735

APPLICATION INFORMATION




Loop filter depends on VCO parameters.

Fig.6 Application example.

PLL frequency synthesizer


TDA8735

PACKAGE OUTLINES



PLL frequency synthesizer

TDA8735



Dimensions in mm.

Fig.8 plastic small outline package; 16 leads; body width 3.9 mm (SO16; SOT109-1).

PLL frequency synthesizer

TDA8735

SOLDERING

Plastic dual in-line packages

BY DIP OR WAVE

The maximum permissible temperature of the solder is 260 °C; this temperature must not be in contact with the joint for more than 5 s. The total contact time of successive solder waves must not exceed 5 s.

The device may be mounted up to the seating plane, but the temperature of the plastic body must not exceed the specified storage maximum. If the printed-circuit board has been pre-heated, forced cooling may be necessary immediately after soldering to keep the temperature within the permissible limit.

REPAIRING SOLDERED JOINTS

Apply a low voltage soldering iron below the seating plane (or not more than 2 mm above it). If its temperature is below 300 °C, it must not be in contact for more than 10 s; if between 300 and 400 °C, for not more than 5 s.

Plastic small-outline packages

BY WAVE

During placement and before soldering, the component must be fixed with a droplet of adhesive. After curing the adhesive, the component can be soldered. The adhesive can be applied by screen printing, pin transfer or syringe dispensing.

Maximum permissible solder temperature is 260 °C, and maximum duration of package immersion in solder bath is 10 s, if allowed to cool to less than 150 °C within 6 s. Typical dwell time is 4 s at 250 °C.

A modified wave soldering technique is recommended using two solder waves (dual-wave), in which a turbulent wave with high upward pressure is followed by a smooth laminar wave. Using a mildly-activated flux eliminates the need for removal of corrosive residues in most applications.

BY SOLDER PASTE REFLOW

Reflow soldering requires the solder paste (a suspension of fine solder particles, flux and binding agent) to be applied to the substrate by screen printing, stencilling or pressure-syringe dispensing before device placement.

Several techniques exist for reflowing; for example, thermal conduction by heated belt, infrared, and vapour-phase reflow. Dwell times vary between 50 and 300 s according to method. Typical reflow temperatures range from 215 to 250 °C.

Preheating is necessary to dry the paste and evaporate the binding agent. Preheating duration: 45 min at 45 °C.

REPAIRING SOLDERED JOINTS (BY HAND-HELD SOLDERING IRON OR PULSE-HEATED SOLDER TOOL)

Fix the component by first soldering two, diagonally opposite, end pins. Apply the heating tool to the flat part of the pin only. Contact time must be limited to 10 s at up to 300 °C. When using proper tools, all other pins can be soldered in one operation within 2 to 5 s at between 270 and 320 °C. (Pulse-heated soldering is not recommended for SO packages.)

For pulse-heated solder tool (resistance) soldering of VSO packages, solder is applied to the substrate by dipping or by an extra thick tin/lead plating before package placement.

PLL frequency synthesizer

TDA8735

DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.

PLL frequency synthesizer

TDA8735

NOTES

Philips Semiconductors – a worldwide company

Argentina: IEROD, Av. Juramento 1992 - 14.b, (1428)
BUENOS AIRES, Tel. (541)786 7633, Fax. (541)786 9367

Australia: 34 Waterloo Road, NORTH RYDE, NSW 2113,
Tel. (02)805 4455, Fax. (02)805 4466

Austria: Triester Str. 64, A-1101 WIEN, P.O. Box 213,
Tel. (01)60 101-1236, Fax. (01)60 101-1211

Belgium: Postbus 90050, 5600 PB EINDHOVEN, The Netherlands,
Tel. (31)40 783 749, Fax. (31)40 788 399

Brazil: Rua do Rocio 220 - 5th floor, Suite 51,
CEP: 04552-903-SÃO PAULO-SP, Brazil.
P.O. Box 7383 (01064-970).

Tel. (011)821-2333, Fax. (011)829-1849

Canada: PHILIPS SEMICONDUCTORS/COMPONENTS:
Tel. (800) 234-7381, Fax. (708) 296-8556

Chile: Av. Santa Maria 0760, SANTIAGO,
Tel. (02)773 816, Fax. (02)777 6730

Colombia: IPRELENZO LTDA, Carrera 21 No. 56-17,
77621 BOGOTA, Tel. (571)249 7624/(571)217 4609,
Fax. (571)217 4549

Denmark: Prags Boulevard 80, PB 1919, DK-2300 COPENHAGEN S,
Tel. (032)88 2636, Fax. (031)57 1949

Finland: Sinikalliontie 3, FIN-02630 ESPOO,
Tel. (9)0-50261, Fax. (9)0-520971

France: 4 Rue du Port-aux-Vins, BP317,
92156 SURESNES Cedex,
Tel. (01)4099 6161, Fax. (01)4099 6427

Germany: P.O. Box 10 63 23, 20043 HAMBURG,
Tel. (040)3296-0, Fax. (040)3296 213.

Greece: No. 15, 25th March Street, GR 17778 TAVROS,
Tel. (01)4894 339/4894 911, Fax. (01)4814 240

Hong Kong: PHILIPS HONG KONG Ltd., 6/F Philips Ind. Bldg.,
24-28 Kung Yip St., KWAI CHUNG, N.T.,
Tel. (852)424 5121, Fax. (852)428 6729

India: Philips INDIA Ltd, Shivsagar Estate, A Block,
Dr. Annie Besant Rd. Worli, Bombay 400 018
Tel. (022)4938 541, Fax. (022)4938 722

Indonesia: Philips House, Jalan H.R. Rasuna Said Kav. 3-4,
P.O. Box 4252, JAKARTA 12950,
Tel. (021)5201 122, Fax. (021)5205 189

Ireland: Newstead, Clonskeagh, DUBLIN 14,
Tel. (01)640 000, Fax. (01)640 200

Italy: PHILIPS SEMICONDUCTORS S.r.l.,
Piazza IV Novembre 3, 20124 MILANO,
Tel. (0039)2 6752 2531, Fax. (0039)2 6752 2557

Japan: Philips Bldg 13-37, Kohnan2-chome, Minato-ku, TOKYO 108,
Tel. (03)3740 5028, Fax. (03)3740 0580

Korea: (Republic of) Philips House, 260-199 Itaewon-dong,
Yongsan-ku, SEOUL, Tel. (02)794-5011, Fax. (02)798-8022

Malaysia: No. 76 Jalan Universiti, 46200 PETALING JAYA,
SELANGOR, Tel. (03)750 5214, Fax. (03)757 4880

Mexico: 5900 Gateway East, Suite 200, EL PASO, TX 79905,
Tel. 9-5(800)234-7381, Fax. (708)296-8556

Netherlands: Postbus 90050, 5600 PB EINDHOVEN, Bldg. VB
Tel. (040)783749, Fax. (040)788399

New Zealand: 2 Wagener Place, C.P.O. Box 1041, AUCKLAND,
Tel. (09)849-4160, Fax. (09)849-7811

Norway: Box 1, Manglerud 0612, OSLO,
Tel. (022)74 8000, Fax. (022)74 8341

Pakistan: Philips Electrical Industries of Pakistan Ltd.,
Exchange Bldg. ST-2/A, Block 9, KDA Scheme 5, Clifton,
KARACHI 75600, Tel. (021)587 4641-49,
Fax. (021)577035/5874546.

Philippines: PHILIPS SEMICONDUCTORS PHILIPPINES Inc,
106 Valero St. Salcedo Village, P.O. Box 2108 MCC, MAKATI,
Metro MANILA, Tel. (02)810 0161, Fax. (02)817 3474

Portugal: PHILIPS PORTUGUESA, S.A.,
Rua dr. António Loureiro Borges 5, Arquiparque - Miraflores,
Apartado 300, 2795 LINDA-A-VELHA,
Tel. (01)14163160/4163333, Fax. (01)14163174/4163366.

Singapore: Lorong 1, Toa Payoh, SINGAPORE 1231,
Tel. (65)350 2000, Fax. (65)251 6500

South Africa: S.A. PHILIPS Pty Ltd.,
195-215 Main Road Martindale, 2092 JOHANNESBURG,
P.O. Box 7430 Johannesburg 2000,
Tel. (011)470-5911, Fax. (011)470-5494.

Spain: Balmes 22, 08007 BARCELONA,
Tel. (03)301 6312, Fax. (03)301 42 43

Sweden: Kottbygatan 7, Akalla. S-164 85 STOCKHOLM,
Tel. (0)8-632 2000, Fax. (0)8-632 2745

Switzerland: Allmendstrasse 140, CH-8027 ZÜRICH,
Tel. (01)488 2211, Fax. (01)481 77 30

Taiwan: PHILIPS TAIWAN Ltd., 23-30F, 66, Chung Hsiao West
Road, Sec. 1. Taipei, Taiwan ROC, P.O. Box 22978,
TAIPEI 100, Tel. (02)388 7666, Fax. (02)382 4382.

Thailand: PHILIPS ELECTRONICS (THAILAND) Ltd.,
209/2 Sanpavuth-Bangna Road Prakanong,
Bangkok 10260, THAILAND,
Tel. (662)398-0141, Fax. (662)398-3319.

Turkey: Talatpasa Cad. No. 5, 80640 GÜLTEPE/ISTANBUL,
Tel. (0212)279 2770, Fax. (0212)269 3094

United Kingdom: Philips Semiconductors LTD.,
276 Bath road, Hayes, MIDDLESEX UB3 5BX,
Tel. (081)73050000, Fax. (081)7548421

United States: 811 East Arques Avenue, SUNNYVALE,
CA 94088-3409, Tel. (800)234-7381, Fax. (708)296-8556

Uruguay: Coronel Mora 433, MONTEVIDEO,
Tel. (02)70-4044, Fax. (02)92 0601

For all other countries apply to: Philips Semiconductors,
International Marketing and Sales, Building BE-p,
P.O. Box 218, 5600 MD, EINDHOVEN, The Netherlands,
Telex 35000 phtcnl, Fax. +31-40-724825

SCD34 © Philips Electronics N.V. 1994

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

budget no./prinrun/ed./pp16
Document order number:

Date of release: September 1994
12NC

Philips Semiconductors



PHILIPS