

DATA SHEET



TDA1381 DCC write amplifier (WRITE3)

Preliminary specification
File under Integrated Circuits, IC01

September 1994

Philips Semiconductors



PHILIPS

DCC write amplifier (WRITE3)**TDA1381****FEATURES**

- Single 3 V power supply
- Low standby current consumption
- 20 bidirectional current outputs (2 × nine heads)
- Single point main data and auxiliary current setting
- Reduction of power consumption between write pulses
- Soft switching of output currents
- Serial data input
- Timing is compatible with TDA1319T
- Uncommitted operational amplifier available.

**GENERAL DESCRIPTION**

The TDA1381 has been designed to drive an 18-channel inductive recording head which is suitable for the DCC (Digital Compact Cassette) system. The bidirectional current outputs are controlled by a two-wire serial bus. The amplitude of the write current pulses can be set by either voltage or current control. The circuit can be switched to standby mode to minimize supply current consumption.

QUICK REFERENCE DATA

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|-----------------|---|------------|------|------|------|------|
| V_{DD} | supply voltage | | 2.7 | 3.0 | 4.0 | V |
| I_{DD} | supply current | note 1 | – | 9 | 12 | mA |
| $I_{DD(av)}$ | average supply current | note 2 | – | 26.5 | – | mA |
| I_{stb} | total standby current | | – | 0.1 | 0.3 | mA |
| $I_{WDAT(max)}$ | maximum write current for main data channels 0 to 7 | note 3 | 100 | – | – | mA |
| $I_{WAUX(max)}$ | maximum write current for auxiliary channel | note 3 | 115 | – | – | mA |
| $I_{EAUX(max)}$ | maximum erase current for auxiliary channel | note 3 | 153 | – | – | mA |
| $P_{d(av)}$ | average power dissipation | note 2 | – | 80 | – | mW |
| T_{amb} | operating ambient temperature | | –30 | – | +85 | °C |

Notes

1. No head connected; all outputs unloaded; $V_{DD} = 3$ V.
2. In the auxiliary and data write mode; writing DCC data; $I_{WDAT} = 60$ mA; $V_{DD} = 3$ V; $f_{clk} = 3.072$ MHz. Data channels resistively loaded with 6Ω , auxiliary channel resistively loaded with 4Ω between pins 23 and 24, and 37 and 38.
3. Resistors connected in accordance with test circuit of Fig.7.

ORDERING INFORMATION

| TYPE NUMBER | PACKAGE | | |
|-------------|-----------------------|---|----------|
| | NAME | DESCRIPTION | VERSION |
| TDA1381H | TQFP48 ⁽¹⁾ | plastic thin quad flat package; 48 leads; body $7 \times 7 \times 1.4$ mm | SOT313-1 |


Note

1. When using IR reflow soldering it is recommended that the Drypack instructions in the "Quality Reference Handbook" (order number 9398 510 63011) are followed.

DCC write amplifier (WRITE3)

TDA1381

BLOCK DIAGRAM



MKA771

Fig.1 Block diagram.

DCC write amplifier (WRITE3)

TDA1381

PINNING

| SYMBOL | PIN | DESCRIPTION |
|-------------------|-----|---|
| V _{DD} | 1 | supply voltage |
| V _{DD} | 2 | supply voltage |
| AMP(pos) | 3 | operational amplifier non-inverting input |
| WCLK | 4 | write clock input |
| WDATA | 5 | write data input |
| V _{SS} | 6 | ground |
| STANDBY | 7 | standby mode control input |
| AB | 8 | tape sector A or B select input |
| AMPO | 9 | operational amplifier output |
| AMP(neg) | 10 | operational amplifier inverting input |
| V _{DD} | 11 | supply voltage |
| V _{DD} | 12 | supply voltage |
| BJ | 13 | sector B write pulse output J |
| BI | 14 | sector B write pulse output I |
| n.c. | 15 | not connected |
| BH | 16 | sector B write pulse output H |
| BG | 17 | sector B write pulse output G |
| BF | 18 | sector B write pulse output F |
| BE | 19 | sector B write pulse output E |
| BD | 20 | sector B write pulse output D |
| BC | 21 | sector B write pulse output C |
| n.c. | 22 | not connected |
| BB | 23 | sector B write pulse output B |
| BA | 24 | sector B write pulse output A |
| V _{DD} | 25 | supply voltage |
| V _{DD} | 26 | supply voltage |
| V _{SET} | 27 | control voltage input |
| V _{CNTR} | 28 | voltage-to-current conversion setting input |
| V _{SS} | 29 | ground |
| I _{SET} | 30 | control current input |
| V _{SS} | 31 | ground |
| V _{ref} | 32 | reference voltage output |
| R _{BIAS} | 33 | bias current resistor |
| V _{DD} | 34 | supply voltage |
| V _{DD} | 35 | supply voltage |
| n.c. | 36 | not connected |
| AA | 37 | sector A write pulse output A |
| AB | 38 | sector A write pulse output B |
| n.c. | 39 | not connected |
| AC | 40 | sector A write pulse output C |

DCC write amplifier (WRITE3)

TDA1381

| SYMBOL | PIN | DESCRIPTION |
|--------|-----|-------------------------------|
| AD | 41 | sector A write pulse output D |
| AE | 42 | sector A write pulse output E |
| AF | 43 | sector A write pulse output F |
| AG | 44 | sector A write pulse output G |
| AH | 45 | sector A write pulse output H |
| n.c. | 46 | not connected |
| AI | 47 | sector A write pulse output I |
| AJ | 48 | sector A write pulse output J |




Fig.2 Pin configuration.

DCC write amplifier (WRITE3)

TDA1381

FUNCTIONAL DESCRIPTION

The TDA1381 is designed to drive the elements of an 18-channel recording head, containing nine elements for tape sector A and nine elements for sector B. A brief functional description of each block (see Fig.1) is given below.

Decoder

The IC is controlled by the 32-bit wide serial data word which is clocked in at WDATA (pin 5). The clock frequency (WCLK, pin 4) is 3.072 MHz with a clock period of 325 ns. The write pulses are made available at the outputs AA to AJ when tape sector A is selected (pin 8 HIGH) or at the outputs BA to BJ when tape sector B is selected (pin 8 LOW). The principle of connection of the recording head to the IC is illustrated in Fig.4.

The timing sequence of the write pulses is shown in Fig.5. The operating mode of the IC can be set by the first 3 bits of WDATA. The signals TCH0 to TCH7 and TCHAUX determine the direction of the write current. When TCH_n is

HIGH, the current flows as indicated in Fig.4. When TCH_n is LOW current flows in the opposite direction. The various modes of operation are given in Table 1. The standby mode can also be forced by setting the STANDBY input (pin 7) HIGH.

Current control

The write current at the outputs is regulated by the current control circuit. The principle of this circuit is shown in Fig.3.

The value of the current I_{WDAT} can be set using an external voltage V_{SET}, connected between pin 27 and V_{SS}. In this configuration, pin 28 has to be resistively loaded to another voltage source or V_{SS} (see Fig.7). The current control circuit regulates the voltage between pins 27 and 28 to zero. When a resistor R_{SET} is connected between pin 28 and V_{SS}, a current gain factor (G_{if}) can be defined

$$\text{as: } G_{if} = \frac{I_{WDAT}}{\left(\frac{V_{SET}}{R_{SET}}\right)}$$

Table 1 Modes of operation.

| MODE | | WRITE CURRENT | | CONTROL BIT ⁽¹⁾ | | |
|--------------------|-------------------|--------------------|------------------------------------|--|---|-------------------------------------|
| MAIN DATA CHANNELS | AUXILIARY CHANNEL | MAIN DATA CHANNELS | AUXILIARY CHANNEL ⁽³⁾ | TDAPLB ⁽²⁾ (DATA CHANNEL PLAYBACK) | TAUPLB ⁽²⁾ (AUXILIARY CHANNEL PLAYBACK) | TERAUX (AUXILIARY CHANNEL ERASE) |
| Read | read | off | off | 1 | 1 | X |
| Write | read | I _{WDAT} | off | 0 | 1 | X |
| Write | write | I _{WDAT} | A _W × I _{WDAT} | 0 | 0 | 0 |
| Write | erase | I _{WDAT} | A _E × I _{WDAT} | 0 | 0 | 1 |
| Read | write | off | A _W × I _{WDAT} | 1 | 0 | 0 |
| Read | erase | off | A _E × I _{WDAT} | 1 | 0 | 1 |

Notes

1. Where 0 = LOW, 1 = HIGH and X = don't care.
2. When both TDAPLB and TAUPLB are HIGH, the IC is set to the standby mode.
3. A_W and A_E are multiplication factors (see Section "Current control").

DCC write amplifier (WRITE3)

TDA1381




Fig.3 Principle of the write current control circuit.

It is also possible to set the write current by providing a current I_i into I_{SET} (pin 30). In this configuration pin 27 must be connected to V_{SS} and pin 28 must be connected to V_{DD} .

The current gain factor is now defined as: $G_{if} = \frac{I_{W DAT}}{I_i}$

During AUX write (outputs AA, AB or BA, BB active) the output current $I_{W DAT}$ is increased by a factor A_W . During the erase mode of the auxiliary channel (TERAUX = HIGH, see Table 1), the output current $I_{W DAT}$ is increased by a factor A_E .

Outputs

Each channel of the chosen sector is selected in sequence. Depending on the data word, the current is directed forward or reversed through the heads. The outputs that are not selected are kept floating to prevent any incorrect current flow. In HIGH state (one of the switches P is closed) the output is internally connected to V_{DD} . In the LOW state (one of the switches N is closed) the output is connected to a current source.

DCC write amplifier (WRITE3)

TDA1381




Fig.4 Definition of the output currents.

Voltage reference

A reference voltage is available at pin 32. This voltage is derived from a bandgap reference source, and can be used to derive a control voltage for the current control circuit.

Standby

The circuit is set to the standby mode when TDAPLB = 1 and TAUPLB = 1 (see Table 1), or when a HIGH level is applied to pin 7. After a HIGH-to-LOW transition at pin 7,


the IC will remain in the standby mode until TDAPLB = 0 or TAUPLB = 0. When the IC is in the standby mode, the current amplifier is switched off to minimize the power consumption, all write current outputs are floating, and the voltage reference is switched off.

Operational amplifier

An uncommitted operational amplifier is available for use in a tape head temperature compensation circuit with the read IC TDA1380.

DCC write amplifier (WRITE3)

TDA1381



(1) Erase pulses are inverted every other cycle of 32 clock pulses.

Fig.5 Data format and timing sequence of the write pulses.

DCC write amplifier (WRITE3)

TDA1381

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134); all voltages referenced to V_{SS} (pins 6, 29 and 31); all currents are positive into the IC.

| SYMBOL | PARAMETER | CONDITIONS | MIN. | MAX. | UNIT |
|---------------|---|--|-------|----------------|--------------------|
| V_{DD} | supply voltage | | -0.3 | 5.5 | V |
| V_I | input voltage pins 4, 5, 7 and 8 | | -0.3 | 5.5 | V |
| V_n | input voltage on other pins | $V_{DD} + 0.3 \text{ V} < 5.5 \text{ V}$ | -0.3 | $V_{DD} + 0.3$ | V |
| $I_{IW(max)}$ | maximum input current on write pulse outputs (pins 13, 14, 16 to 21, 23, 24, 37, 38, 40 to 45, 47 and 48) | | -200 | +200 | μA |
| $I_{I(max)}$ | maximum input current on supply and ground pins (pins 1, 2, 6, 11, 12, 25, 26, 29, 31, 34 and 35) | | -250 | +250 | μA |
| $I_{n(max)}$ | maximum input current on other pins (pins 3 to 5, 7 to 10, 27, 28, 30, 32 and 33) | | -10 | +10 | μA |
| T_{stg} | storage temperature | | -55 | +150 | $^{\circ}\text{C}$ |
| T_{amb} | operating ambient temperature | | -30 | +85 | $^{\circ}\text{C}$ |
| V_{es} | electrostatic handling | note 1 | -3000 | +3000 | V |
| | | note 2 | -300 | +300 | V |

Notes

- Human body model: equivalent to discharging a 100 pF capacitor through a 1.5 k Ω series resistor.
- Machine model: equivalent to discharging a 200 pF capacitor through a 25 Ω series resistor and a 2.5 μH series inductor.

THERMAL CHARACTERISTICS

| SYMBOL | PARAMETER | VALUE | UNIT |
|--------------|---|-------|------|
| $R_{th j-a}$ | thermal resistance from junction to ambient in free air | 65 | K/W |

DCC write amplifier (WRITE3)

TDA1381

CHARACTERISTICS

$V_{DD} = 3\text{ V}$ (pins 1, 2, 11, 12, 25, 26, 34 and 35 tied together externally); $T_{amb} = 25\text{ °C}$; $f_{clk} = 3.072\text{ MHz}$; measured in test circuit of Fig.7; unless otherwise specified.

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|---|---|-----------------------------|-------------|----------------------|----------------|-----------------|
| Supply | | | | | | |
| V_{DD} | supply voltage | | 2.7 | 3.0 | 4.0 | V |
| I_{DD} | supply current | note 1 | – | 9 | 12 | mA |
| I_{stb} | total standby current | standby mode | – | 0.1 | 0.3 | mA |
| $P_{d(av)}$ | average power dissipation | note 2 | – | 120 | – | mW |
| Digital inputs (pins 4, 5, 7 and 8) | | | | | | |
| V_{IH} | HIGH level input voltage | | $0.7V_{DD}$ | V_{DD} | 5.5 | V |
| V_{IL} | LOW level input voltage | | –0.3 | 0 | $0.3V_{DD}$ | V |
| I_{LI} | input leakage current | | –10 | 0 | +10 | μA |
| t_{su} | WDATA set-up time | see Fig.6 | 30 | – | – | ns |
| t_h | WDATA hold time | see Fig.6 | 30 | – | – | ns |
| Analog inputs/output (pins 27, 28, 30, 32 and 33) | | | | | | |
| V_{SET} | input voltage (pin 27) | | 0.4 | – | $V_{DD} - 1.3$ | V |
| V_{CNTR} | input voltage (pin 28) | | 0.4 | – | $V_{DD} - 1.3$ | V |
| V_{ref} | output reference voltage (pin 32) | $I_o < 500\ \mu\text{A}$ | 1.95 | 2.05 | 2.15 | V |
| G_{if} | current gain factor | with voltage input | 550 | 700 | 850 | |
| | | with current input | 590 | 720 | 850 | |
| Write pulse outputs (pins 13, 14, 16 to 21, 23, 24, 37, 38, 40 to 45, 47 and 48) | | | | | | |
| $I_{WDAT(min)}$ | minimum output current channels 0 to 7 | $f_{clk} = 6.15\text{ MHz}$ | – | – | 20 | mA |
| $I_{WDAT(max)}$ | maximum output current channels 0 to 7 | note 3 | 100 | – | – | mA |
| $I_{AUX(max)}$ | maximum output current auxiliary channel | note 3 | 153 | – | – | mA |
| A_W | relative auxiliary write current increase | | 1.0 | 1.2 | 1.4 | dB |
| A_E | relative auxiliary erase current increase | | 3.0 | 3.7 | 4.4 | dB |
| ΔI_{WDAT} | deviation between main data channels per sector | note 4 | – | – | 0.5 | dB |
| $\frac{\Delta I_{WDAT}}{\Delta T}$ | temperature coefficient of the output currents | note 5 | – | 200×10^{-6} | – | K^{-1} |


DCC write amplifier (WRITE3)

TDA1381

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|---|---|------------|------|------|----------------|------|
| Operational amplifier (pins 3, 9 and 10); note 6 | | | | | | |
| G_o | DC open loop gain | | – | 45 | – | dB |
| B_G | gain bandwidth | | – | 1 | – | MHz |
| V_o | output voltage (pin 9) | | 0.5 | – | $V_{DD} - 1.3$ | V |
| $V_{i(cm)}$ | common mode input voltage (pins 3 and 10) | | 0.85 | – | V_{DD} | V |

Notes

1. No head connected, all outputs unloaded.
2. Auxiliary and data write mode; $I_{W_{DAT}} = 100$ mA.
3. Maximum resistive load of auxiliary channel is 6.5 Ω ; maximum resistive load of data channels is 10 Ω .
4. $20 \log \frac{I_{W_{DAT}(max)}}{I_{W_{DAT}(min)}}$ for channels 0 to 7, $I_{W_{DAT}} = 100$ mA.
5. With constant V_{SET} or I_{SET} (see Fig.7).
6. $R_L > 100$ k Ω ; $C_L < 100$ pF; load connected between pin 9 and V_{SS} .



DCC write amplifier (WRITE3)

TDA1381

TEST AND APPLICATION INFORMATION




Fig.7 Test circuit.

DCC write amplifier (WRITE3)**TDA1381**

SOLDERING**Plastic quad flat-packs**

BY WAVE

During placement and before soldering, the component must be fixed with a droplet of adhesive. After curing the adhesive, the component can be soldered. The adhesive can be applied by screen printing, pin transfer or syringe dispensing.

Maximum permissible solder temperature is 260 °C, and maximum duration of package immersion in solder bath is 10 s, if allowed to cool to less than 150 °C within 6 s. Typical dwell time is 4 s at 250 °C.

A modified wave soldering technique is recommended using two solder waves (dual-wave), in which a turbulent wave with high upward pressure is followed by a smooth laminar wave. Using a mildly-activated flux eliminates the need for removal of corrosive residues in most applications.

BY SOLDER PASTE REFLOW

Reflow soldering requires the solder paste (a suspension of fine solder particles, flux and binding agent) to be

applied to the substrate by screen printing, stencilling or pressure-syringe dispensing before device placement.

Several techniques exist for reflowing; for example, thermal conduction by heated belt, infrared, and vapour-phase reflow. Dwell times vary between 50 and 300 s according to method. Typical reflow temperatures range from 215 to 250 °C.

Preheating is necessary to dry the paste and evaporate the binding agent. Preheating duration: 45 min at 45 °C.

REPAIRING SOLDERED JOINTS (BY HAND-HELD SOLDERING IRON OR PULSE-HEATED SOLDER TOOL)

Fix the component by first soldering two, diagonally opposite, end pins. Apply the heating tool to the flat part of the pin only. Contact time must be limited to 10 s at up to 300 °C. When using proper tools, all other pins can be soldered in one operation within 2 to 5 s at between 270 and 320 °C. (Pulse-heated soldering is not recommended for SO packages.)

For pulse-heated solder tool (resistance) soldering of VSO packages, solder is applied to the substrate by dipping or by an extra thick tin/lead plating before package placement.

DCC write amplifier (WRITE3)

TDA1381

DEFINITIONS

| | |
|---|---|
| Data sheet status | |
| Objective specification | This data sheet contains target or goal specifications for product development. |
| Preliminary specification | This data sheet contains preliminary data; supplementary data may be published later. |
| Product specification | This data sheet contains final product specifications. |
| Limiting values | |
| Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability. | |
| Application information | |
| Where application information is given, it is advisory and does not form part of the specification. | |

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.



The Digital Compact Cassette logo is a registered trade mark of Philips Electronics N.V.

Philips Semiconductors – a worldwide company

Argentina: IEROD, Av. Juramento 1992 - 14.b, (1428)
BUENOS AIRES, Tel. (541)786 7633, Fax. (541)786 9367

Australia: 34 Waterloo Road, NORTH RYDE, NSW 2113,
Tel. (02)805 4455, Fax. (02)805 4466

Austria: Triester Str. 64, A-1101 WIEN, P.O. Box 213,
Tel. (01)60 101-1236, Fax. (01)60 101-1211

Belgium: Postbus 90050, 5600 PB EINDHOVEN, The Netherlands,
Tel. (31)40 783 749, Fax. (31)40 788 399

Brazil: Rua do Rocio 220 - 5th floor, Suite 51,
CEP: 04552-903-SÃO PAULO-SP, Brazil.
P.O. Box 7383 (01064-970).

Tel. (011)821-2333, Fax. (011)829-1849

Canada: PHILIPS SEMICONDUCTORS/COMPONENTS:
Tel. (800) 234-7381, Fax. (708) 296-8556

Chile: Av. Santa Maria 0760, SANTIAGO,
Tel. (02)773 816, Fax. (02)777 6730

Colombia: IPRELENZO LTDA, Carrera 21 No. 56-17,
77621 BOGOTA, Tel. (571)249 7624/(571)217 4609,
Fax. (571)217 4549

Denmark: Prags Boulevard 80, PB 1919, DK-2300 COPENHAGEN S,
Tel. (032)88 2636, Fax. (031)57 1949

Finland: Sinikalliontie 3, FIN-02630 ESPOO,
Tel. (9)0-50261, Fax. (9)0-520971

France: 4 Rue du Port-aux-Vins, BP317,
92156 SURESNES Cedex,
Tel. (01)4099 6161, Fax. (01)4099 6427

Germany: P.O. Box 10 63 23, 20043 HAMBURG,
Tel. (040)3296-0, Fax. (040)3296 213.

Greece: No. 15, 25th March Street, GR 17778 TAVROS,
Tel. (01)4894 339/4894 911, Fax. (01)4814 240

Hong Kong: PHILIPS HONG KONG Ltd., 6/F Philips Ind. Bldg.,
24-28 Kung Yip St., KWAI CHUNG, N.T.,
Tel. (852)424 5121, Fax. (852)428 6729

India: Philips INDIA Ltd, Shivsagar Estate, A Block,
Dr. Annie Besant Rd. Worli, Bombay 400 018
Tel. (022)4938 541, Fax. (022)4938 722

Indonesia: Philips House, Jalan H.R. Rasuna Said Kav. 3-4,
P.O. Box 4252, JAKARTA 12950,
Tel. (021)5201 122, Fax. (021)5205 189

Ireland: Newstead, Clonskeagh, DUBLIN 14,
Tel. (01)640 000, Fax. (01)640 200

Italy: PHILIPS SEMICONDUCTORS S.r.l.,
Piazza IV Novembre 3, 20124 MILANO,
Tel. (0039)2 6752 2531, Fax. (0039)2 6752 2557

Japan: Philips Bldg 13-37, Kohnan2-chome, Minato-ku, TOKYO 108,
Tel. (03)3740 5028, Fax. (03)3740 0580

Korea: (Republic of) Philips House, 260-199 Itaewon-dong,
Yongsan-ku, SEOUL, Tel. (02)794-5011, Fax. (02)798-8022

Malaysia: No. 76 Jalan Universiti, 46200 PETALING JAYA,
SELANGOR, Tel. (03)750 5214, Fax. (03)757 4880

Mexico: 5900 Gateway East, Suite 200, EL PASO, TX 79905,
Tel. 9-5(800)234-7381, Fax. (708)296-8556

Netherlands: Postbus 90050, 5600 PB EINDHOVEN, Bldg. VB
Tel. (040)783749, Fax. (040)788399

New Zealand: 2 Wagener Place, C.P.O. Box 1041, AUCKLAND,
Tel. (09)849-4160, Fax. (09)849-7811

Norway: Box 1, Manglerud 0612, OSLO,
Tel. (022)74 8000, Fax. (022)74 8341

Pakistan: Philips Electrical Industries of Pakistan Ltd.,
Exchange Bldg. ST-2/A, Block 9, KDA Scheme 5, Clifton,
KARACHI 75600, Tel. (021)587 4641-49,
Fax. (021)577035/5874546.

Philippines: PHILIPS SEMICONDUCTORS PHILIPPINES Inc,
106 Valero St. Salcedo Village, P.O. Box 2108 MCC, MAKATI,
Metro MANILA, Tel. (02)810 0161, Fax. (02)817 3474

Portugal: PHILIPS PORTUGUESA, S.A.,
Rua dr. António Loureiro Borges 5, Arquiparque - Miraflores,
Apartado 300, 2795 LINDA-A-VELHA,
Tel. (01)14163160/4163333, Fax. (01)14163174/4163366.

Singapore: Lorong 1, Toa Payoh, SINGAPORE 1231,
Tel. (65)350 2000, Fax. (65)251 6500

South Africa: S.A. PHILIPS Pty Ltd.,
195-215 Main Road Martindale, 2092 JOHANNESBURG,
P.O. Box 7430 Johannesburg 2000,
Tel. (011)470-5911, Fax. (011)470-5494.

Spain: Balmes 22, 08007 BARCELONA,
Tel. (03)301 6312, Fax. (03)301 42 43

Sweden: Kottbygatan 7, Akalla. S-164 85 STOCKHOLM,
Tel. (0)8-632 2000, Fax. (0)8-632 2745

Switzerland: Allmendstrasse 140, CH-8027 ZÜRICH,
Tel. (01)488 2211, Fax. (01)481 77 30

Taiwan: PHILIPS TAIWAN Ltd., 23-30F, 66, Chung Hsiao West
Road, Sec. 1. Taipei, Taiwan ROC, P.O. Box 22978,
TAIPEI 100, Tel. (02)388 7666, Fax. (02)382 4382.

Thailand: PHILIPS ELECTRONICS (THAILAND) Ltd.,
209/2 Sanpavuth-Bangna Road Prakanong,
Bangkok 10260, THAILAND,
Tel. (662)398-0141, Fax. (662)398-3319.

Turkey: Talatpasa Cad. No. 5, 80640 GÜLTEPE/ISTANBUL,
Tel. (0212)279 2770, Fax. (0212)269 3094

United Kingdom: Philips Semiconductors LTD.,
276 Bath road, Hayes, MIDDLESEX UB3 5BX,
Tel. (081)73050000, Fax. (081)7548421

United States: 811 East Arques Avenue, SUNNYVALE,
CA 94088-3409, Tel. (800)234-7381, Fax. (708)296-8556

Uruguay: Coronel Mora 433, MONTEVIDEO,
Tel. (02)70-4044, Fax. (02)92 0601

For all other countries apply to: Philips Semiconductors,
International Marketing and Sales, Building BE-p,
P.O. Box 218, 5600 MD, EINDHOVEN, The Netherlands,
Telex 35000 phtcnl, Fax. +31-40-724825

SCD34 © Philips Electronics N.V. 1994

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

Philips Semiconductors



PHILIPS