

THE CORVUS CONCEPT
PASCAL
REFERENCE MANUAL

★ ★ **CORVUS SYSTEMS**
★ ★

DISCLAIMER OF ALL WARRANTIES & LIABILITIES

Corvus Systems, Inc. makes no warranties, either expressed or implied, with respect to this manual or with respect to the software described in this manual, its quality, performance, merchantability, or fitness for any particular purpose. Corvus Systems, Inc. software is sold or licensed "as is." The entire risk as to its quality or performance is with the buyer and not Corvus Systems, Inc., its distributor, or its retailer. The buyer assumes the entire cost of all necessary servicing, repair, or correction and any incidental or consequential damages. In no event will Corvus Systems, Inc. be liable for direct, indirect, incidental or consequential damages, even if Corvus Systems, Inc. has been advised of the possibility of such damages. Some states do not allow the exclusion or limitation of implied warranties or liabilities for incidental or consequential damages, so the above limitation may not apply to you.

Every effort has been made to insure that this manual accurately documents the operation and servicing of Corvus products. However, due to the ongoing modification and update of the software along with future products, Corvus Systems, Inc. cannot guarantee the accuracy of printed material after the date of publication, nor can Corvus Systems, Inc. accept responsibility for errors or omissions.

NOTICE

Corvus Systems, Inc. reserves the right to make changes in the product described in this manual at any time without notice. Revised manuals and update sheets will be published as needed and may be purchased by writing to:

Corvus Systems, Inc.
2029 O'Toole Avenue
San Jose, CA 95131

Telephone: (408) 946-7700
TWX 910-338-0226

This manual is copyrighted and contains proprietary information. All rights reserved. This document may not, in whole or in part be copied, photocopied, reproduced, translated or reduced to any electronic medium or machine readable form without prior consent, in writing, from Corvus Systems, Inc.

Copyright© 1982 by Corvus Systems, Inc. All rights reserved.

Mirror® patent pending. The Corvus Concept™, Transporter™, Corvus OMNINET™, Corvus Logical™, Time Travel Editing™, EdWord™, Constellation™, Corvus™, Corvus Systems™, Personal Workstation™, Tap Box™, Passive Tap Box™, Active Junction Box™, Omninet Unit™ are trademarks of Corvus Systems, Inc.

FCC WARNING

This equipment generates, uses, and can radiate radio frequency energy and if not installed and used in accordance with the instruction manual, may cause interference to radio communications. As temporarily permitted by regulation it has not been tested for compliance with the limits for Class A computing devices pursuant to Subpart J of Part 15 of FCC Rules, which are designed to provide reasonable protection against such interference. Operation of this equipment in a residential area is likely to cause interference in which case the user at his own expense will be required to take whatever measures may be required to correct the interference.

* CORVUS SYSTEMS

* _____

* *

* The Corvus Concept Pascal
 Reference Manual

PART NO. : 7100-02827

DOCUMENT NO. : CCC/34-33/1.1

RELEASE DATE : February, 1982

CORVUS CONCEPT (TM) is a trademark of Corvus Systems, Inc.

Table of Contents

Chapter 1 Introduction	1
1.1 Overview of the Pascal Language	2
1.2 Metalanguage	6
1.3 Elementary Lexical Constructs	7
1.3.1 Alphabet	7
1.3.2 Pascal Identifiers	8
1.3.3 Numbers	8
1.3.4 Pascal Strings	9
1.3.5 Pascal Labels	10
1.3.6 Basic Symbols	11
1.3.7 Conventions for Spaces	13
1.3.8 Comments	13
Chapter 2 Defining Data Types	15
2.1 Defining Constants	15
2.1.1 Predefined Constants	16
2.2 Standard Types	17
2.3 Defining Data Types	18
2.4 Simple Types	19
2.4.1 Scalar Types	19
2.4.2 Subrange Types	20
2.5 Structured Types	20
2.5.1 Array Types	21
2.5.2 String Types	23
2.5.3 Record Types	24
2.5.4 Set Types	25
2.5.5 File Types	26
2.6 Pointer Types	27
2.7 Type Identity and Assignment Compatibility	28
2.7.1 Identical Types	28
2.7.2 Assignment Compatible Types	29
Chapter 3 Declaring and Referencing Variables	31
3.1 Declaring Variables	31
3.2 Predeclared Variables	32

3.3	Establishing Variables	32
3.4	Lifetimes of Variables	33
3.4.1	Global Variables	33
3.4.2	Lifetime of Formal Parameters	33
3.4.3	Lifetime of Dynamic Variables	33
3.5	Referencing or Accessing Variables	34
3.5.1	Entire Variables	34
3.5.2	Component Variables	34
3.5.2.1	Referencing Indexed Variables	35
3.5.2.2	Referencing Strings	35
3.5.2.3	Referencing Fields of Records	36
3.5.2.4	Referencing File Buffers	36
3.5.3	Pointer Referenced Variables	37
Chapter 4	Expressions	39
4.1	Operators in Expressions	40
4.2	Address Evaluation Operator	40
4.3	NOT Operator	40
4.4	Multiplying Operators	41
4.5	Adding Operators	42
4.6	Sign Operators	43
4.7	Relational Operators	44
4.7.1	Comparison of Scalars	44
4.7.2	Comparison of Booleans	45
4.7.3	Direct Pointer Comparison	45
4.7.4	String Comparison	45
4.7.5	Set Comparison	46
4.7.6	Non-Comparable Types	47
4.8	Out of Range Values	47
4.9	Order of Evaluation in Expressions	47
4.10	Compile Time Constant Expressions	48
4.10.1	Dead Code Elimination	48
Chapter 5	Statements	51
5.1	Statement Labels	51
5.1.1	Scope Of Statement Labels	51
5.2	Assignment Statements	51
5.2.1	Assignments to Variables and Functions	52

5.3 Procedure Reference Statement	52
5.4 Structured Statements	53
5.4.1 BEGIN .. END - Compound Statements	53
5.4.2 IF .. THEN .. ELSE Statements	53
5.4.3 CASE Statements	55
5.4.4 WHILE .. DO Statements	56
5.4.5 REPEAT .. UNTIL Statements	57
5.4.6 FOR .. DO Statements	57
5.5 The WITH Statement	59
5.6 The GOTO Statement	60
Chapter 6 Input and Output	61
6.1 General File Handling Procedures	61
6.1.1 The File Buffer Variable	61
6.1.2 GET - Get Component from File	62
6.1.3 PUT - Append Component to a File	63
6.1.4 RESET - Position to Start of File	63
6.1.5 REWRITE - Create or Overwrite a File	64
6.1.6 The Buffering Option on RESET and REWRITE	64
6.2 Text File Handling Procedures	65
6.2.1 READ and READLN Intrinsic	65
6.2.2 READ from a file of any type	66
6.2.3 WRITE and WRITELN Intrinsic	66
6.2.4 Write Parameters	67
6.2.4.1 Integer Element	68
6.2.4.2 Real or Double Element	68
6.2.4.3 Scalar Subrange Element	69
6.2.4.4 Character Element	69
6.2.4.5 String Element or Packed Array of Char	69
6.2.4.6 Boolean Element	69
6.2.5 WRITE to file of any type	70
6.2.6 SEEK - Random Access to Typed Files	70
6.2.7 CLOSE - Close a File	71
6.3 Block Input Output Intrinsic	72
6.3.1 BLOCKREAD - Read Block from File	72
6.3.2 BLOCKWRITE - Write Block to File	73
6.4 Unit Input Output	73

6.4.1 UNITBUSY - Check if Unit Busy	74
6.4.2 UNITCLEAR - Initialize the Unit	74
6.4.3 UNITSTATUS - Get Status of Device	74
6.4.4 UNITREAD - Read from a Unit	75
6.4.5 UNITWRITE - Write from a Unit	76
6.4.6 Notes On UNIT Input and Output	76
6.5 IORESULT - Return Input-Output Result	77
Chapter 7 Program Structure	79
7.1 Compilation Units	79
7.2 Declarations and Scope of Identifiers	81
7.3 Program Heading	83
7.3.1 Predeclared Variables	83
7.3.1.1 ARGC and ARGV - Access to Command Line	84
7.4 Declarations	84
7.4.1 Label Declarations	84
7.4.2 Constant Definition	84
7.4.3 Type Definition	85
7.4.4 Variable Declaration	85
7.5 Procedure and Function Declaration	85
7.5.1 External and Forward Attributes	87
7.5.2 Parameters for Procedures and Functions	87
7.5.2.1 Value Parameters	88
7.5.2.2 Variable Parameters	88
7.5.2.3 Procedure and Function Parameters	88
Chapter 8 Standard Procedures and Functions	91
8.1 String Manipulation Facilities	91
8.1.1 LENGTH - Determine String Length	92
8.1.2 COPY - Copy a Substring	92
8.1.3 CONCAT - Concatenate Strings	93
8.1.4 POS - Match a Substring in a String	94
8.1.5 SCANEQ and SCANNE - Scan for Character	94
8.1.6 DELETE - Delete Characters from String	95
8.1.7 INSERT - Insert Characters into String	96
8.2 Storage Allocation Procedures	96

8.2.1	NEW - Allocate Storage	97
8.2.2	DISPOSE - Dispose of Allocated Storage	98
8.2.3	MARK - Mark Position of Heap	98
8.2.4	RELEASE - Release Allocated Memory	99
8.2.5	MEMAVAIL - Determine Available Memory	99
8.3	Arithmetic Functions	99
8.3.1	ABS - Compute Absolute Value	99
8.3.2	SQR - Compute Square of a Number	100
8.3.3	SIN - Trigonometric Sine	100
8.3.4	COS - Trigonometric Cosine	100
8.3.5	ARCTAN - Trigonometric Arctangent	100
8.3.6	EXP - Compute Exponential of Value	100
8.3.7	PWROFTEN - Compute Ten to a Power	100
8.3.8	LN - Natural Logarithm of Value	101
8.3.9	SQRT - Square Root of Value	101
8.4	Predicates or Boolean Attributes	101
8.4.1	ODD - Test Integer for Odd or Even	101
8.4.2	EOLN - Determine if End of Line Read	101
8.4.3	EOF - Determine if End of File Read	101
8.5	Value Conversion Functions	102
8.5.1	TRUNC - Truncate to Nearest Integer	102
8.5.2	ROUND - Round to Nearest Integer	102
8.5.3	ORD - Convert Type to Integer Value	102
8.5.4	ORD4 - Convert to Long Integer	103
8.5.5	CHR - Integer to Character Representation	103
8.6	Other Standard Functions	103
8.6.1	SUCC - Determine Successor of Value	103
8.6.2	PRED - Determine Predecessor of Value	103
8.7	Miscellaneous Low Level Routines	104
8.7.1	MOVELEFT and MOVERIGHT	104
8.7.2	FILLCHAR - Fill A Storage Region With A Character	105
8.7.3	SIZEOF - Determine Size of Data Element or Type	105
8.7.4	POINTER - Convert Integer Expression to Pointer	106
8.8	Control Procedures	106

8.8.1 EXIT - Exit from Procedure	106
8.8.2 HALT - Terminate Program with Return Value	107
8.8.3 CALL - Call up Another Program	107
Chapter 9 Pascal Compile Time Options	109
Appendix A Messages from the Pascal System	113
A.1 Compile Time Lexical Errors	113
A.2 Compile Time Syntactic Errors	113
A.3 Compile Time Semantic Errors	114
A.4 Specific Limitations of the Compiler	116
A.5 Input Output Errors	117
A.6 Code Generation Errors	117
A.7 IORESULT Error Codes	117
A.8 Codes Returned From the HALT Procedure	118
Appendix B Pascal Language Summary	119
B.1 Predefined Identifiers	119
B.2 Pascal Syntax Definitions	120
Appendix C Relationships to ISO Pascal	129
Appendix D Relationships to UCSD Pascal	131
D.1 Differences from UCSD Pascal	131
Appendix E Data Representations	135
E.1 Storage Allocation	135
E.2 Representation of Integers	137
E.3 Representation of Reals and Doubles	137
E.4 Representation of Extreme Numbers	138
E.5 Representation of Sets	144
E.6 Representation of Arrays	145
E.7 Packing Methods	146
E.8 Parameter Passing Mechanism	150
E.9 Limitations On Size of Variables	151
E.10 Compiler Generated Linker Names	151
Appendix F Bibliography	153
Appendix G Pascal on the UNIX System	155
G.1 Running Pascal On the UNIX System	155
G.2 UNIX System Dependencies	162
G.3 Interfacing Pascal to UNIX C Programs	164

Chapter 1**Introduction**

Pascal is a "modern" computer programming language designed by Professor Niklaus Wirth (of the Eidgenossische Technische Hochschule, Zurich, Switzerland) in reaction to the perceived disorder of contemporary programming languages. Originally intended as an aid to teaching rigorous and disciplined computer programming, Pascal has since gained international acceptance as a programming language for a multiplicity of applications ranging from writing compilers (including Pascal compilers) to controlling a grain elevator. Pascal is not an acronym for anything. Pascal is named after Blaise Pascal, the 17th century philosopher and mathematician.

Pascal is one of the many derivatives of Algol-60. Algol introduced the notion of nested control structures such as if..then..else that form the basis of today's structured programming methods. In addition to the control structures, Pascal goes one step further with the notion that data structures play at least as important a part in rigorous programming as do control structures. The absence of an adequate data structuring notation was seen as Algol's most obvious deficiency.

Pascal's major contribution to the advance in programming technology is the concept of user definable data types. This provides powerful facilities for defining new data types and data structures in terms of a few basic types.

This reference manual describes the Pascal language as implemented by Silicon Valley Software Incorporated. Throughout, the term "SVS Pascal" means the Pascal implementation as described in this reference manual.

1.1 Overview of the Pascal Language

A Pascal program consists of a series of declarations and statements. Declarations serve to define program objects. Statements determine actions to be performed upon such objects. These two things, declarations and statements, serve to describe a computer program.

Definable Pascal objects include variables, functions, procedures, and files. Declaring an instance of an object requires an identifier and, usually, a type description. An object's identifier serves to identify that object so that it can be referenced later. The type associated with an object defines its operational characteristics, and in some cases, indicates a referential notation.

It is important to note that all user supplied objects must be fully described, especially as to their type. Pascal is unlike many other programming languages in that it does not supply any default attributes for undeclared identifiers.

One of Pascal's strongest points is the ability for users to define new types. Pascal supplies a small number of predefined or basic types, such as integer. Pascal then supplies notations for defining new (user defined) types, both in terms of the basic types, and in terms of other user defined types.

A type can be described directly in a declaration, or, a type can be referenced by a type identifier which, in turn, must be defined by another explicit type declaration.

In general, a Pascal object is only subject to operations that lie inside of a domain indicated by its type. For example, most binary operators are restricted to objects of the same type (for instance, characters and integers cannot be added directly). These operational constraints are rigid, as are the rules for type identity and assignment compatibility. Departures from the rules have to be spelled out explicitly in terms of conversion functions.

The basic data type is the scalar type, often referred to as an enumerated type. A scalar definition indicates an ordered set of values, where each identifier in the set stands for a specific value.

In addition to the definable scalar types, there are six standard basic types, namely integer, longint, char(acter), real, double, and Boolean types. With the exception of the Boolean type, their values are denoted by numbers or quoted characters, instead of by identifiers.

A type may also be defined as a subrange of a scalar type by indicating the lower and upper bounds of the subrange.

Structured types are aggregates, defined by describing the types of their components, and by indicating a structuring method. The structuring methods differ in the way that components of a structured variable are selected, and the operations in which they can participate. Pascal provides five basic ways to construct an aggregate object, namely array, record, set, string, and file.

An array has components which are all of the same type. A component is selected by a computable index. The type of such an index must be a scalar, and is determined at the time the array is declared.

A record has components called fields which need not be all of the same type. A field selector for a component of a record is an identifier that is uniquely associated with the component to be selected. Unlike an array element index, a field selector is not a computable quantity. The field selectors are defined at the same time that the record is defined. A record type may consist of several variants. This means that different variables of the same record type may actually contain different structures. That is, the number and types of the components may differ between different instances of the same type. The particular variant which the specific variable assumes is indicated by a field called the tag field, common to all variants of that record.

A set is a homogeneous collection of elements selected from some base type. The base type might be a user defined scalar type or a subrange of some scalar type such as integer or char. A Pascal set is the collection of values comprising the powerset of the base type. That means, the set of all subsets of that base type.

A string data type is a sequence of characters whose length can vary dynamically during program execution. A string has a maximum length (its static length) which is determined when it is defined. There are a rich set of intrinsic procedures and functions to manipulate strings.

A file is a sequence of components of the same type. The sequence is normally associated with external storage or input

and output devices, so that files are the means whereby a Pascal program communicates with the world outside of the computer. Files can be sequential such that there is a natural ordering, and only one component of the file is accessible at any one time, or they can be random, such that any given component of the file is accessible on demand.

Explicitly declared variables are called static, in that they are known at compile time (lexically static). A declaration associates an identifier with the variable. The identifier is subsequently used to refer to that variable. In contrast to static variables, dynamic variables are created by executable statements. Such a dynamic creation of a variable yields a pointer (which substitutes for an explicit declaration), that is subsequently used to refer to the dynamically allocated variable. Any given pointer variable may only assume values pointing to variables of a specific type, and is said to be bound to that type. A pointer may be assigned to other pointer variables of the same type. Any pointer can assume the value nil - a universal pointer that is not bound to a specific type.

The assignment statement is the fundamental Pascal statement. It assigns a newly computed value to a variable or a component of a variable. New values are obtained by evaluating expressions. Expressions consist of variables, constants, sets, operators, and functions, operating on specified objects, to produce new values. Operands of expressions are either declared in the program, or are standard Pascal entities. Pascal defines a fixed set of operators that can be considered to define a mapping from given operand types into result types. Operators encompass the four groups: (1) arithmetic operators, (2) Boolean operators, (3) set operators, and (4) relational operators.

A procedure statement causes execution of a designated procedure. This is known as activating or calling the procedure. Assignment and procedure statements are the basic elements of structured statements. Structured statements specify sequential, selective, or repetitive execution of their component statements. Sequential execution is obtained by the compound statement; Conditional and selective execution by the if statement and the case statement; Repetitive execution is specified by the while statement, the repeat statement, or the for statement.

A statement can be given a name (an identifier), and subsequently be referenced via that name. The statement is then called a procedure, and its declaration is a procedure declaration. A procedure declaration can itself contain type declarations, variable declarations, and further procedure declarations. These subsequent declarations can only be referenced within that procedure, and are thus said to be local

to the procedure. The program text that comprises a procedure body is called the scope of any identifiers declared local to that procedure. Since procedures may be declared local to other procedures, scopes may be nested. Objects declared in the main program block, not local to any procedure, are said to be global, in that their scope is that of the entire program.

A procedure can have a number of parameters (determined at procedure declaration time), each parameter being denoted by an identifier called the formal parameter. When a procedure is activated, each of the formal parameters has an actual quantity substituted such that that quantity is accessed by reference to the formal parameter identifier. These quantities are called actual parameters. There are three sorts of parameters, namely value parameters, variable parameters, and procedure or function parameters. A value parameter is an actual parameter which is evaluated once. The formal parameter then represents a local variable conveniently initialized to the value of the actual parameter. In the case of a variable parameter, the actual parameter is a variable - the formal parameter actually references and can alter that variable. Possible array indexes are evaluated before activation of the procedure or function. In the case of a procedure or function parameter, the actual parameter is a procedure or function identifier.

Functions are declared in the same way as procedures. The difference is that a function returns a value. Pascal functions have intuitive similarities to the mathematical notion - a function is a computational entity that is applied to some arguments and generates a result. Pascal functions differ from the rigorous mathematical notion of functions in that they can have side effects. The type of the returned value must be specified as part of the function declaration. Functions can only return scalar types or pointer types. A function reference must appear in the context of an expression.

Pascal procedures and functions are inherently recursive. That means that a procedure or function can call itself anew before the current activation is complete. On each activation, a fresh set of local data is created. Recursive activation can be direct (the reference is contained within the procedure or function itself) or indirect (the reference is from another procedure or function which in turn is referenced from the current procedure or function).

1.2 Metalanguage

A "metalanguage" is a collection of notations that describe another language. In this case the language being described is Pascal. The metalanguage used in this manual to describe Pascal is a modified version of the ubiquitous Backus-Naur Form, or BNF (first used to describe Algol). A description of the metalanguage follows.

Syntactic constructs enclosed between "angle brackets" < and > define the basic language elements. Every language construct should eventually be defined in terms of basic lexical constructs defined in the remainder of this chapter.

A construct appearing outside the angle brackets stands for itself, that is, it is supposed to be self denoting. Such a construct is known as a terminal symbol. Terminal symbols and reserved words appear in **bold face text** throughout this manual.

The symbol ::= is to be read "defined as".

The symbol .. means "through", indicating an ordered sequence of things where only the start and end elements are specified. (The reader is left to infer the middle elements). For example, the notation 'a' .. 'z' means "the ordered collection starting with the letter 'a', ending with the letter 'z', and containing the letters 'b', 'c'....'x', 'y' in between". In other words, all the lower case letters.

The "vertical bar" symbol | is read as "or". It separates sequences of elements that represent a choice of one out of many.

The metalanguage construct {...} (elements inside braces) enclose elements which are to be repeated "zero to many times". Although the braces are also used as one of the forms of comment delimiters in Pascal, this should not cause any ambiguity. The one case where ambiguity would occur is in the definition of comments, and this is explicitly pointed out at that time.

It is recognized that the syntactic descriptions are not completely rigorous in that they do not cover semantic issues. For example, the syntactic definition of a decimal number does not mention how big a number can be. Where the formal descriptions fall short they are augmented with narrative English prose.

1.3 Elementary Lexical Constructs

Pascal language lexical units - identifiers, basic symbols, and constants - are constructed from one or more (juxtaposed) elements of the alphabet described below.

1.3.1 Alphabet

SVS Pascal uses an extended form of the ASCII character set for all text related processing. ASCII is the American Standard Code for Information Interchange. There are 128 characters in the ASCII character set: 52 letters (upper case 'A' thru 'Z', and lower case 'a' thru 'z'), 10 digits, space (often called "blank"), 33 "control codes" (such as "carriage return" and "line feed"), and 32 graphic characters such as colon, equals sign, and so on. Pascal also allows an additional 128 values to be used as data values, for a total of 256 possible data values.

The Pascal compiler recognizes the following alphabet or character set:

```

<letter> ::= 'A' .. 'Z', 'a' .. 'z', and '_'
<digit>  ::= '0' .. '9'
<hex digit> ::= <digit> | 'a' .. 'f' | 'A' .. 'F'
<ASCII graphic characters> ::= ! " # $ % & ' ( ) * =
                               + - , . / < > ? \ [
                               @ ^ | ~ ` { } ; : ]

```

Note that the definition of <letter> above includes the underline character.

1.3.2 Pascal Identifiers

Pascal Identifiers serve to denote constants, variables, procedures, and other language objects.

```
<identifier> ::= <letter> { <letter> | <digit> }
```

A Pascal identifier must start with a letter or an underline character. It can contain letters, digits, and the underline character. The underline is usually used to mark off spaces in the identifier to provide for readable and meaningful names. A Pascal identifier may be any length, but only the first 31 characters are significant to the compiler. Upper and lower case letters are all "folded" to a single case in the compiler, making them equivalent.

Examples of Identifiers

here_and_there	August_1979	Steve_and_Jeff
_X25	Tau_Epsilon_Xi	DragonsEgg
UPanddown	upandDOWN	upANDdown

The last three identifiers in the examples are equivalent because the compiler folds letters to a single case.

Examples of Invalid Identifiers

```
1st_character_must_be_a_letter
mustn't_have_odd_#$_[_characters_in_it
```

1.3.3 Numbers

Numbers are used to denote **integer**, **real**, and **double** data elements. Integers are assumed to be in the decimal number base, unless designated as a hexadecimal number.

```
<unsigned integer> ::= <digit> {<digit>}
```

```
<unsigned real> ::=
| <unsigned integer>.<unsigned integer>
| <unsigned integer>.<unsigned integer>E<scale factor>
| <unsigned integer>E<scale factor>
| <unsigned integer>.<unsigned integer>D<scale facto
```

```

      | <unsigned integer>D<scale factor>
<unsigned number> ::= <unsigned integer> | <unsigned real>
      <scale factor> ::= <unsigned integer> | <sign><unsigned integer>
      <sign> ::= + | -
<hex number> ::= $<hex digit> {<hex digit>}

```

Hexadecimal numbers are considered unsigned, unless they are explicitly written as 32-bit values with the most significant bit a one. For instance, the value \$ffff is 65535 and not -1. The value \$fffffff is a negative number.

integer numbers are represented internally in the two's complement notation. As a consequence, there is one more negative integer than there are positive integers.

Values of type **double** are designated by a letter **D** preceding the exponent part of the number.

Examples of Valid Numbers

666	{	unsigned decimal integer	}
+99 -457		signed decimal numbers	
\$3e8		a hexadecimal number	
0.0		the real number zero	
3.14159	{	a double number	}
1.23D10			

Examples of Invalid Numbers

5.	{	should be a digit after the point	}
.618		should be a digit before the point	
5.E10		should be a digit after the point	
2FC9	{	Invalid decimal number	}
F034		An identifier, not a hex number	

1.3.4 Pascal Strings

Sequences of characters enclosed in apostrophes are called **strings**. Strings of one character are constants of type **char**. A string of "n" characters, where "n" is greater than one, is an ambiguous constant that is either a **string** value, or is a value of the type **packed array** [1 .. n] of **char**; The exact type of such a string constant is determined from the context in which it

appears.

A string constant which is just simply two juxtaposed apostrophes `' '` represents a variable string constant of length zero.

SVS Pascal provides for entering any character value into a string by coding its two-digit hexadecimal value preceded by a reverse slash `\`. This means that non-printing characters such as "BEL" and "ETX" may be entered into a string. A `\` sign followed by a non-hexadecimal digit is simply that character. Thus `\Y` is equivalent to `'Y'`, `\\` represents `'\'` and `\3X` represents `'\03X'`. This last case is interesting in that leading zeros are implicit in the hexadecimal number if there is only one hexadecimal digit followed by a non-hexadecimal digit.

An apostrophe in a string is represented by two juxtaposed apostrophes. The rules for reverse slash character representations above means that an apostrophe can also be represented by the string `'\''`, or even more rebarbatively by the string `'\27'`.

```
<string> ::= '<character> {<character>}'
```

```
<character value> ::= \

```

Examples of Strings

```
'This is a string constant'
```

```
'This string has an embedded ' ' apostrophe'
```

```
'here is how to get a \07 bell character in a string'
```

```
'to get a back slash, just type \\'
```

1.3.5 Pascal Labels

A label is used to mark statements as the potential target of a `goto` statement.

Pascal labels are unsigned integer constants in the range 0 .. 9999.

```
<label> ::= <unsigned integer>
```

1.3.6 Basic Symbols

Pascal has a set of "basic symbols" which the compiler uses for specific purposes in the language. These basic symbols include selected identifiers (reserved words), graphic characters, and pairs of graphic characters. These basic symbols are used as keywords, operators, delimiters and separators. Such symbols are introduced throughout the body of this manual.

Note that user-defined identifiers may not be the same as any Pascal reserved word.

Identifiers (reserved words) used as basic symbols are shown in this manual in bold faced typefont. For example, **procedure**, **else**, and **type** are Pascal reserved words.

There are two lists of basic symbols shown below. One is a list of Pascal reserved words and the other is a list of the special graphic symbols that Pascal uses.

Pascal Reserved Words

and	else	interface	procedure	unit
array	end	label	program	until
begin	file	mod	record	uses
case	for	nil	repeat	var
const	function	not	set	while
div	goto	of	string	with
do	if	or	then	
	implementation	otherwise	to	
downto	in	packed	type	

Pascal Special Symbols

- + Adding Operator.
- Subtracting Operator.
- * Multiplying Operator.
- / Division Operator (for **real** and **double** data types).
- := Assignment Operator.
- . Terminates a Pascal Compilation Unit; Separates integer from fraction in a **real** or **double** number; Indicates reference to a field of a record.
- , Separates items in lists.
- ; Statement and Declaration Separator.
- : used after case labels, statement labels, variable and parameter descriptions.
- ' string delimiter.
- = Relational equality operator; Used in constant and type definition.
- <> Relational operator for inequality.
- < Relational operator for "less than".
- <= Relational operator for "less than or equal to".
- >= Relational operator for "greater than or equal to".
- > Relational operator for "greater than".
- (and) encloses lists of elements; encloses parts of expressions that are to be considered indivisible factors.
- [and] encloses array subscripts and lists of set elements.
- { and } comment delimiters.
- (* and *) are an alternative form of comment delimiters.
- ^ pointer dereference operator.

.. indicates a range of elements.

1.3.7 Conventions for Spaces

Spaces (also called blanks) are used to separate lexical items. Identifiers, reserved words and constants must not abut each other, neither may they contain embedded spaces. Multiple-character basic symbols such as <= must not contain embedded spaces.

Other than that, spaces may be used freely (to improve program readability for instance). They have no effect, outside of character and string constants, where a space represents itself.

1.3.8 Comments

Comments in Pascal may appear anywhere that a space may appear, and in fact, serve the same purpose as do spaces. But note that a comment within a string constant is part of the string constant and is not really a comment. Pascal comments are enclosed between braces {...} or between the characters (* and *).

```
<comment> ::= { <any printable characters except ">"> }
              | (* <any printable characters except "*"> *) *
```

In the description above, the braces enclosing the comment are the comment delimiters, not metalanguage symbols.

For historical reasons, Pascal accepts two forms of comment delimiters. The open and close braces { } can be used where the character set provides such. Most modern computer systems and terminals accommodate those characters. Those systems which do not accommodate the full ASCII character set can use the alternative forms of (* and *) to delimit comments.

Comments that start with one kind of opening delimiter must end with the corresponding closing delimiter. For example:

```
{ this Pascal comment is enclosed in braces }
(* this comment uses the alternative delimiter *)
{ this Pascal comment would go on for ever because *}
(* does not close the comment. For that we need a
closing brace }
```

Pascal comments can span multiple lines, thus providing a "block comment" capability.

Chapter 2

Defining Data Types

One of Pascal's major attractions is the ease with which users can describe and manipulate data. An important aspect of structured programming technology is the ability to structure data as well as control statements. This is provided in Pascal through the notion of a data type.

A type defines a collection of values that a variable, constant or expression may take on. A type has an associated size, but of itself reserves no storage space. Storage is only reserved when a variable is declared as an instance of that type. Although Pascal data types can be quite complex, they are ultimately composed of simple unstructured components. An example is the predefined type integer. Its size is two bytes (16 bits). The set of values it contains is -32768, ..., -1, 0, 1..., 32767.

In addition to having a size and a set of values, a type has a collection of operations in which values of that type can participate.

Pascal provides a number of predefined types (some of which were described in chapter 1), as well as the means for users to define their own types. Section 2.2 of this chapter describes all predefined Pascal types.

Type constructors are the means by which users can define their own types. Structured type constructors facilitate the definition of new and larger types based upon other existing types as components.

2.1 Defining Constants

A literal constant is a value that denotes itself - its value is manifest from its appearance. The integer 1776 and the string 'Manila' are literal constants. A constant definition introduces an identifier that is a synonym for a constant. Using the

identifier is equivalent to using the associated literal constant. Whereas the string "3.14159" is a literal constant, an identifier called "Pi" could be defined which is a synonym for the number. The identifier is then known as a constant identifier, or just a constant.

```

<constant identifier> ::= <identifier>

      <constant> ::= <unsigned number>
                    | <sign> <unsigned number>
                    | <constant identifier>
                    | <sign> <constant identifier>
                    | <string>

<constant definition> ::= <identifier> = <constant>;
    
```

The definition above means that a constant may be defined to be another constant, but prohibits constant expressions.

2.1.1 Predefined Constants

Pascal provides three constants that are automatically declared as part of the language. The three constants are:

- true** Represents the truth value for a Boolean type.
- false** Represents the falsity value for a Boolean type.
- maxint** An integer constant representing the largest integer that Pascal can store. Maxint is currently defined as 32767.

Examples of Constant Definitions

<pre> Liters_per_bottle = 0.750; Bottles_per_Case = 12; first_vowel = 'a'; Winery = 'Chateau Montelena'; Carriage_Return = '\0d'; </pre>	<pre> { standard bottle is 750 ml standard case a char constant a string constant carriage return character } </pre>
--	--

2.2 Standard Types

SVS Pascal has eight predefined types available:

integer integer type represents an implementation defined subset of the integers. It is equivalent to a subrange defined by a type definition that looks like:

```
integer = -32768 .. 32767
```

The **integer** data type therefore occupies 16 bits of data storage.

longint is a long integer type. It is equivalent to a subrange defined by a type definition that looks like:

```
longint = -2147483648 .. 2147483647
```

The **longint** data type therefore occupies 32 bits of data storage.

real real type is a subset of the continuum of real numbers. Reals are represented in the "floating point" format which consists of a fractional part (a mantissa) and an exponent. The range of real numbers is approximately $-3.4E38 .. +3.4E38$, with a precision of approximately seven decimal places. In addition, the real data type can take on "extreme values", such as plus infinity, minus infinity, and "Not a Number" (abbreviated NaN), which arise from overflow and division by zero. There is a detailed discussion of extreme values in appendix E - "Data Representations".

double double type is a double precision form of the real data type described above, and is a subset of the continuum of real numbers. Double numbers are represented in the "floating point" format which consists of a fractional part (a mantissa) and an exponent. The range of double numbers is approximately $-1.8D308 .. +1.8D308$, with a precision of approximately 15 decimal places. In addition, the double data type can

take on "extreme values", such as plus infinity, minus infinity, and "Not a Number" (abbreviated NaN), which arise from overflow and division by zero. There is a detailed discussion of extreme values in appendix E - "Data Representations".

Boolean Boolean type represents the ordered set of "truth values" whose constant denotations are **false** and **true**. **Boolean** is conceptually equivalent to an ordinal type specified by a type definition that looks like:

```
Boolean = (false, true)
```

char character type defines the set of 256 values of the ASCII character set, and is equivalent to the subrange defined by a type definition that looks like:

```
char = '\00' .. '\ff'
```

An unpacked **char** data item occupies one word or 16 bits of data storage. A packed **char** data item occupies one byte or 8 bits of data storage.

text is equivalent to a packed file of **char**.

interactive is a file type the same as that of **text**, except that the standard procedures **READLN** and **WRITELN** treat the end-of-line in a way that is more suitable for interactive (terminal) devices.

2.3 Defining Data Types

Pascal data types (or just types for short), are used to define sets of values that Pascal variables may assume and in many cases, a notation for referencing such variables. Pascal provides a small number of predefined types, reserved identifiers for these types, and a notation for defining new types in terms of existing types.

Type declarations introduce new (user defined) types, and identifiers for those newly-declared types.

```
<type spec> ::= <type identifier> = <Pascal type>;
```

Type declarations can be used for purposes of brevity, clarity and accuracy. Once declared, a type may be referred to elsewhere in the program by its declared type-identifier.

2.4 Simple Types

Simple types are those that have neither structure nor components. The simple types are as follows:

```
<simple type> ::= <scalar type>
                | <standard type>
                | <subrange type>
                | <type identifier>
```

2.4.1 Scalar Types

A scalar type defines a well-ordered set of values by enumerating the identifiers that denote those values. A scalar type is also known as an enumerated type or an ordinal type. An ordinal type is represented by the ordered set of integers 0, 1, 2, 3,, with the first identifier begin 0, up to the last identifier which is "n"-1, where "n" is the number of identifiers in the list.

```
<scalar type> ::= (<identifier> {,<identifier>})
```

Examples of Scalar Type Definitions

```
salad_greens = (Spinach, Lettuce, Coriander,
                Escarole, Watercress);
bottle_sizes = (Fillette, Bottle, Magnum, Marie_Jeanne,
                Jeroboam, Imperial);
mealtimes = (Breakfast, Elevenses, Lunch, AfternoonTea, Dinner);
```

2.4.2 Subrange Types

A subrange type represents a subrange of values of another scalar type. It is defined by a lower and an upper bound. The lower bound must not be greater than the upper bound, and both bounds must be of identical scalar types.

Values from a subrange and values from its parent range (or another subrange of its parent range) can be assigned to each other and can enter into the operations of assignment, comparison, and other binary operations.

```
<subrange type> ::=
    <subrange type identifier> | <lower> .. <upper>

<lower> ::= <signed scalar constant>
<upper> ::= <signed scalar constant>
```

Examples of Subrange Type Definitions

```
small_integer = 0 .. 15;
days_in_year = 1 .. 366;
positive_integer = 0 .. 32767;
lower_case_letters = 'a' .. 'z';
    colors = (red, orange, yellow, green, blue);
    hot_colors = red .. yellow;
    cold_colors = green .. blue;
    hues = red .. blue;
weekdays = Monday .. Friday;
weekends = Saturday .. Sunday;
```

2.5 Structured Types

Structured types represent collections of objects. They are defined by describing their element types and indicating a structuring method. These differ in the accessing mechanisms and in the notation used to select elements from the collection.

Pascal makes available five structuring methods: **array**, **string**, **set**, **record** and **file**. Each type is described in the subsections to follow.

A structured type may be given the **packed** storage attribute. This "advises" the compiler that the structure is to use data storage economically, by packing the components of the structure densely. Packing is often achieved at a cost of larger code size and slower execution speed. Furthermore, a component of a **packed** variable can not be passed as a **var** parameter to a procedure or function (this restriction applies to components of **packed array** of **char**). A full discussion on how components are packed can be found in appendix E - "Data Representations".

```

<structured type> ::= <unpacked structured type>
                    | packed <unpacked structured type>

<unpacked structured type> ::= <array type>
                               | <string type>
                               | <record type>
                               | <set type>
                               | <file type>

```

2.5.1 Array Types

An **array type** is a structure consisting of a fixed number of components, all of the same type (called the **component type**). Array elements are designated by indexes, which are values belonging to the so-called **index type**. The array type-definition specifies the component type as well as the index type.

```

<array type> ::= array [<index list>] of <type>

<index list> ::= <simple type> {, <simple type>}

```

If "n" index types are specified, the array is an "n" dimensional array. Note that the above definition for an **array type** means that there are two alternative ways of specifying an array. By definition, a component of an array can be another array type. Thus a three dimensional array could be specified as follows:

```

blivet = array [1..10, 11..20, 21..30] of blimps;

widget = array [1..10] of array [11..20] of
                    array [21..30] of blimps;

```

The alternative forms of specifying array types are equivalent. The first form can be thought of as a shorthand notation for the second form. There is a similar choice of notations when specifying the index elements for accessing an array component.

When the index type is a subrange of the type **integer**, the type:

packed array [1 .. n] of char

is a special case. Objects of this type can be assigned and compared as single entities, whereas arrays of other data types must be assigned and compared element by element. A literal string constant can be assigned to a **packed array of char**, providing that the lengths are the same. The type of a literal string of length 'n', where 'n' is greater than 1 is the type:

packed array [1 .. n] of char

An object of type **packed array of char** can be assigned and compared up to a maximum length of 255 characters. See chapters 4 and 5 for details.

Examples of Array Type Definitions

```

rows = 1 .. 3;
columns = 1 .. 4;

bottle_quantities = array [bottle_sizes] of integer;

standard_case = packed array [rows]
                  of array [columns]
                      of bottles;

token = packed array [1 .. 100] of char;

```

2.5.2 String Types

SVS Pascal has a structured type constructor called **string**. A **string** variable has a maximum length (called its static length) which is determined when the string is defined. A **string** variable also has a dynamic length which can vary over the range 0 through its static length during execution of a program. The standard function **LENGTH** can be used to determine the string's dynamic length. The maximum static length of a **string** variable is 255 characters.

Strings can be manipulated by standard Pascal syntax, or by using string handling intrinsics, described in chapter 8 - "Standard Procedures and Functions".

```

<string type> ::= string[<static length>]
<static length> ::= integer constant in the range 1 .. 255

```

A **string** constant which is '' (two juxtaposed apostrophes) represents a null or zero-length string.

Example of String Type Definition

```

manila = string[100];
punched_card = string[80];

```


2.5.3 Record Types

A record type is a structure consisting of a fixed number of components that may be of different types. For each component, or field of the record, the definition specifies both a type and an identifier used to reference the field. The scope of these field identifiers is the definition of the record itself. This means that the same field identifier may appear in more than one record. A field identifier is also accessible within a field designator when referring to a variable of this record type.

Record components which are themselves records do not inherit the packing attribute of the containing record. Each component which is a record has independent packing attributes.

A variant record caters to the need for a record composed of a portion which is always the same, plus one or more variants whose layouts differ between different instances of the record. The specific variant that is selected in any given instance is determined by an optional tag field. Such a structure is called a variant record or a discriminated union. The tag field is often called a discriminant. The tag field's value indicates which variant the record assumes at a given time. Each variant structure is identified via a case label which is a constant of the tag field's type. Referencing a field of a variant that is inconsistent with the tag field's value is a serious programming error.

```

<record type> ::= record <field list> end;
<field list> ::= <fixed part>
                | <fixed part> ; <variant part>
                | <variant part>

<fixed part> ::= <record section> {; <record section>}
<record section> ::= <field identifier list> : <type>
<field identifier list> ::= <field identifier> {,<field identifier>}

<variant part> ::=
    case {<tag field>} <type identifier> of <variant list>
<variant list> ::= <variant> {; <variant>}
<variant> ::= <case label list> : (<field list>)
<case label list> ::= <case label> {, <case label>}
<case label> ::= <constant>
<tag field> ::= <identifier>:

```

Note that the <tag field> is optional in a variant record definition.

Examples of Record Type Definitions

```
{ the example to follow illustrates an
  ordinary record called ComplexNumber,
  which contains two fields, namely the
  real part and the imaginary part. }
```

```
ComplexNumber = record
    RealPart: real;
    Imaginary: real;
end;
```

```
{ The example below illustrates a variant
  record type which has different sections
  that are accessed depending on the tags.
  First we define an enumerated type which
  is used as the variant case selector. }
```

```
shapes = (rectangle, triangle, circle, polygon);

angle = -180 .. +180;

PositionRec = record
    x_position: real;
    y_position: real;
    case whatshape: shapes of
        rectangle: (base: real;
                    height: real);
        triangle: (base: real;
                  height: real;
                  skew: angle);
        circle: (radius: real);
        polygon: (SideCount: integer;
                 radius: real);
    end;
```

2.5.4 Set Types

A **set** type definition serves to define the base type that the set is to use in future manipulations. Sets are limited to 2032 elements. The range of the set elements must be within the range 0 .. 2031.

```
<set type> ::= set of <simple type>
```

Examples of Set Type Definitions

```

salad_base = set of salad_greens;
dressings = set of salad_dressings;
lower_case = set of 'a' .. 'z';

```

2.5.5 File Types

A file type defines a sequence of elements. A file is usually associated with external storage devices or communication devices. SVS Pascal supports the standard Pascal typed files, untyped files and an interactive file type more suitable for terminals.

When a file variable "f" with components of type "T" is declared, there is an additional implied declaration of a so called buffer variable or "window", also of type "T". This window is referenced by the notation f^ where "f" is the file variable. This window is used in conjunction with the GET and PUT procedures (see chapter 6 - "Input and Output") and serves to append components to the file when writing, and to access the components when reading from the file.

```

<file type> ::= file of <type>
              |   file

```

SVS Pascal supports untyped files. An untyped file can be considered to not have a window variable. Such files must be accessed using the BLOCKREAD and BLOCKWRITE functions described in chapter 6 - "Input and Output".

A file of the pre-defined type text can be considered to be defined by a type definition of the form:

```

text = packed file of char;

```

Such a file is special in that the range of its components (characters) are extended to include an end-of-line marker. Such a file can then be conveniently structured into lines. The EOLN predicate described in chapter 8 - "Standard Procedures and Functions", covers how the end-of-line is detected.

SVS Pascal also supports an interactive file type which display different behavior in the way that the READ, READLN and RESET intrinsics work. The differences are covered in chapter 6 -

"Input and Output". An **interactive** file is more suitable for use with interactive terminals.

Examples of File Type Definitions

```
block_access = file;
numbers      = file of integer;
Capping_Line = file of bottles;
Terminal     = interactive;
legible_file = text;
```

2.6 Pointer Types

Explicitly declared variables are accessible by reference to the identifier used to declare them. Such variables are accessible during the activation (scope) of the procedure in which they are declared. These variables are called static, that is, lexically static.

Variables may also be created dynamically, in other words, with no correlation to the program structure. These dynamic variables are created via the procedure NEW. Since such variables do not have an associated name, they are accessed via a pointer value which is generated when the variable is allocated. A pointer type is therefore a value which points to a variable of a specific type.

There is a universal pointer value called nil, which belongs to any pointer type. It represents a pointer which points to no element.

```
<pointer type> ::= ^<type identifier>
```

Examples of Pointer Type Definitions

```
blackboard = record
  long_side: integer;
  short_side: integer;
end;
```

```
cue = ^blackboard;

TwoWay = record
    next: ^TwoWay;
    previous: ^TwoWay;
    stuff: array[0 .. 10] of integer;
end;

SymTree = record
    name: string[31];
    LeftNode: ^SymTree;
    RightNode: ^SymTree;
end;
```

2.7 Type Identity and Assignment Compatibility

Pascal has strict type checking such that objects of one type cannot be combined in operations with objects of a different type. There are two major concepts to be described here, namely identical types and assignment compatible types.

2.7.1 Identical Types

Two types, T1 and T2 are considered identical under the following conditions:

- . T1 and T2 are the same type.
- . T1 is declared as synonymous with another type T3, where T2 and T3 are identical.

Examples of Type Identity

```
type_x = integer;
type_y = integer;
type_1 = set of char;
type_2 = set of char;
id_type = type_1;
```

In the above example, the types "type_x" and "type_y" are identical, because they are defined to be the same type, **integer**. The types "type_1" and "type_2" are not identical, since they occur in different type definitions. The types "type_1" and "id_type" are identical however, because "id_type" is defined to be the same as "type_1".

2.7.2 Assignment Compatible Types

A value of type T1 is considered to be assignment compatible with a variable of type T2 if any of the following conditions are true:

- . T1 and T2 are identical and do not contain a file as a component.
- . T1 is a subrange of T2, or
- . T2 is a subrange of T1, or
- . T1 and T2 are subranges of identical types.
- . T1 is assignment compatible with **integer** and T2 is **real** or **double**.
- . T1 and T2 are both variable **string** types.
- . T1 and T2 are sets of elements of types T3 and T4, and T3 is assignment compatible to T4.

Chapter 3

Declaring and Referencing Variables

This chapter covers two topics. First there is a discussion of how Pascal variables are declared in terms of the data types described in the previous chapter. Then there is a description of the way that variables of different types are accessed or referenced.

3.1 Declaring Variables

A variable has a type and a storage area in memory. At any given time, a variable takes on one value out of the collection of values that define its type. A variable is initially undefined, and remains so until it is initialized by an explicit assignment.

All variables in a Pascal program must be declared explicitly and prior to their use.

Variable declarations consist of a list of identifiers that represent the variables, followed by the type of the variable.

```
<variable declaration> ::=
    <identifier> {,<identifier>}: <data type>;
```

Examples of Declaring Variables

```
Impedance: ComplexNumber; { a record variable }
ChainHead: TwoWay;        { another record }
TreeTop: SymTree;         { and another }
First, Middle, Last: integer; { plain integers }
ValueFile: Numbers;      { a file variable }
CurChar: char;           { a character variable }
Omega: real;              { a real variable }
```


3.2 Predeclared Variables

SVS Pascal has five pre-declared variables. These are:

input, output, and stderr

default files associated with the standard input, the standard output, and the standard error output file, respectively.

On those operating systems which do not have a standard error output file, the file **stderr** is directed to the same place as the **output** file.

argc and **argv** are variables which provide access to the command line that invoked the current Pascal program.

These pre-declared variables are covered in detail in chapter 7 - "Program Structure".

3.3 Establishing Variables

Establishing a variable is a process that involves:

1. determination of the variable's type.
2. allocation of storage for the values that the variable takes on.

Explicitly declared variables are automatically established on each entry to the procedure or function block in which they are declared. "Global" variables (declared in the outermost block) are established once and only once.

Formal parameters of procedures or functions are automatically established on each activation of that procedure or function.

So-called "dynamic" variables are explicitly established by storage management operations (for type determination and storage allocation), and by assignment operations (for initialization).

3.4 Lifetimes of Variables

The lifetime of a local variable is that of the block in which it is declared. Allocation occurs on each entry to that block, and de-allocation occurs on each exit from that block.

3.4.1 Global Variables

Global variables are those variables declared in the outermost block (in the `program` block). The lifetime of such global variables is the lifetime of the entire program.

3.4.2 Lifetime of Formal Parameters

The lifetime of a formal parameter is the lifetime of the procedure or function which that formal parameter is a part of. The formal parameter becomes established upon each entry to the procedure or function, and becomes undefined upon exit from the procedure or function.

3.4.3 Lifetime of Dynamic Variables

Dynamic variables are established (but not initialized) by an explicit allocation operation (such as `NEW`). Dynamic variables become undefined when they are explicitly freed, or when no pointer variable points to them. Note that generally a pointer value has a finite lifetime which may be different from that of the pointer variable that can point to it. Local variables belonging to procedures and functions, cease to exist on exit from the block in which they were declared. Dynamic variables, on the other hand, cease to exist when they are explicitly freed or when no pointer variable points to them. Attempts to reference non-existent variables beyond their lifetimes is a programming error, usually with undesirable results from the programmer's viewpoint.

3.5 Referencing or Accessing Variables

The method by which a variable or a component of a variable is accessed differs depending on the structuring method used in the type definition for that variable. There are three basic access methods:

1. An entire variable is a variable of a simple type (no structure). An entire variable is referenced simply by giving its name.
2. A component variable is a variable of array, record or file type. The access methods are explained below.
3. A referenced variable is accessed through a pointer.

```
<variable> ::= <entire variable>
           | <component variable>
           | <referenced variable>
```

3.5.1 Entire Variables

An entire variable is denoted by its identifier. Since an entire variable has no structure, its identifier alone is enough to reference it.

```
<entire variable> ::= <variable identifier>
```

Examples of Entire Variable References

```
ChickenTeeth
GiddyGoatHorns
First
```

3.5.2 Component Variables

A component of a variable is denoted by the variable followed by some selector that specifies the component. The form of the selector depends on the structuring method used to access the variable.

```

<component variable> ::= <indexed variable>
                       | <field designator>
                       | <file buffer>

```

3.5.2.1 Referencing Indexed Variables

A component of an "n"-dimensional array variable is denoted by the variable followed by "n" index expressions. An entire array (which can be a component) of an array can be denoted by giving "n"-1 index expressions. In such a case, the entire last dimension of the array is indicated. This occurs when an entire array or an entire subarray is passed as an actual parameter to a procedure or function.

```

<indexed variable> ::= <array variable> <subscript list>

<subscript list> ::= [ <expression> {,<expression>} ]
                   | [ <expression> ] [ [ <expression> ] ]

```

The {,<expression>} in the definition above implies that there are as many expressions in the subscript list as there are dimensions in the array variable. Just as in defining an array type, there are two alternative methods for referencing an array variable. Either the subscripts can be listed, separated by commas, inside the brackets, or there can be a list of bracketed subscript expressions.

The index expression types must correspond with the index types declared in the array type definition.

Examples of Array Variable References

```

ladder[top]
stairs[flight][step]
Footing[Left, Center, Right]

```

3.5.2.2 Referencing Strings

string variables can be referenced as single entities (when the entire string is being operated upon) or single characters from a string can be referenced just like a **packed array of char**. Values can be assigned to string variables using assignment statements, string intrinsics or the READ or READLN procedure. String indexing is based from one (1) so that the expression on the string "s":

s[LENGTH(s)]

correctly yields the last character in the string. It is an error to reference a string "s" with an index less than one (1) or greater than LENGTH(s).

3.5.2.3 Referencing Fields of Records

A component of a record variable is denoted by the record variable followed by the component's field identifier. The field identifiers are separated by periods.

<field designator> ::= <record variable>.<field identifier>

It is an error to reference a field of a variant record that is inconsistent with the tag field for that variant.

Examples of Accessing Fields in Record Variables

```

    { The first example is a simple field reference }
    impedance.RealPart

    { The second example illustrates a reference
      to a field of an array of records }
    bottles[BurgundyType].Loire

    { The third example illustrates a
      deeply nested field reference }
    King_Caractacus.Court.Ladies.Faces.Noses
    
```

3.5.2.4 Referencing File Buffers

At any time, only the one component determined by the current file position (read/write head) is directly accessible. This component is called the "current file component", and is represented by the file's buffer variable.

<file buffer> ::= <file variable>^
 <file variable> ::= <variable>

3.5.3 Pointer Referenced Variables

```
<referenced variable> ::= <pointer variable>^  
  <pointer variable> ::= <variable>
```

If "p" is a variable which is a pointer to type "T", "p" means the pointer variable and its pointer value, whereas "p^" means the variable of type "T" that "p" references.

Examples of Pointer Reference

```
TreeTop.LeftNode^ { Left Node in the tree variable }  
cue^.longside    { gets Long Side of Blackboard   }
```


Chapter 4
Expressions

An expression is a construct which defines the rules of computation for creating a value by performing operations (specified by operators) on operands (specified by variables, constants, and function references). These newly-created values can then be used in assignment statements or can be used (in conditional expressions) to control subsequent program actions.

```

<unsigned constant> ::= <unsigned number>
                       | <string>
                       | <constant identifier>
                       | nil

<factor> ::= <variable>
             | <unsigned constant>
             | <function designator>
             | <set constructor>
             | (<expression>)
             | not <factor>

<set constructor> ::= [ <element> {,<element>} ]
<element> ::= <expression>
             | <expression> .. <expression>

<term> ::= <factor>
          | <term> <multiplying operator> <factor>

<simple expr> ::= <term>
                | <simple expr> <adding operator> <term>
                | <adding operator> <term>

<expression> ::=
  <simple expr>
  | <simple expr> <relational operator> <simple expr>

```


4.1 Operators in Expressions

Operators perform operations on a value or a pair of values to produce a new value. Most operators are defined only on basic types, though some are defined on most types. The following subsections define the applicable range, as well as the result, of the defined operators.

With the exception of the @ operator, an operation on a variable or field which has an undefined value, produces an undefined result.

4.2 Address Evaluation Operator

The @ operator generates the address of a variable, user procedure or user function. Its precedence is above that of all other operators, but below that of array indexing and record field referencing. It can be applied to unpacked fields of records and unpacked array elements and to the dynamic variables pointed to by a pointer. It cannot be applied to components of any packed structure.

Examples of the @ Operator

@Uncle_Bill generates the address of a variable named "Uncle_Bill".

@TypeWheel[tilde] generates the address of the "tilde"th element of the array "TypeWheel".

4.3 NOT Operator

The not operator applies to factors of type Boolean or integer.

When applied to type Boolean, the meaning is negation. That is, not true = false, and not false = true.

When applied to type **integer**, the **not** operator negates all the bits in the value. That is, it performs a one's complement negation of each bit in the operand. The result of applying the **not** operator to a value of type **integer** is type **integer**.

4.4 Multiplying Operators

The multiplying operators have the next highest precedence after the **not** operator.

<multiplying operator> ::= * | / | div | mod | and

The following table shows the multiplying operators, the permissible types of their operands, and the result types. Operands of the * (multiplication) and / (division) operators can be mixed **integer**, **real**, and **double** data types.

If both operands of the * operator are of type **integer**, the result is of type **integer**.

If either operand is of type **double**, the other operand is converted to type **double**, and the result is of type **double**. Otherwise, if either operand is of type **real**, the result is of type **real**. The result of the / operator is either **real**, or in the case when one or both operands are of type **double**, the result is of type **double**.

Operator	Operation	Operands	Result
*	multiplication	real, double, or integer	real, double, or integer
	set intersection	any set type T	T
/	division	real, double, or integer	real double
div	division with truncation	integer	integer
mod	modulus	integer	integer
and	logical and	Boolean	Boolean
	bitwise and	integer	integer

The `div` operator applies to values of type `integer` only and represents truncating division. `div` always truncates towards zero. It is an error to divide by zero. If the signs of the operands are the same, the result is positive; if the signs are different, the result is negative.

The `mod` operator defines the modulus operation between two values of type `integer`. It is an error if the right operand of `mod` is zero. The interpretation of `mod` is:

$$a \text{ mod } b = a - (a \text{ div } b) * b$$

When applied to operands of type `Boolean`, the `and` operator produces a result of type `Boolean` as one might expect. When applied to operands of type `integer` however, the `and` operator performs a bitwise logical and on the operands and produces a result of type `integer`.

4.5 Adding Operators

The adding operators have the next highest precedence after the multiplying operators.

<adding operator> ::= + | - | or

The following table shows the adding operators, their permissible operand types, and the result types. Operands of the + (addition) and - subtraction operators can be mixed `integer`, `real`, and `double` data data types.

If both operands of the + or - operator are of type `integer`, the result is of type `integer`.

If either operand is of type `double`, the other operand is converted to type `double`, and the result is also of type `double`. Otherwise, if either operand is of type `real`, the result is also of type `real`.

operator	operation	operand types	result type
+	addition	real, double, or integer	real, double, or integer
	set union	any set type T	T
-	subtraction	real, double, or integer	real, double, or integer
	set difference	any set type T	T
or	logical or	Boolean	Boolean
	bitwise or	integer	integer

When applied to operands of type **Boolean**, the **or** operator produces a result of type **Boolean** as one might expect. When applied to operands of type **integer** however, the **or** operator performs a bitwise logical or on the operands and produces a result of type **integer**.

4.6 Sign Operators

The "+" and "-" signs can be used as unary operators. They apply to **integer**, **real**, and **double** data types only. Applying a unary operator to a data type produces a result which is the same data type as that of the operand.

<sign operator> ::= + | -

The table below shows the sign operators, their permissible operand types and their result types.

operator	operation	operand types	result type
+	identity	real, double, or integer	real, double, or integer
-	negation	real, double, or integer	real, double, or integer

4.7 Relational Operators

The following table shows the relational operators, their permissible operand types, and the result type.

operator	operand types	result type
= <>	any scalar or subrange type set type pointer type packed array of char string	Boolean
<= >=	any scalar or subrange type set type packed array of char string	Boolean
< >	any scalar or subrange type packed array of char string	Boolean
in	any scalar or subrange type and its set type respectively.	Boolean

Note that all scalar types define ordered sets of values.

4.7.1 Comparison of Scalars

All six relational operators (<, <=, >, >=, = and <>) are defined between operands of the same scalar type.

For operands of type **integer**, **real**, or **double**, the operators have their usual meaning. Operands of **integer**, **real**, and **double** data types are considered to form a hierarchy, with the **integer** data type at the bottom of the pecking order, the **double** data type at the top, and the **real** data type in the middle. If the operands are of different numeric types, the lower type of operand is converted (or promoted) to the type of the other operand prior to the comparison. For example, in the expression:

integer type < double type

the **integer** operand is converted to **double** before the comparison is made.

For operands of type **Boolean** the relation **false < true** defines the ordering.

For operands of type **char** the relation "a" **op** "b" holds if and only if the relation **ORD(a) op ORD(b)**, holds, where **op** denotes any of the six comparison operators and **ord** is the mapping function from type **char** to type **integer** defined by the ASCII collating sequence.

For operands of any ordinal type "T", "a" = "b" if and only if, "a" and "b" are the same value; "a < b" if and only if, "a" precedes "b" in the ordered list of values that define "T".

4.7.2 Comparison of Booleans

If "p" and "q" are **Boolean** expressions, "p = q" means equivalence, and "p <= q" means implication of "q" by "p".

4.7.3 Direct Pointer Comparison

Two direct pointers can be compared if they are pointers to identical types. To compare pointers of differing types, take their **ORD**. (See chapter 8 - "Standard Procedures and Functions").

Pointers may be compared for equality or inequality only.

Two pointers with the value **nil** are always equal.

4.7.4 String Comparison

All six relational operators may be applied to **string** operands. The relational operators compare both **packed array of char** and **string** values.

In the case of a **packed array of char**, both operands must be the same size. The maximum length of string comparison of values of **packed array of char** is 255 characters. That is, a variable whose declaration is like:

```
var
  strtype: packed array [1 .. 255] of char;
```

is the largest string variable that can be compared in one operation.

In the case of **string** comparison, the operands may be of different sizes. If the operands are of different sizes, trailing spaces are significant. That is, the string

```
'A'
```

compares less than the string

```
'A '
```

Comparison of **string** operands or **packed array of char** operands denotes alphabetical ordering according to the ASCII character set collating sequence.

Note that because a **string** data type is represented differently from a **packed array of char**, they cannot be compared with each other. On the other hand, a character string constant is of ambiguous type, and so a string constant can be compared either to a **string** operand or to a **packed array of char** operand, because the type of the string constant is converted to the type of the other operand in comparison operations.

4.7.5 Set Comparison

The relation "scalar_value" in "some_set" is true if the "scalar_value" is a member of the "some_set". The base type of the set must be the same as, or a subrange of, the type of the scalar.

The set operations = (identical to), and <> (different from), <= (is included in), and >= (includes) are defined between two set values of the same base type. For two sets "S1" and "S2" of the same base type:

S1 = S2	is true if all members of S1 are contained in S2, and all members of S2 are contained in S1.
S1 <> S2	is true when S1 = S2 is false.
S1 <= S2	is true if all members of S1 are also members of S2.
S1 >= S2	is true if all members of S2 are also members of S1.

4.7.6 Non-Comparable Types

Certain Pascal types cannot be compared. These include files, arrays, variant records, and records containing fields of non-comparable types. The exception to this rule is that **packed array of char** operands can be compared if they are the same size.

4.8 Out of Range Values

It is possible that expression evaluation can yield results which are outside of the range of values for a given data type. Expressions involving the **real** and **double** data types can generate several different extreme values.

The extreme value of positive or negative infinity is a result either of overflow, or by dividing a non-zero value by 0.0.

Underflow generates a value of zero.

Dividing 0.0 by 0.0 generates a value of Not a Number (NaN).

Appendix E - "Data Representations" contains a description of the extreme values and their behavior in comparisons.

4.9 Order of Evaluation in Expressions

The rules of composition for expressions specify operator precedence according to five operator classes. The precedence is as follows:

1. the "address of" @ operator has the highest precedence.
2. then the not operator.
3. then the multiplying operators.
4. then the adding operators.
5. the lowest precedence is the relational operators.

Operators at the same precedence level are applied left to right, except where parentheses are used to override the normal order of evaluation. The order in which operators are applied is according to the rules above. The precise order of operand evaluation is undefined. Some operands may not be evaluated at all, if the value of the expression can be determined without the value of that particular operand.

4.10 Compile Time Constant Expressions

The Pascal compiler evaluates certain types of integer and Boolean constant expressions at compile time. integer expressions consisting of constant expression operands and the following operators are folded into constant expressions:

```
Binary Operators = <> + - *
Unary Operators  -
```

Boolean expressions consisting of constant expression operands and the following operators are folded into constant expressions:

```
Binary Operators = <> and or
Unary Operators  not
```

4.10.1 Dead Code Elimination

The Pascal compiler recognizes code of the form:

```
if FALSE then
  statement_1
else
  statement_2
```

and generates code for statement_2 only. Similarly, if the Boolean expression is TRUE, only statement_1 is generated. Constant expressions which fold into constants are recognized as constant TRUE or FALSE. This feature facilitates keeping several versions of similar source in the same file without adding extra generated code after the code is compiled.

Example of Conditional Compilation

```
const
  version = 10;

if version = 7 then
  writeln('Too old!')
else
  writeln('Not too old!');
```

The code fragment above, with the constant "version" set equal to 10, has the same effect as a code fragment like this:

```
writeln('Not too old!');
```


Chapter 5

Statements

Statements denote algorithmic actions, and are said to be executable. Statements define the actions that are to be performed on program objects that were introduced via type and variable declarations, discussed earlier in this manual.

5.1 Statement Labels

A statement can be labelled by preceding it with an unsigned integer constant in the range 0 .. 9999, followed by a colon. The statement can then be explicitly referred to by a `goto` statement.

5.1.1 Scope Of Statement Labels

The scope of a statement label is the body of the procedure or function in which the label is declared. This means that a `goto` statement cannot transfer control into a procedure or function body from outside the procedure or function.

5.2 Assignment Statements

The assignment statement replaces the current value of a variable with a new value derived from expression evaluation, or defines the value that a function variable returns.

```
<assignment statement> ::=
    <variable> := <expression>
    | <function identifier> := <expression>
```

5.2.1 Assignments to Variables and Functions

The part to the left of the assignment symbol (the :=) is evaluated to obtain a reference to some variable. The expression on the right side is evaluated to obtain a value. The referenced variable's current value is discarded and replaced with the expression's value.

The variable on the left hand side of an assignment statement must be assignment compatible with the type of the expression on the right hand side.

A string value may be assigned to a variable of type packed array of char, providing that the string value is the same length as the array object. The maximum length of such an assignment is 255 characters.

Examples of Assignment Statements

x := 5	{	simple assignment to variable	}
y := x * 10 + 18	{	assignment of expression	}
ch := CHR(10)	{	assignment of function value	}
rope := 'hemp'	{	string assignment	}
poke := POINTER(\$200)	{		}
poke^ := 0	{	clobber the system vector	}

5.3 Procedure Reference Statement

A procedure reference statement creates an environment for execution of the specified procedure and transfers control to that procedure.

```
<procedure call statement> ::=
    <procedure identifier><actual parameter list>
    | <procedure identifier>
<actual parameter list> ::=
    (<actual parameter> {,<actual parameter>})
<actual parameter> ::= <expression>
    | <procedure identifier>
    | <function identifier>
```

The actual parameter list must be compatible with the formal parameter list of the procedure. An actual parameter corresponds to the formal parameter which occupies the same ordinal position in the formal parameter list.

Only formal parameters that are value parameters can have an actual parameter which is an <expression>. Value parameters must be assignment compatible with the type of the formal parameter.

Formal parameters that are var parameters must have actual parameters that are identical types. In addition, the actual parameters must not be packed objects or components of packed objects.

5.4 Structured Statements

Structured statements are constructs composed of statement lists. They provide scope control, selective execution, or repetitive execution of the constituent statement lists.

```
<structured statement> ::= <begin statement>
                        | <if statement>
                          <while statement>
                            <repeat statement>
                              <for statement>
                                <case statement>
```

5.4.1 BEGIN .. END - Compound Statements

A **begin** statement specifies execution of a statement list. Exit from the statement list is either through completing execution of the last statement in the statement list, or through explicit transfer of control.

```
<begin statement> ::= begin <statement list> end
<statement list> ::= <statement> {; <statement>}
```

5.4.2 IF .. THEN .. ELSE Statements

The **if** statement specifies that another statement be executed (or not) depending on the truth (or falsity) of a conditional expression. If the value of the conditional expression is **true**, the statement is executed. If the value of the conditional expression is **false**, either no subsequent statement is executed,

or the statement following an **else** clause is executed.

```
<if statement> ::=
    if <Boolean expression> then <statement>
    |  if <Boolean expression> then <statement> else.<statement>
```

Because Pascal statements are open forms, it is possible to construct a chain of **else if** clauses to select "one out of many different conditions".

In common with similar languages, Pascal has what is called the "dangling else" problem. If an if statement contains another if statement as a subordinate, when an **else** clause is encountered, which if statement does the **else** clause apply to? In Pascal, the **else** clause matches the most recent if statement that does not have an **else** clause. One of the examples below clarifies this point.

Examples of If Statements

```

                                { example of a simple if statement }
if day in [Monday .. Friday] then
    Get_up_and_go
else
    Roll_over

                                { an if statement with a
                                compound block }
if sun > yardarm then
    begin
        make_cocktails;
        prepare_snacks;
        relax
    end
else
    flog_on

                                { an else if chain }
if weather = raining then
    sleep_in
else if lawn = wet then
    clip_the_hedge
else if grass > 6 then
    mow_the_lawn
else
    turn_on_lawn_sprinklers
```

```

                { A dangling else clause }
if condition_1 then { 1 }
    if condition_2 then { 2 }
        if condition_3 then { 3 }
            ..... statements .....
        else { goes with statement 1 }
            ..... statements .....
    else { goes with statement 2 }
        ..... statements .....
else { goes with statement 3 }
    ..... statements .....

```

5.4.3 CASE Statements

A case statement selects one of its component statements depending on the value of an expression. The expression is called the selector. Each of the component statements is tagged with one or more simple scalar constants. The tags are called selection specifications (<selection specs> for short). If the value of the selector matches that of one of the statement tags, that statement is executed. If the selector value matches none of the statement selection specifications, the statement (if any) following an **otherwise** symbol is executed.

Note that this Pascal implementation differs from the ISO standard in the provision of the **otherwise** clause. ISO Pascal has no provision for "what to do if none of the case selectors match the selector expression". Strict Pascal considers this situation a run-time error.

```

<case statement> ::= case <expression> of <cases>
                    {otherwise: <statement>} end

<cases> ::= <a case> {<a case>}
<a case> ::=
    <selection spec> {, <selection spec>} : <statement>;

<selection spec> ::= <scalar constant>

```

Case selectors and the statement tags must be non-real scalar types. In addition, the case selectors and the statement tags must be of assignment compatible types.

It must be stressed that the selection specifications which the component statements are tagged with are not labels in the Pascal sense, and as such, cannot be used as the target of a **goto** statement, and neither should they appear in any label declaration part.

Examples of Case Statements

```
case wine_type of
  Champagne:
    Anything_goes;

  Cabernet:
    Roast_Lamb;

  Chardonnay:
    Veal_Piccata;

  otherwise:
    Hamburger;
end;
```

5.4.4 WHILE .. DO Statements

A **while** statement controls repetitive execution of another statement until evaluation of a Boolean expression becomes false.

```
<while statement> ::= while <expression> do <statement>
```

The <statement> is repeated while the value of <expression> remains true. The <expression> must be of type **Boolean**. When <expression> becomes false, control passes to the statement after the **while** statement. If the value of <expression> is false at the time that the **while** statement is encountered for the first time, the subordinate statement is never executed at all. Thus the **while** statement provides a means to "do nothing gracefully". Contrast this behavior with the **repeat** statement described below.

Example of WHILE Statement

```

while bytes_to_go > 0 do
  begin
    if bytes_to_go <= BlockSize then
      TransferLength := bytes_to_go
    else
      TransferLength := BlockSize;
    DoTransfer;
    bytes_to_go := bytes_to_go - TransferLength;
    BlockNumber := BlockNumber + 1
  end

```

5.4.5 REPEAT .. UNTIL Statements

The **repeat** statement controls the repetitive execution of a list of statements. The statements are executed until the condition at the end of the statement evaluates to **true**. The form of a **repeat** statement is:

```
<repeat statement> ::= repeat <statement list> until <expression>
```

The expression controlling repetition must be of type **Boolean**. The statement between the **repeat** and **until** symbols is executed repeatedly until the expression becomes **true**. Note that the body of a **repeat** statement is always executed at least once, since the termination test is at the end. Contrast this behavior with the **while** statement described in the previous subsection.

Example of Repeat Statement

```

repeat
  consume_glassfull;
  refill_glass;
until (Champagne_Volume <= 0) or (Consumer = Blotto);

```

5.4.6 FOR .. DO Statements

The **for** statement executes its subordinate statement repeatedly, while a progression of values is assigned to a control variable of the **for** statement.

```
<for statement> ::=
  for <control variable> := <for list> do <statement>
```

```

<for list> ::= <initial value> to <final value>
              | <initial value> downto <final value>

<control variable> ::= <identifier>

<initial value> ::= <expression>
<final value> ::= <expression>

```

The control variable is set to the initial value. After every iteration the control variable is either incremented (to) or decremented (downto) until its value is greater than or less than the final value.

The control variable, the initial value, and the final value, must all be of the same scalar type or a subrange of that scalar type. No part of the statement controlled by the for statement may alter the control variable during the execution of the for statement.

Neither the control variable, nor the initial value, nor the final value, may be of type real. The control variable must be local to the procedure or function that contains the for statement.

The value of the control variable is undefined on normal termination from the for statement. If the for statement is exited prematurely (via a goto statement), the value of the control variable is defined.

Examples of the FOR Statement

```

                                { initialize an array to zero }
for index := 1 to 100 do
    row[index] := 0

                                { scan from the end of an array }
for where := 200 downto 1 do
    if what[where] = thing then
        foundit := true

```

5.5 The WITH Statement

The **with** statement provides a "shorthand" notation for referring to fields in a record. The **with** statement effectively "opens the scope" that contains field identifiers of a specified record variable.

```
<with statement> ::=
    with <record variable> {,<record variable>}
                                do <statement>
```

Within the body of the **with** statement, fields of the specified record variable do not need to be qualified by the name of the record.

If there is a local variable "x" and a field "x" in a record which is the subject of a **with** statement, the statement:

```
with x do
```

"hides" the local variable "x" until the end of the **with** statement.

A **with** statement which has multiple <record variable> fields is interpreted as nested **with** statements. The statement:

```
with record_1, record_2, record_3 do
```

is equivalent to the statement:

```
with record_1 do
    with record_2 do
        with record_3 do
            ..... statement .....
        
```

Example of the WITH Statement

```

var
  TreeTop: SymTree;
with TreeTop do
  begin
    LeftNode := nil;
    RightNode := nil
  end { with }

```

This is a shorthand for the following statements

```

TreeTop.LeftNode := nil;
TreeTop.RightNode := nil

```

5.6 The GOTO Statement

The `goto` statement names as its successor, a labelled statement designated by a label.

```
<goto statement> ::= goto <label>
```

The following should be noted concerning the `goto` statement and the label that it designates:

The scope of a label is the procedure in which that label is defined. Therefore it is not possible (nor valid) to jump into a procedure from outside that procedure.

Every label in a procedure must be declared in the label declaration part at the head of the procedure.

Example of Goto Statement

```

if status = error then
  goto 9999 { exit to end of procedure }

```

Chapter 6

Input and Output

Input and Output facilities provide the means whereby a Pascal program can communicate with the world outside the computer system on which it runs.

SVS Pascal supports the input-output facilities as defined by standard Pascal, and additionally supports untyped (block access) files, interactive files, random access to typed files and unit input-output (direct access to the devices on the system).

6.1 General File Handling Procedures

This Section covers the standard Pascal procedures for handling files of any type. The four supplied procedures are GET, PUT, RESET and REWRITE.

6.1.1 The File Buffer Variable

A Pascal file of some type is a sequential file - its components appear in strict sequential order (ignore the SEEK procedure for the duration of this discussion). Writing implies appending a component to the end of the file. Reading implies that the next component in sequence is obtained from the file. The following discussion applies only to typed files.

Associated with each typed file variable there is an implicit "buffer variable", often called the file "window". The buffer variable can be thought of as a place holder where the current file component is held. The buffer variable holds the next available component when reading. When writing, it holds the component that will be appended to the file by a PUT procedure call.

For a given file variable "f", the buffer variable is referenced by the notation "f^". Consider the following

declarations:

```
type
  whammo = file of gobion;

var
  frammmis: whammo;
  CurComp: gobion;
```

When the file "frammmis" is opened for reading via the RESET procedure call, the first component of the file is in the buffer variable. An assignment statement of the form:

```
CurComp := frammmis^;
```

assigns the contents of the buffer variable to the variable "CurComp". The contents of the buffer variable then become undefined. The next component from the file is moved into the buffer variable by a GET procedure call.

When the file "frammmis" is opened for writing via the REWRITE procedure call, the buffer variable is undefined. An assignment of the form:

```
frammmis^ := CurComp;
```

assigns the value of the variable "CurComp" to the buffer variable. A subsequent PUT procedure call appends the contents of the buffer variable to the file "frammmis". The contents of the buffer variable become undefined until another assignment defines it.

For files of type **interactive** the handling of the buffer variable is different. In standard Pascal, when a file is RESET, the first element of the file is read and placed in the file buffer variable. means that the system would expect the user to type a character at the terminal, else the system would "hang". Thus a RESET on an **interactive** file does not perform an immediate GET. This affects the way that EOLN functions. When an end-of-line is read, EOLN becomes true and the character read is a space.

6.1.2 GET - Get Component from File

The procedure GET obtains the next element from a file (assuming there is a next element to be obtained).. A call on the GET procedure of the form:

```
GET(file)
```

advances the current file position to the next component in the file. The value of this component is then assigned to the buffer variable `file^`.

If there was no "next component" in the file, the value of the buffer variable is undefined and the predicate `EOF(file)` becomes **true**.

If the predicate `EOF(file)` is already **true**, a `GET(file)` (in other words, trying to read past end-of-file) has an undefined result.

6.1.3 PUT - Append Component to a File

A call on the `PUT` procedure of the form:

```
PUT(file)
```

appends the value of the buffer variable `file^` to the file "file". The value of `file^` becomes undefined after the call to `PUT`. The predicate `EOF(file)` becomes **true** after the `PUT`.

If the predicate `EOF(file)` was **false** before the call to `PUT` (in other words, there were intervening `GET`'s on the file), the call to `PUT` has an undefined result.

6.1.4 RESET - Position to Start of File

A call to the `RESET` procedure of the form:

```
RESET(file, string [, buffering option])
```

resets the current file position to the beginning of the file. If the file is not empty, the first element of the file is assigned to the buffer variable `file^` and the predicate `EOF(file)` becomes **false**. If the file is empty, the buffer variable `file^` is undefined and the predicate `EOF(file)` becomes **true**.

If the file is an **interactive** file, `RESET` does not read the first element of the file.

SVS Pascal provides for a second parameter to `RESET`. This parameter is the name of an **existing** disk file or device. The parameter takes the form of a **string** constant or variable.

The third parameter to `RESET` is an option to determine whether the file is buffered or unbuffered. The buffering option may be specified as the keyword `BUFFERED` or `UNBUFFERED`, and it is described in the subsection following `REWRITE`, below.

6.1.5 REWRITE - Create or Overwrite a File

The REWRITE procedure creates a new file of a specified name and discards any existing file of the same name. Thus a call of the form:

```
REWRITE(file, string [, buffering option])
```

discards the current value of the file variable "file", effectively creating a new file. The value of the buffer variable "file^" is undefined and the predicate EOF(file) becomes true.

SVS Pascal provides for a second parameter to REWRITE. This parameter is the name of a disk file. The parameter can be a string variable or constant. REWRITE always creates a temporary file of the specified name. Upon closing the file, it can either be discarded, or the existing file (if any) can be replaced.

The third parameter to REWRITE is an option to determine whether the file is buffered or unbuffered. The buffering option may be specified as the keyword BUFFERED or UNBUFFERED, and it is described in the subsection below.

6.1.6 The Buffering Option on RESET and REWRITE

The optional "buffering option" parameter to RESET and REWRITE can be specified as either BUFFERED or UNBUFFERED. On some operating systems, there is a significant difference in throughput between buffered and unbuffered input output.

Normally, buffered input output is much more efficient than unbuffered input output. But, there can also be undesirable side effects in buffered input output, most notably that output does not appear at a terminal until a full buffer has been collected.

The "buffering option" parameter provides a means to request either buffered or unbuffered input output for the file specified in the RESET or REWRITE request. A given operating system might well override the request, depending on the nature of the device on which the file resides. The standard situation is unbuffered input output, in the absence of the "buffering option" parameter.

6.2 Text File Handling Procedures

Pascal provides standard procedures for controlling text-file input and output. These procedures apply to files of type **text** or **interactive**.

6.2.1 READ and READLN Intrinsic

READ and READLN read character strings representing numbers from a textfile and convert them into their internal representations. There is more on converting numbers later in this subsection.

READ (v_1, v_2, \dots, v_n)
is equivalent to a

READ(input, v_1, v_2, \dots, v_n)

READ (file, v_1, v_2, \dots, v_n)
is equivalent to a sequence of READ procedure calls as follows:

READ (file, v_1);
READ(file, v_2);
READ(file, v_n)

If "ch" is a variable of type **char**, the two programs displayed here are equivalent:

<pre>var ch: char; rasp: file of char; begin READ(rasp, ch) end</pre>	<pre>var ch: char; rasp: file of char; begin ch := rasp^; GET(rasp) end</pre>
--	--

If "v" is a variable of type **integer**, any subrange of **integer**, **real**, or **double**, the procedure reference:

READ(file, v)

reads a sequence of characters from the file referenced by "file". The sequence of characters should form a valid number

according to Pascal's rules for numbers (described in chapter 1). Note that if a real or double number contains a decimal point, there must be at least one digit on either side of the decimal point. When the number is formed it is then assigned to the variable "v". Blank lines and spaces preceding the number are skipped in the file. Reals are read in the same way as integers. Booleans cannot be read via a READ or READLN call. Structured types cannot be read.

If the sequence of characters read from the file do not form a valid number according to the syntax rules, one of two actions are taken: if I/O checking is on, the Pascal run-time system issues an error diagnostic; if I/O checking is off, READ or READLN return zero (0) and the IORESULT code is set. See appendix A - "Messages from the Pascal System" for a list of I/O error codes.

6.2.2 READ from a file of any type

The READ procedure can also read from a file of any type. A READ procedure call of the form:

```
READ(file, v1, v2, ..., vn);
```

is equivalent to the sequence:

```
v1 := file^; GET(file);
v2 := file^; GET(file);
.
.
.
vn := file^; GET(file);
GET(file);
```

where the "v_n" are the list of variables to read into.

Note that the type of each variable in the list must be identical to the type of the elements in the file.

6.2.3 WRITE and WRITELN Intrinsics

The WRITE and WRITELN intrinsics append character strings to a textfile. Usually the character strings are generated by converting one or more Write parameters (see below) from their machine representations into external representations.

The procedure WRITELN differs from the procedure WRITE only in that WRITELN sends an end-of-line to the output file after the write is complete.

```

<write intrinsic> ::= WRITE(<file> <write parameters>);
<writeln intrinsic> ::= WRITELN(<file> <write parameters>);
                        | WRITELN;
<file> ::= <file variable>,
<write parameters> ::= <write parameter> {, <write parameter>}

```

The <file> parameter in all cases is a file variable which refers to the file on which to append character strings. If the <file> parameter is omitted, output is written to file **output** (the computer standard output).

6.2.4 Write Parameters

The WRITE and WRITELN procedures can control the format of the individual elements that are written. Each parameter to WRITE or WRITELN is of the form:

```

<write parameter> ::= <element>
                    | <element>:<field width>
                    | <element>:<field width>:<fraction size>
<element> ::= is the value to be written.
              (see descriptions below)

```

<field width> ::= <integer expression>

<fraction size> ::= <integer expression>

<element> is the value to be written. It may be of type **char**, **integer**, **real**, **double**, **Boolean**, **string** or **packed array of char**.

<field width> and <fraction size> are optional. If <fraction size> is present, <field width> must also be present.

<field width> specifies the size of the output field into which the converted value is written. If the converted value is smaller than <field width>, the field is filled out with leading spaces.

<fraction size> is only applicable when the <element> is of type **real** or **double** (see below).

6.2.4.1 Integer Element

The value of the **integer** expression is converted into a string representation of that expression in the base 10. The resulting string is placed right justified into the output field if a field width greater than needed is specified. If `<field width>` is too small to contain the resulting character string, the output field is expanded until it can contain the output string. If the integer expression is negative in value, a minus sign precedes the leftmost significant digit in the field. If the integer expression is positive, no space precedes the character string unless the `<field width>` is greater than the number of characters to be printed. If `<field width>` is omitted, the default field width is eight (8) characters.

6.2.4.2 Real or Double Element

A **real** or **double** element is converted much the same as an integer element, except that there can be a specification for the number of digits after the decimal point. In this case, `<fraction size>` specifies the number of digits to appear after the decimal point. The converted value is then written in so called "fixed point" notation. If `<fraction size>` is omitted, the converted number is written out in the floating or exponential notation. The diagram below illustrates the different forms of writing real elements.

```
WRITE(number:f)           results in a number of the form:
  _x.yyyyyE+nn
```

where "f" is the total number of characters in the converted number. There is one digit before the decimal point and "f"-7 digits after the decimal point.

```
WRITE(number:f:w)        results in a number of the form:
  xxx.yyy
```

where "f" is the total number of characters (including the decimal point), and "w" is the number of digits after the decimal point.

The extreme **real** and **double** values are printed as follows: positive infinity prints as a row of + signs; negative infinity prints as a row of - signs; NaN (Not a Number) prints as a row of ? marks.

6.2.4.3 Scalar Subrange Element

A write parameter which is a scalar subrange is handled exactly as the scalar range of which it is a subrange.

6.2.4.4 Character Element

A write parameter which is a character is output as a single string character right justified in the output field. If <field width> is greater than one (1), the field is filled with leading spaces.

Furthermore, an <element> of type **char** means that the two programs displayed below are equivalent.

```
WRITE(file, <char expression>:field width)
                                     is equivalent to
file^ := ' ';   { these two statements repeated ..... }
PUT(file);     { <field width> - 1 times                }
file^ := <char expression>;   PUT(file)
```

6.2.4.5 String Element or Packed Array of Char

A write parameter which is a string or packed array of **char** expression is placed right justified into the output field with leading spaces. If <field width> is less than the dynamic length of the string expression, the output field is expanded to contain the string. If <field width> is omitted, the output field is the minimum length needed to hold the string.

6.2.4.6 Boolean Element

An expression which is of type **Boolean** is written as one of the standard reserved words **False** or **True**. If <field width> is greater than the length of the resulting string (5 for "False"; 4 for "True"), the string is written with leading spaces. If <field width> is less than the length of the string, the field is expanded to contain the string. If the value of the expression is not a valid **Boolean**, the string "UNDEF" is printed.

6.2.5 WRITE to file of any type

The WRITE intrinsic can also write to a file of any type. A WRITE procedure call of the form:

```
WRITE(file, expr1, expr2, ..., exprn);
```

is equivalent to the sequence:

```
file^ := expr1; PUT(file);
file^ := expr2; PUT(file);
      .
      .
file^ := exprn; PUT(file);
```

where the expr_n are a list of expressions to be written to the file.

Note that the type of each expression in the list must be the same as the type of the elements in the file. Integer subranges are converted to the proper length as needed.

6.2.6 SEEK - Random Access to Typed Files

SVS Pascal supports random access to files of specific types. The SEEK procedure has two parameters, namely the file variable and an integer specifying the record number to which the file window should be moved. SEEK can only be applied to typed files that are not text files. The format of SEEK is:

```
procedure SEEK(file: file_type; position: integer);
```

file is the file variable for the specified file.

position is the number of the record to which the file window is to be moved. Records are numbered sequentially from zero (0).

SEEK moves the file window to the "position"th record in the file specified by "file". The EOF and EOLN predicates are set to false.

An attempt to PUT a record beyond the physical end of file sets the EOF predicate true. The physical end of file is the place where the next record in the file would overwrite another file on the storage device.

If a GET or PUT is not performed between two SEEK procedures, the contents of the file window are undefined.

6.2.7 CLOSE - Close a File

CLOSE removes the association of a file variable with an external file. A CLOSE procedure call marks the file as closed. The file variable for that file is then undefined. If a file is already closed, a CLOSE call does nothing. The form of the CLOSE procedure is:

procedure CLOSE(file [, close_option]);

file is a file variable.

close_option is an optional parameter that controls the disposition of the closed file. "close_option" can be one of the following:

normal The state of the file is set to closed. If the file was opened with a RESET procedure call, the "normal" option means that the file is retained in the file system. If the file was opened with a REWRITE procedure call, the "normal" option means that the file is removed from the file system. The "normal" option is the default.

lock makes the file permanent in the disk system if it is a disk file. Any existing file of the same name is removed from the file system. If the file is not a disk file, a "normal" close is done.

purge deletes the file from the file system if the file is on a block-structured device. If the file associated with "file" is a device instead of a block-structured volume, the device is set off-line. If no physical device or file is associated with "file", a "normal" close is done.

crunch is the same as the "lock" option but in addition, truncates the file at the point at which it was last

accessed. That is, the end of the file is the position at which the last PUT or GET was performed.

6.3 Block Input Output Intrinsic

BLOCKREAD and BLOCKWRITE support random (block level) access to untyped files only.

6.3.1 BLOCKREAD - Read Block from File

BLOCKREAD reads specific blocks from an untyped file. The function definition is:

```
function BLOCKREAD(file, where, blocks [,relblock]): integer;
```

file is an untyped file.

where is a variable of any type. The variable must be large enough to contain the number of blocks requested.

blocks is an integer value which specifies the number of blocks to read from the file.

relblock is an optional parameter. If "relblock" is present, it represents the block number at which to start reading from. Blocks are numbered relative to zero (0).

if "relblock" is omitted, it implies a sequential read of the next block in the file. When the file is opened, or when the file is reset, the starting block number is set to zero (0). Thus a BLOCKREAD with the "relblock" parameter omitted starts reading from block zero, and reads sequential blocks on every subsequent call that has the "relblock" parameter omitted.

The return value of BLOCKREAD is the number of blocks actually read. If the value is zero, it indicates either end-of-file or an error condition. If the value is greater than zero, it indicates the number of blocks read. If the return value is less than the number of blocks specified in the function call, it is possible that an end-of-file was encountered during the read.

6.3.2 BLOCKWRITE - Write Block to File

BLOCKWRITE writes specific blocks to an untyped file. The function definition is:

```
function BLOCKWRITE(file, where, blocks [,relblock]): integer;
```

file is an untyped file.

where is a variable of any type. It must be large enough to contain the number of blocks to be transferred.

blocks is an **integer** value which specifies the number of blocks to write to the file.

relblock is an optional parameter. If "relblock" is present, it represents the block number at which to start writing to. Blocks are numbered relative to zero (0).

if "relblock" is omitted, it implies a sequential write of the next block in the file. When the file is opened, or when the file is reset, the starting block number is set to zero (0). Thus a BLOCKWRITE with the "relblock" parameter omitted starts writing to block zero, and writes blocks sequentially on every subsequent call that has the "relblock" parameter omitted.

The return value of BLOCKWRITE is the number of blocks that were actually written. If the return value is zero, it means either that there was an error or that there is no room for the blocks on the device. If the value is greater than zero, it indicates the number of blocks written. If the return value is less than the number of blocks specified, it means that the end-of-file was encountered.

6.4 Unit Input Output

SVS Pascal provides UNIT input-output facilities that are compatible with those of UCSD Pascal. Unit input output provides the means to communicate directly with devices (units) on the system.

Note that because unit input output explicitly addresses specific units, data transfers to or from units cannot be re-directed at the system level.

6.4.1 UNITBUSY - Check if Unit Busy

UNITBUSY checks if the specified unit is busy (waiting for an input output transfer to complete). If the unit is busy, UNITBUSY returns true, otherwise UnitBusy returns false. The function definition is:

```
function UNITBUSY(UnitNumber: integer): Boolean;
```

For example, UNITBUSY(1) is true if the is data available at the console.

"UnitNumber" is an integer expression which is the number of the device to check.

6.4.2 UNITCLEAR - Initialize the Unit

UNITCLEAR cancels all input output to a specified unit, and then resets that unit to its initial state. The function definition is:

```
procedure UNITCLEAR(UnitNumber: integer);
```

The IORESULT function can be used to check if an error occurred.

6.4.3 UNITSTATUS - Get Status of Device

UNITSTATUS obtains status information for a specific device. The function definition is:

```
procedure UNITSTATUS(UnitNumber: integer;
                      var StatusRecord;
                      Control: longint);
```

UnitNumber is an integer expression which is the device number from which to return status.

StatusRecord may be a variable of any type. Its size and the values returned are determined by the specific driver.

Control is an integer expression whose value depends upon the specific input-output driver associated

with that unit.

6.4.4 UNITREAD - Read from a Unit

UNITREAD reads bytes from a specified device. UNITREAD performs no limit checks on the transfer area. It is the caller's responsibility to ensure that the variable is large enough for the transfer. The definition is:

```
procedure UNITREAD(UnitNumber: integer;
                   var MemoryArray;
                   TransferLength: longint;
                   BlockNumber: longint;
                   mode: integer);
```

UnitNumber is the number of the unit to read from.

MemoryArray is the variable in memory into which the bytes are to be transferred. MemoryArray can be of any type.

TransferLength is the number of bytes to read.

BlockNumber is optional. It is the number of the block from which the read is to start. Blocks are numbered from zero, and defaults to zero. BlockNumber only has meaning when the device is a blocked device.

mode is optional and device-dependent.

Note there is a potential problem with using the UNITREAD intrinsic to read a single character to an unpacked char object. Consider the following program fragment:

```
var
    one_char: char;

    UNITREAD(some_unit, one_char, 1);
```

This example will not have the expected result. SVS Pascal represents a single unpacked char variable such as "one_char" as a 16-bit word, with the character normally occupying the least significant eight bits. The UNITREAD intrinsic in the above example, however, reads bytes on a byte-by-byte basis, and so the single read places the byte into the upper eight bits of the "one_char" variable, leading to erroneous results. The "some_unit" unit number in the example is irrelevant to the discussion - it doesn't matter which unit is involved in the transfer.

In order to have this program fragment work correctly, the program would have to be changed as follows:

```
var
  two_char: packed array [0 .. 1] of char;
  UNITREAD(some_unit, two_char, 1);
```

which reads the data into the 0'th element of "two_char".

6.4.5 UNITWRITE - Write from a Unit

UNITWRITE writes bytes from a specified device. UNITWRITE performs no limit checks on the transfer area. It is the caller's responsibility to ensure that the transfer area is large enough. The definition is as follows:

```
procedure UNITWRITE(UnitNumber: integer;
                    var MemoryArray;
                    TransferLength: longint;
                    BlockNumber: longint;
                    mode: integer);
```

UnitNumber is the number of the unit to write from.

MemoryArray is the variable in memory from which the bytes are to be transferred. MemoryArray can be of any type.

TransferLength is the number of bytes to write.

BlockNumber is optional. It is the number of the block from which the write is to start. Blocks are numbered from zero, and defaults to zero. BlockNumber only has meaning when the device is a blocked device.

Mode is optional and device-dependent.

Note that doing a UNITWRITE from an unpacked **char** object can lead to the same problems as described under UNITREAD, above.

6.4.6 Notes On UNIT Input and Output

UNIT input output performs the function of direct communication with a unit (device) in the computer system. When the Pascal system performs UNIT transfers, no code conversions or any other changes are done to the stream of bytes as they pass through the system.

As was mentioned in UNITREAD, the actions on a single character UNIT transfer to or from an unpacked **char** object do not lead to the expected results, because an unpacked **char** data object is stored as a word, with the actual character in the least significant eight bits. UNIT transfers are done on a strict byte-by-byte basis, and are unaware of the data type of the object to or from which the transfer is being performed.

Similarly, **string** data objects have the string length as their first byte, so a UNITWRITE of a **string** will first send out the length byte, which is not necessarily a printable ASCII character. A UNITREAD to a **string** variable would place the first character read into the length byte. Again, this does not always lead to the desired result. It is up to the programmer to ensure the correct interpretation of data involved in UNIT transfers.

6.5 IORESULT - Return Input-Output Result

IORESULT is a function that can be used after an input-output operation to check on the validity of the operation. The function definition is:

```
function IORESULT: integer;
```

Use of the IORESULT function is only appropriate if I/O checking has been turned off. The \$I- compiler option turns checking off. If I/O checking is on (as it is by default) or turned on via the \$I+ compiler option, any I/O error generates a non-recoverable run-time error.

If I/O checking has been turned off, I/O errors do not generate run-time errors, and the programmer can then use IORESULT to check the completion status of each input output operation.

The value of IORESULT is zero if an input-output operation has a normal completion. If the value is non-zero, it indicates some form of error has occurred. See appendix A - "Messages from the Pascal System" for a list of error codes.

Example of using IORESULT

```
{ $I- } { Turn off the I/O Checking }
type
  data_file = file of text;
var
  data: data_file;

  RESET(data, '/source/printer');
  if IORESULT <> 0 then begin { <> 0 = problem }
    REWRITE (data, '/source/printer'); { so create it }
    if IORESULT <> 0 then begin
      WRITELN('Cannot create printer file');
      HALT
    end;
  end;
```

In the above example, the \$I- comment toggle turns off the I/O checking for that part of the program. The IORESULT function returns a non-zero value to mean that the file could not be RESET, so the program then tries a REWRITE statement. If that fails, then the program halts.

Chapter 7

Program Structure

A Pascal program is a collection of declarations and statements which is meant to be translated, via a compilation process, into a relocatable object-module. Object modules obtained from other, separate compilations can be combined, via a linking process, into a form suitable for execution.

The collection of declarations and statements may also include compiler directives which control the compilation, and do not change the meaning of the program.

7.1 Compilation Units

SVS Pascal implements independent compilation via the unit concept of UCSD Pascal. A compilation unit is either a program (a main program), or a unit. A complete executable program consists of a single program and zero or more units.

A **program** is a main program, consisting of all the statements between a **program** statement and an **end.** statement. The main program is described in more detail later in this chapter, in the section entitled "Program Heading".

A **unit** is a collection of declarations and statements packaged so as to make parts of the declarations in the unit public to other parts of the same compilation unit or separate compilation units. Units are useful for sharing common code among different programs or as a means to avoid compiling a huge program every time one line is changed. Units are compiled separately.

A program or unit that uses another unit is known as a "host". A host uses other units' declarations by naming those units in **uses** declarations. The **uses** clause appears after a program heading or it appears in a unit at the start of the **interface** section (see below).

A unit contains two major parts, namely an **interface** part which describes how other units view this unit, and an **implementation** part which supplies the actual body of code to implement this unit.

```

<unit> ::= unit <identifier>;
        <interface part>
        <implementation part>
        end.

<interface part> ::= interface
                    <uses clause>
                    <constant definition part>
                    <type definition part>
                    <variable definition part>
                    <procedure and function declaration part>

<implementation part> ::=
                    implementation
                    <label declaration part>
                    <constant definition part>
                    <type definition part>
                    <variable definition part>
                    <procedure and function declaration part>

<uses clause> ::= uses <identifier> {,<identifier>} ;

```

The **interface** part declares constants, types, variables, procedures and functions that are globally available. A host program that uses that unit has access to those objects just as if they had been declared in the host program itself.

Procedures and functions declared in the **interface** part consist only of the procedure or function name and the description of the formal parameters. These declarations serve as procedure or function prototypes - there is no executable code associated with them. This is equivalent to a **forward** declaration except that no **forward** attribute is allowed.

The **implementation** part follows the **interface** part. Local objects are declared first, then the global procedures and functions are declared. Formal parameters and function result type declarations are omitted from the **implementation** part, since they were already declared in the **interface** part.

A unit can consist entirely of interface declarations (constants, types and variables). There need not be any procedure or function declarations.

The overall layout of a **unit** is like this:

```

unit GanipGanop;

interface      { This part declares the
                 interface section }

uses names of  { This part is optional if
  other units   { GanipGanop does not use any
                 things from other units
                 Note that any declarations
                 imported from other units are
                 also public to any unit that
                 uses GanipGanop. }
{..... declarations and
  procedure headings
  for the GanipGanop unit.
  All these declarations and procedure
  headings are PUBLIC to other units .....,}

implementation { This part declares the
                 implementation section }
{..... declarations and
  code for the GanipGanop unit.
  All these declarations and code are
  PRIVATE to GanipGanop .....,}
end.           { of the GanipGanop unit }

```

7.2 Declarations and Scope of Identifiers

Declarations introduce program objects, together with their identifiers, which denote these objects elsewhere in a program.

```

<declaration> ::= <label declaration>
                | <constant declaration>
                | <type declaration>
                | <variable declaration>
                | <procedure or function declaration>

```

The program region (over which all uses of an identifier are associated with the same object) is called the scope of the identifier. Within a compilation unit, such a region is either a unit body or a block body. In the case of a unit, the scope is a declaration list. In the case of a block, the scope is a statement list preceded by an optional declaration list.

The scope of an identifier is determined by the context in which it was declared.

A program or a unit is a static construct intended to control the scope of identifiers according to these rules:

1. The scope of an identifier declared at the outermost level of a program is the body of that program.
2. The scope of an identifier listed in the **interface** part of a unit is the body of that unit, and is also extended "outwards" to any other unit that uses that unit.
3. Identifiers declared at the outermost level of the **implementation** part of a unit have the entire body of that unit as their scope, but are private to that unit.

Procedure or function blocks also control the scope of identifiers. There are both similarities with, and differences from, programs or units.

Like programs or units, blocks control the scope of identifiers.

Unlike programs or units, blocks control the processing of declarations and determine when the declarations take effect.

The block-structured scope rules are as follows:

1. The scope of an identifier declared in the declaration list of a block is the body of that block.
2. If the scope of an identifier includes another block, its scope is extended "inward" to include the body of that inner block, unless the body contains a re-declaration of that identifier.
3. An identifier which is declared as a formal parameter of a procedure or function has as its scope the body of that procedure or function.
4. Field selectors are identifiers introduced as part of the definition of a record type for the purpose of selecting fields of records. The scope of a field selector is the record in which it is declared. As with the nesting of procedures, the existence of an inner scope identifier masks the accessibility of any outer identifiers of the same name. Field selectors must be unique within the declaration of a record.
5. Identifiers must be unique within the bounds of a given scope.

7.3 Program Heading

The **program** statement identifies the main program for a Pascal compilation. In SVS Pascal, the program header is scanned but otherwise ignored. A program has the same form as a procedure declaration except for the heading.

```
<program> ::= <program heading> {<uses clause>} <block>.
<program heading> ::=
    program <identifier> {(<program parameters>)};
<program parameters> ::= <identifier> {,<identifier>}
```

The identifier following the word **program** is the program name. It has no further meaning inside the program. The program parameters are optional. No global identifiers in the program may have the same name as any of the program parameters.

7.3.1 Predeclared Variables

SVS Pascal supplies five pre-declared variables. First there are standard files :

input	is the standard file from which console input can be done via READ and READLN statements,
output	is the standard file to which console output is directed via WRITE and WRITELN statements,
stderr	is the standard error output file. On those operating systems which support a separate file for error responses, stderr is connected to that stream. On those operating systems which do not support a separate file for error responses, stderr is connected to the same place as output .

Then there are the two variables associated with obtaining arguments from the operating system command line (see the next subject heading below):

argc	is a count of the number of arguments supplied on the command line.
-------------	---

argv is an array of pointers to the character strings containing the command line arguments.

7.3.1.1 ARGV and ARGV - Access to Command Line

As mentioned above, "argc" and "argv" provide access to the Pascal program's command line as the user typed it. "argc" and "argv" can be considered to be defined by a declaration of the form:

```

type
  pstring = ^string;

var
  argc: integer;
  argv: array[1 .. argc] of pstring;

```

Each element of argv contains a separate field from the command line that invoked this Pascal program. If "argc" is zero (0), no attempt should be made to reference "argv". The first element of "argv" is the first parameter from the command line. The name of the command itself is not available. Avoid assigning to any element of "argv".

7.4 Declarations

7.4.1 Label Declarations

The label declaration part declares all labels (which tag statements) in the statement part of the block.

```
<label declaration part> ::= label <label> {, <label>;}
```

7.4.2 Constant Definition

The constant definition part declares all constant names and their associated values that are local to the procedure or function definition.

```

<constant definition part> ::= const <constant definition list>
<constant definition list> ::=
    <constant definition> {<constant definitio

```

7.4.3 Type Definition

The type definition part contains all the type definitions that are local to the procedure or function definition.

```
<type definition part> ::= type <type definition list>
<type definition list> ::= <type definition> {<type definition>}
```

7.4.4 Variable Declaration

The variable declaration part contains a definition of all the variables that are local to the procedure or function.

```
<variable declaration part> ::= var <variable declaration list>
<variable declaration list> ::=
    <variable declaration> {<variable declaration>}
```

7.5 Procedure and Function Declaration

A procedure declaration or a function declaration associates an identifier (the procedure or function name) with a collection of declarations and statements. A Pascal statement can then cause that procedure to be executed (activated) by giving its name in a procedure reference statement. A function declaration is similar to that of a procedure with the additional capability that a function can compute and return a value, called the value of the function. A function is referenced by giving its name in an expression, when the value of the function appears as a factor in that expression.

The type of value that a function returns is specified when the function is declared. The function return value is the value last assigned to its function identifier before a return is made from the function. Returning from a function without ever assigning a value to the function designator (for the current activation of the function) produces an undefined result (usually with undesirable results from the programmer's viewpoint).

Using a procedure or function identifier within the declaration of that procedure or function implies recursive activation of that procedure or function, except when a function identifier appears on the left hand side of an assignment statement,

(implying assignment to the function variable rather than recursive activation - see below).

```

<procedure declaration> ::= <procedure heading> <block>
<block> ::= <label definition part>
           <constant definition part>
           <type definition part>
           <variable declaration part>
           <procedure and function declaration part>
           <statement part>
<statement part> ::= begin <statement list> end
<statement list> ::= <statement> {; <statement>}

```

All the definition and declaration parts above are optional, with the exception of the <statement part>.

The procedure heading specifies the identifier that names the procedure, and any formal parameters for that procedure.

Procedure parameters are either value parameters, variable parameters, or procedure or function parameters.

```

<procedure heading> ::=
  procedure <identifier>; {<attribute>;}
| procedure <identifier> (<formal parameters>); {<attribute>;}
<function heading> ::=
  function <identifier>: <result type>; {<attribute>;}
| function <identifier>(<formal parameters>);{<attribute>;}
<formal parameters> ::=
  <formal parameter> {;<formal parameter>}
<formal parameter> ::=
  <parameter group>
  | var <parameter group>
  | <procedure heading>
  | <function heading>
<parameter group> ::=
  <identifier> {,<identifier>}:<type identifier>
  <attribute> ::= external | forward | cexternal
<result type> ::= <simple type>

```

Note that the "external", "forward", and "cexternal" attributes are optional.

7.5.1 External and Forward Attributes

A Pascal host can use routines that are separately compiled or assembled in languages other than Pascal. To use an external routine, the host must make a **procedure** or **function** declaration for that external routine just as if it is a Pascal routine that is declared in this compilation unit or another compilation unit. The declaration is then followed by the **external** attribute to indicate that the body routine does not appear in the current compilation unit. External routines must conform with the Pascal calling conventions and data representation methods as defined in appendix E - "Data Representations". The **cexternal** attribute means that the compiler generates calls to external procedures in a manner which is compatible with the SVS C compiler.

Pascal normally dictates that procedures and functions be declared before they can be referenced. There are cases when program layout makes this impossible, such that a procedure or function must be referenced before it can be declared. The **forward** attribute indicates that the particular procedure or function declaration consists only of the header, and that the body of that procedure or function appears later in the program source text, possible after it is referenced. A forward-declared procedure or function, then, is actually declared in two distinct parts: its header or prototype is declared, with the **forward** attribute, before any reference is ever made to it; at some later point in the program source text, its body is declared. At this later point, the formal parameter section must not appear.

7.5.2 Parameters for Procedures and Functions

Parameters (also called arguments) provide a dynamic substitution method such that a procedure or function can process different sets of data in different activations.

There is a correspondence between the formal parameters declared in a procedure or function heading and the actual parameters supplied when the procedure or function is activated.

The procedure or function heading declares a list of formal parameters. These are "dummy" variables that are assigned values when the procedure or function is activated.

A reference to the procedure or function supplies a list of actual parameters that are substituted for the formal parameters, which then become local variables initialized to the value of the

actual parameters.

There are four kinds of formal parameters:

- . Value parameters.
- . Variable or Reference parameters.
- . Procedure parameters.
- . Function parameters.

A parameter group without a preceding specifier, implies that the parameter is a value parameter.

7.5.2.1 Value Parameters

Value parameters are those whose formal parameter declaration has no symbol marking them as one of the other three forms. The corresponding actual parameter must be an expression. In the body of the procedure or function, the formal parameter is initialized to the value of the expression at the time the procedure or function is activated. The formal parameter is then just like a local variable. The value of the formal parameter may be changed by assignment - the actual parameter remains unchanged.

7.5.2.2 Variable Parameters

Variable parameters, also called reference parameters, are those whose declarations start with the symbol var (for variable). The actual parameter must be a variable of a type which is identical to that of the formal parameter. The formal parameter directly represents, and can change, the actual parameter's value during the entire execution of the procedure or function.

var actual parameters must be distinct actual variables. It is a programming error to supply the same variable to more than one actual parameter in a procedure or function reference.

All index computations, field selection and pointer dereferencing are done at the time the procedure or function reference is made.

7.5.2.3 Procedure and Function Parameters

Procedure and Function parameters are the names and parameter lists of procedures or functions that can be referenced by the current procedure. These parameters are indicated by the symbol procedure or function in the formal parameter declarations. Such

procedures or functions are called parametric. Actual parameters to parametric procedures and functions must be of identical type to those declared in the formal parameter declarations.

Examples of Procedure and Function Declarations

```

      { a procedure with only value parameters }
procedure ByTheBook(Chapter, Verse: integer);
begin
    Chapter := 1;      { does not change the caller's
                       version of Chapter }
end;

      { a procedure with variable parameters }
procedure Change(var winds: integer);
begin
    winds := 76;      { Changes the caller's version }
end;

      { the Ackerman function }
function Ackerman(m, n: integer):integer;
begin
    if m = 0 then
      Ackerman := n + 1
    else if n = 0 then
      Ackerman := Ackerman(m - 1, 1)
    else
      Ackerman := Ackerman(m - 1, Ackerman(m, n - 1))
    end;

      { parametric function parameter }
function Integrate(lo, hi: real;
                  what(x: real):real): real;
var
    start: integer;
    finish: integer;
    point: integer;
    current: real;
    sum: real;

begin
    start := TRUNC(lo);

```

```
finish := ROUND(hi);
sum := 0.0;

for point := start to finish do
begin
    current := point;
    sum := sum + what(current);
end;
Integrate := sum / (finish - start);
end
```

Chapter 8

Standard Procedures and Functions

SVS Pascal (in common with other Pascal implementations) supplies a number of standard ("built in") procedures and functions. This Chapter covers those. The standard procedures and functions fall into several logically related groups, as follows:

- . String Manipulation. These intrinsics handle the SVS Pascal dynamic string types.
- . Memory Management. These intrinsics deal with dynamic memory allocation and de-allocation.
- . Arithmetic Functions.
- . Boolean Predicates.
- . Conversion Functions.
- . Miscellaneous Low Level Procedures and Functions.

8.1 String Manipulation Facilities

This section discusses those facilities for manipulating string data types in Pascal. Here is a brief summary of the facilities:

CONCAT	concatenate a number of strings into one string.
COPY	Extract substring of a string.
DELETE	delete characters from a string.
INSERT	insert characters into a string.

LENGTH determine the current dynamic length of a string.

POS Scan for a pattern within a string.

SCANEQ and SCANNE
 scan for a specific character within a string.

8.1.1 LENGTH - Determine String Length

LENGTH is an **integer function** that returns the length of a string expression. The function definition is:

```
function LENGTH (source: string): integer;
```

LENGTH returns an integer value which is the dynamic length of the string "source".

The length of the string '' is zero (0).

Examples of LENGTH

```
alphabet := 'abcdefghijklmnopqrstuvwxy';
WRITELN(LENGTH(alphabet), ' ',
        alphabet[1], ' ',
        alphabet[LENGTH(alphabet)], ' ',
        LENGTH(''));

```

the following output is displayed

```
26    a    z    0
```

8.1.2 COPY - Copy a Substring

COPY returns a **string** which is a substring of another string. The function definition is:

```
function COPY(source: string;  
              index: integer;  
              size: integer): string;
```

COPY returns a string which is a substring of the string "source". **COPY** extracts "size" characters from "source", starting at the character position given by "index".

The first character in the string is numbered 1.

If "index" is negative or zero, the result is a null string.

If "index" is greater than LENGTH(source), the result is a null string.

If "index" + "size" is greater than LENGTH(source), the result is a string which extends from "index" to LENGTH(source).

Example of COPY

```
var
  left: string[100];
  middle: string[100];
  right: string[100];
  title: string[255];

  title := 'Left Side. Middle Part. Right Side.';
  left := COPY(title, 1, 10);
  middle := COPY(title, 12, 12);
  right := COPY(title, 25, 11);
  WRITELN(left);
  WRITELN(middle);
  WRITELN(right);
```

This should generate the output:

```
Left Side.
Middle Part.
Right Side.
```

8.1.3 CONCAT - Concatenate Strings

CONCAT returns a string result, which is the concatenation of its (string) parameters. The function definition of CONCAT is:

```
function CONCAT (s1: string;
                 s2: string; .....
                 sn: string): string;
```

Each of the "Sn" is a string variable or a string constant or a literal value. There may be any number of source strings, each separated by a comma from the next. There must be at least two source strings.

Example of CONCAT

```
title := CONCAT('Here', ' ', 'there', ' ', 'and everywhere');  
WRITELN(title);
```

This should generate the output:

```
Here, there, and everywhere
```

8.1.4 POS - Match a Substring in a String

POS is used for string matching. The function definition is:

```
function POS (pattern: string;  
             inwhat: string): integer;
```

POS scans from left to right trying to find an instance of the string "pattern" in the string "inwhat". If a match is found, POS returns an integer value that is the position in "inwhat" at which the "pattern" starts to match.

If there is no match, the result is zero (0).

If "pattern" is longer than "inwhat", the result is zero (0), or no match.

Example of POS

```
herbs := 'Basil, Chervil, Fennel, Tarragon';  
WRITELN(POS('Chervil', herbs), ' ', ' ', POS('Nutmeg',  
herbs));
```

This should generate the output:

```
8      0
```

8.1.5 SCANEQ and SCANNE - Scan for Character

SCANEQ and SCANNE search a character array until they find (SCANEQ) or do not find (SCANNE) a specified character in the array. The function definitions are:

```
function SCANEQ(len: integer; what: char; object): integer;  
function SCANNE(len: integer; what: char; object): integer;
```

SCANxx scans "object" for "len" characters, or until the character "what" is found (SCANEQ) or not found (SCANNE). The result is the offset into "object" where the scan stopped. If the character "what" is not found (SCANEQ) or is found (SCANNE), SCANxx returns the value "len". If the "len" parameter is positive, scanning is from left to right; if the "len" parameter is negative, the scan proceeds from right to left, and a negative value is returned.

Note that the SCANxx functions simply look at bytes in memory. They ignore any higher level structure that the user might perceive or might have imposed on the object. Thus "object" is simply an address in memory at which to begin scanning (or in the case where "len" is negative, to end the scan). Thus, for example, if the programmer were to do a SCANEQ on a data type of `string[80]`, the length byte of that string would also be scanned, and the results might be unexpected.

8.1.6 DELETE - Delete Characters from String

DELETE removes a specified number of characters from a string. The procedure definition is:

```
procedure DELETE (destination: string;  
                  index: integer;  
                  size: integer);
```

"destination" is a string. "index" and "size" are integers.

DELETE removes "size" characters from "destination", starting at the position specified by "index".

If "index" is greater than `LENGTH(destination)`, there is no action taken.

If "index" is negative or zero, there is no action taken.

If "index" + "size" is greater than `LENGTH(destination)`, DELETE removes all characters from "index" up to the end of the "destination" string.

Example of DELETE

```

var
  large: string[100];

  large := 'A long exhausting rally, eh what, chaps';
  DELETE(large, 8, 11);
  Writeln(large);

```

This should generate the output:

A long rally, eh what, chaps

8.1.7 INSERT - Insert Characters into String

INSERT inserts one character string into another character string at a specified place. The procedure definition is:

```

procedure INSERT (source: string;
                  destination: string;
                  index: integer);

```

The "source" string is inserted into the "destination" string at a position determined by the value of "index".

If the length of the result string is greater than the static length of the destination string, the result varies depending on whether run-time range checking is on or off:

- . if range checking is on (the \$R+ option), a run-time error is generated.
- . if range checking is off (the \$R- option), the result string is truncated to fit into the declared length of the destination string.

8.2 Storage Allocation Procedures

Dynamically allocated storage is held in a large common storage pool, called a "heap". Storage is allocated from that pool by using the procedure NEW. Storage is released back to the pool (de-allocated) by using the DISPOSE procedure. Alternatively, some Pascal implementations handle memory de-allocation via the

MARK and RELEASE procedures. SVS Pascal provides MARK and RELEASE for compatibility.

NEW is responsible for allocating storage.

DISPOSE is responsible for freeing or releasing storage back to the common storage pool.

MARK provides a means to "remember" the current top of the heap.

RELEASE releases memory from a previously MARK'ed point.

MEMAVAIL determines the amount of memory available for allocation.

8.2.1 NEW - Allocate Storage

The procedure NEW allocates dynamically available storage. If "p" is a variable of type pointer to "T", NEW(p) allocates storage for a variable of type "T" and assigns a pointer to that storage to the variable "p". There are two forms of the NEW procedure reference:

NEW(p) allocates a new variable "v", and assigns the pointer reference of "v" to the pointer variable "p". If the type of "v" is a variant record, storage is allocated for the largest variant of the record. Storage for a specific variant can be allocated by using the second form of the NEW procedure, as follows:

NEW(p, t₁, t₂, ..., t_n) allocates a variable of the variant, with tag fields t₁ .. t_n. The tag fields must be listed contiguously and in the order of their declaration in the variant record type definition.

If NEW is used to allocate storage for a specific variant record, the subsequent call to DISPOSE must use exactly the same variant. Any mismatch between the variants specified on the call to NEW and those on the DISPOSE call can damage the integrity of the heap, causing strange behavior at best and system crashes at worst.

If NEW fails to allocate the requested storage (usually because the storage is not available), the pointer variable "p" contains the value nil upon return from the procedure.

Example of NEW

```

const
  UpperLimit = 255;

type
  LArray = array[1 .. UpperLimit] of integer;
  ArrayAddr = ^LArray;

var
  head: ArrayAddr;

  NEW(head);
  if head = nil then
    ..... take some recovery action .....
  else
    begin
      head^[1] := 0;      { zero fill array }
      MOVELEFT(head^[1], head^[2],
                SIZEOF(integer)*(UpperLimit - 1));
      ..... and so on .....
    end

```

8.2.2 DISPOSE - Dispose of Allocated Storage

DISPOSE frees (or de-allocates) dynamically allocated storage. The procedure reference:

```
DISPOSE (p);
```

frees up the allocated storage referenced by the pointer variable "p". Upon return from DISPOSE, the pointer variable "p" contains the value nil.

Attempts to DISPOSE using a pointer variable that contains nil is a no-op and is ignored.

If NEW was used to allocate a variable with a specific variant, DISPOSE should be called with exactly the same variant, else the heap is likely to be corrupted.

8.2.3 MARK - Mark Position of Heap

MARK is used to "remember" the current position of the top of heap. MARK and RELEASE are used together to de-allocate memory and return the top of the heap to a previously MARK'ed point. For example, a procedure might, upon entry, MARK the heap top,

then allocate large numbers of variables, and then, just prior to exiting, **RELEASE** all the allocated memory. Such a situation might occur, for instance, in allocating the local symbol table for an assembly unit. At the end of the unit, all the local labels need to disappear - **MARK** and **RELEASE** provide a handy means to dispose of storage in bulk. The procedure definition of **MARK** is:

```
procedure MARK(HeapPointer: ^anything);
```

"HeapPointer" must be a pointer - the pointer type is irrelevant but conventionally it is a pointer to a **longint**. "HeapPointer" must not be used for any purpose other than as a **MARK** pointer.

8.2.4 **RELEASE** - Release Allocated Memory

RELEASE is used to cut the heap back to a point previously **MARK**'ed. The procedure definition of **RELEASE** is:

```
procedure RELEASE(HeapPointer: ^anything);
```

As for **MARK**, "HeapPointer" is a pointer of any type but conventionally is a pointer to **longint**. **RELEASE** cuts the heap back to the place indicated by "HeapPointer". "HeapPointer" must have been properly initialized by a previous call to **MARK**. **MARK**'s and **RELEASE**'s must be matched properly.

8.2.5 **MEMAVAIL** - Determine Available Memory

MEMAVAIL returns the number of bytes available for allocation in the storage pool. The function definition of **MEMAVAIL** is:

```
function MEMAVAIL: longint;
```

8.3 Arithmetic Functions

8.3.1 **ABS** - Compute Absolute Value

ABS(x) computes the absolute value of its argument "x". The type of the result is the same as the type of "x", which must be either **integer**, **real**, or **double**.

8.3.2 SQR - Compute Square of a Number

SQR(x) computes the square of "x", that is, it computes x^2 . The type of the result is the same as the type of "x", which must be either integer, real, or double.

8.3.3 SIN - Trigonometric Sine

SIN(x) computes the trigonometric sine of the argument "x". The type of "x" may be either integer, real, or double. The return type of SIN is always real or double. The argument is in radians.

8.3.4 COS - Trigonometric Cosine

COS(x) computes the trigonometric cosine of the argument "x". The type of "x" may be either integer, real, or double. The return type of COS is always real or double. The argument is in radians.

8.3.5 ARCTAN - Trigonometric Arctangent

ARCTAN(x) computes the trigonometric arctangent of the argument "x". The type of "x" may be either integer, real, or double. The return type of ARCTAN is always real or double.

8.3.6 EXP - Compute Exponential of Value

EXP(x) computes the exponential of the argument "x". The type of "x" may be either integer, real, or double. The return type of EXP is always real or double.

8.3.7 PWROFTEN - Compute Ten to a Power

The function PWROFTEN(x) returns a value which is 10 raised to the power specified by the argument. The function definition is:

```
function pwrופן (exponent: integer): real;
```

The valid range of the "exponent" argument is 0 .. +38.

8.3.8 LN - Natural Logarithm of Value

LN(x) computes the natural logarithm of the argument "x". The type of "x" may be either **integer**, **real**, or **double**. The return type of LN is always **real** or **double**. It is an error to supply an argument less than or equal to zero.

8.3.9 SQRT - Square Root of Value

SQRT(x) computes the square root of the argument "x". The type of "x" may be either **integer**, **real**, or **double**. The return type of SQRT is always **real** or **double**. It is an error to supply an argument less than or equal to zero.

8.4 Predicates or Boolean Attributes

8.4.1 ODD - Test Integer for Odd or Even

ODD(x) determines if the argument is odd or even. The type of the argument "x" must be **integer**. The result is **true** if "x" is an odd number, **false** if "x" is an even number.

8.4.2 EOLN - Determine if End of Line Read

The function EOLN returns **true** if the textfile position is at an end-of-line character. Otherwise the EOLN function returns **false**. EOLN is only defined for files whose components are of type **text** or **interactive**.

8.4.3 EOF - Determine if End of File Read

The function EOF returns **true** if a read from a file encounters an end-of-file. EOF returns **false** in all other cases. To set EOF **true** for a file attached to the console, the EOF character must be typed. In SVS Pascal this is Control-D. For a textfile, EOF being true implies that EOLN is true as well.

If a file is closed, EOF returns **true**. After a RESET takes place, EOF is **false** for the RESET file. If EOF becomes **true** during a GET or a READ, the data obtained is not valid.

8.5 Value Conversion Functions

8.5.1 TRUNC - Truncate to Nearest Integer

The function TRUNC(x) truncates its argument "x" to the nearest integer. "x" must be of type real or double. If the result of truncating the argument "x" cannot be stored in an integer variable, the maximum integer value is returned.

For $x \geq 0$, the result is the largest integer $\leq x$.

For $x < 0$, the result is the smallest integer $\geq x$.

8.5.2 ROUND - Round to Nearest Integer

The function ROUND(x) rounds its argument "x" to the nearest integer. "x" must be of type real or double. The result is of type integer. If the result of rounding the argument "x" cannot be stored in an integer variable, the maximum integer value is returned.

For $x \geq 0$, the result is TRUNC(x+0.5).

For $x < 0$, the result is TRUNC(x-0.5).

8.5.3 ORD - Convert Type to Integer Value

The function ORD(x) returns an integer which is the ordinal number of the argument "x" in the set of values defined by the type of "x". The argument "x" can be any non-floating point scalar. For example:

```
var
  one_letter : char;
  converted  : integer;

begin
  one_letter := 'm';
  converted  := ORD(one_letter);
```

At the end of this program fragment, the variable "converted" has the value 109, since that is the ordinal position of lower case 'm' in the ASCII character set.

8.5.4 ORD4 - Convert to Long Integer

The function ORD4(x) returns a **longint** which is the ordinal number of the argument "x". As for ORD, the argument "x" can be any non-floating point scalar.

8.5.5 CHR - Integer to Character Representation

The function CHR(x) converts its argument "x" to a character. The argument "x" must be an **integer**. The result type of CHR is the character whose ordinal number is "x". The argument must therefore lie in the range 0 .. 255 for CHR to return a valid result.

8.6 Other Standard Functions

8.6.1 SUCC - Determine Successor of Value

The function SUCC(x) accepts an argument which is any scalar type except **real** or **double**. The result of SUCC is the successor value of the argument, if such a successor value exists.

SUCC(x) is undefined if "x" does not have a successor value.

8.6.2 PRED - Determine Predecessor of Value

The function PRED(x) accepts an argument which is any scalar type except **real** or **double**. The result of PRED is the predecessor value of the argument, if such a predecessor value exists.

PRED(x) is undefined if "x" does not have a predecessor value.

8.7 Miscellaneous Low Level Routines

8.7.1 MOVELEFT and MOVERIGHT

MOVELEFT and MOVERIGHT transfer a number of bytes from a source to a destination. MOVELEFT starts at the leftmost byte in the source (the first byte), while MOVERIGHT starts at the rightmost byte in the source (the last byte). In all cases the source and destination strings can overlap, with the appropriate undesired results if the move is in the wrong direction. The format of MOVELEFT and MOVERIGHT is:

```
procedure MOVELEFT(var source, var destination, length);
```

```
procedure MOVERIGHT(var source, var destination, length);
```

source is the place to move bytes from.

destination is the place to move bytes to.

length is an integer specifying the number of bytes to move.

"source" and "destination" can be any sort of type. If either "source" or "destination" is an array, the array can be subscripted. If either "source" or "destination" is a record, a field specification can be given.

For a MOVELEFT, the byte at "source" is moved to "destination" and so on until the byte at "source"+"length"-1 is moved to "destination"+"length"-1. For a MOVERIGHT, the move starts from the other end, so that the byte at "source"+"length"-1 is moved to "destination"+"length"-1 and so on until the byte at "source" is moved to "destination".

Neither MOVELEFT nor MOVERIGHT perform any range checking. They should therefore be used with a modicum of caution.

Example of MOVELEFT

The example shown below illustrates how MOVELEFT can be used to "zero fill" an array.

```

var
  manifold: array[1 .. 100] of -128 .. 127;

  manifold[1] := 0;      { place an initial zero }
  MOVELEFT(manifold[1], manifold[2], 99);

```

8.7.2 FILLCHAR - Fill A Storage Region With A Character

FILLCHAR is a procedure that replicates a byte throughout a region of storage. The procedure definition of FILLCHAR is:

```

procedure FILLCHAR(var address; integer count; char byte);

```

address is the address of an arbitrary storage location in memory. Note that 'address' is a var parameter to FILLCHAR, so it may not be the address of a packed object.

count is the number of times that the next parameter - 'byte' should be replicated.

byte is a single character value which is replicated throughout the region of storage starting at 'address' and ending at 'address'+ 'count'-1.

Example of FILLCHAR

The example shown below illustrates how FILLCHAR can be used to "space fill" a print buffer

```

var
  printbuf: array[1 .. 256] of char;

  FILLCHAR(printbuf, 256, ' ');

```

8.7.3 SIZEOF - Determine Size of Data Element or Type

SIZEOF is a function that returns the number of bytes that a variable or type is allocated. The function definition of SIZEOF is:

```

function SIZEOF(identifier): integer;

```

where "identifier" is a variable name or a type identifier. The SIZEOF function is particularly useful as a parameter to MOVELEFT or MOVERIGHT, or in performing unit input-output, where the number of bytes to transfer must be known.

8.7.4 POINTER - Convert Integer Expression to Pointer

POINTER converts an integer expression to a pointer value. The function definition of POINTER is:

```
function POINTER(expression): universal;
```

POINTER converts the "expression", which must be an integer expression, to a pointer value. The result type of POINTER is a "universal" pointer type that has the type of nil, which means that it may be assigned to any pointer variable.

8.8 Control Procedures

8.3.1 EXIT - Exit from Procedure

EXIT provides the means to "get out of" a procedure prematurely. EXIT finds especial use in recursive applications such as expression evaluators or tree-walking procedures. Its effect is to cause an immediate (and clean) return from a named procedure or function. The procedure definition of EXIT is:

```
EXIT(name);
```

where "name" is the name of the procedure or function to be exited.

If the "name" parameter is the name of a recursive procedure or function, the most recent activation of that procedure or function is terminated.

Files that are local to an EXIT'ed procedure or function are not implicitly closed upon exit - they must be closed explicitly before the EXIT statement.

If an EXIT statement is made inside a function before any assignment is made to the function identifier, the result of the function is undefined.

EXIT is exactly the same as a goto a label at the end of the named procedure or function.

8.8.2 HALT - Terminate Program with Return Value

The HALT procedure terminates the currently executing program. HALT returns a value to the host operating system to indicate a successful termination or an error termination. The procedure definition of the HALT procedure is:

```
HALT(i: integer);
```

The "i" parameter is optional. If the "i" parameter is omitted, by simply executing a:

```
HALT
```

statement, the correct "no error" code is returned to the host operating system.

The HALT procedure also returns a value to the CALL function, described below.

A list of the values which the HALT procedure can return can be found in appendix A - "Messages from the Pascal System".

8.8.3 CALL - Call up Another Program

The CALL function requests the host operating system to execute another program. The function definition of CALL is:

```
function CALL(pathname: string;
              var infile, outfile: interactive | text;
              fargv: ?; fargc: integer): integer;
```

The parameters to the CALL function are:

pathname is a string containing the pathname of the file in which the program resides which is to be run. The definition of what constitutes a pathname is operating system dependent.

infile and outfile specify the standard input and standard output for the program specified by "pathname". In addition, the definition specifies whether the standard input and standard output files for that program are text files residing in the file system, or the user's terminal.

fargv is an array of pointers to strings consisting of the options and filename arguments for the program in question.

fargc is an integer count of the number of arguments in "fargv".

The value returned from the CALL function is either the value which a program returns via a HALT call, or is one of the operating system error codes. A list of the values which the HALT procedure can return can be found in appendix A - "Messages from the Pascal System".

Chapter 9

Pascal Compile Time Options

Pascal compile-time options are introduced via toggles embedded in comments. Comment toggle format is like:

```
(* $T params *)
   or
{ $T params }
```

where either the (* and *) form, or the { and } form of comment delimiters may be used.

The toggle must immediately follow the opening comment delimiter, with no intervening spaces.

A comment toggle is always introduced by a \$ sign. The \$ sign is followed by the toggle letter, either in upper or lower case, followed by the parameters for that toggle. Compiler options that are followed by a + or - may be given in a list:

```
{ $C+,I+,L- .... }
```

There must not be any spaces after the commas in the list. Scanning of a list of compiler options terminates if any incorrect syntax is encountered.

Compiler options do not obey any of the Pascal scope rules. Once an option is selected by a toggle, it remains in effect until another toggle in the source text de-selects that option. Compiler options are described in the list below.

Some of the descriptions of the compiler options make references to the options specified on the compiler command line. A description of the command line options can be found in appendix G - "Using The Pascal Compiler".

\$C+ or \$C- Turns Code generation on (+) or off (-). This is done on a procedure by procedure basis. The value of the options at the end of a procedure controls code generation. The default is C+.

- \$E filename** starts listing Errors to the file specified by "filename". Also see the \$L option below.
- \$I filename** Include the file specified by "filename" at this point in the source.
- \$I+ or \$I-** Turn automatic Input Output checks on (+) or off (-). The default is I+.
- \$L filename** Make a compilation Listing on the file specified by "filename". If a listing file already exists, that file is closed and saved before the new file is opened.
- \$L+ or \$L-** Turn Listing on (+) or off (-) without changing the listing file name. The listing filename must be specified before turning listing on. The default is \$L+ (listing on) when a listing file has been specified on the compiler's command line or \$L- (listing off) when a listing file was not specified. When the list option is on, the listing is directed to whatever list file was specified on the Pascal compiler's command line.
- \$M+ or \$M-** The \$M+ option specifies that the Pascal run-time system should check the stack and heap for overflow upon entry to each procedure. The \$M+ option enables the check. The \$M- option disables the check. The default setting is \$M- (disable the check).
- \$P+ or \$P-** Specifies whether the Pascal compiler should prompt the user for corrective action when errors are detected. The \$P+ option indicates that the compiler should prompt the user as to whether to continue the compilation when errors are detected. The \$P- option disables the prompting feature. This feature is also available via the -p or +p option on the compiler command line. The default setting of the \$P option is operating system dependent.
- \$Q+ or \$Q-** Controls the amount of messages that the Pascal compiler prints while compiling a program. The \$Q+ option results in fewer messages. The \$Q- option results in more messages. The default setting of the \$Q option depends upon the operating system on which the Pascal system is running.

- \$R+ or \$R-** Turns Range checking on (+) or off (-). At present, range checking is done in assignment statements, on array indexes, and for string value parameters. The default setting is \$R+.
- \$S segment** Places code modules into the Segment specified by "segment". The default segment name is ' ' (eight spaces), which is where the main program and all built-in support code is always linked. All other code can be placed into any segment.
- \$S+ or \$S-** Is the swapping option. The \$S+ option specifies that the compiler should run in swapping mode. The \$S- option specifies that the compiler should not run in swapping mode. In operating systems which support generalized overlay schemes, swapping mode means that the compiler runs in less memory, at the expense of a considerable speed penalty. The \$S+ option (if used) must appear before the initial **program** or **unit** header, else the option has no effect. The default setting is \$S- (do not run in swapping mode).
- \$U filename** Searches for subsequent Units in the file specified by "filename".
- \$%+ or \$%-** Specifies that the percent sign % is a valid character (+) or is not a valid character (-) in identifiers. The default is \$%-.

Appendix A
Messages from the Pascal System

This appendix describes the error messages that the Pascal system generates.

A.1 Compile Time Lexical Errors

- 10 Too many digits in a number
- 11 Digit expected after '.' in a real number
- 12 Integer Overflow
- 13 Digit expected in the exponent of a real number
- 14 End of line encountered in a string constant
- 15 Invalid character in input
- 16 Premature end of file in source program
- 17 Extra characters encountered after the end of the program
- 18 End of file encountered in a comment

A.2 Compile Time Syntactic Errors

- 20 Illegal symbol
- 21 Error in simple type
- 22 Error in declaration part
- 23 Error in parameter list of a procedure or function
- 24 Error in constant
- 25 Error in type
- 26 Error in field list of a record declaration
- 27 Error in factor of an expression
- 28 Error in variable
- 29 Identifier expected

- 30 Integer expected
- 31 '(' expected
- 32 ')' expected

```
33 '[' expected
34 ']' expected
35 ':' expected
36 ';' expected
37 '=' expected
38 ',' expected
39 '*' expected

40 ':=' expected
41 program keyword expected
42 of keyword expected
43 begin keyword expected
44 end keyword expected
45 then keyword expected
46 until keyword expected
47 do keyword expected
48 to or downto keyword expected

50 if keyword expected
51 '.' expected
52 implementation keyword expected
53 interface keyword expected
```

A.3 Compile Time Semantic Errors

```
100 Identifier declared twice in the same block
101 Identifier is not of the appropriate class
102 Identifier not declared
103 Sign not allowed
104 Number expected
105 Lower bound exceeds upper bound
106 Incompatible subrange types
107 Type of constant must be integer
108 Type must not be real
109 Tagfield must be a scalar or subrange

110 Type incompatible with tagfield type
111 Index type must not be real
112 Index type must be scalar or subrange
113 Index type must not be integer or longint
114 Unsatisfied forward reference
115 Forward reference type identifier cannot appear in a variable
    declaration
116 Forward declaration - repetition of parameter list not
    allowed
117 Forward declared function - repetition of result type not
    allowed
```

- 118 Function result type must be scalar, subrange, or pointer
- 119 File is not allowed as a value parameter

- 120 Missing result type in function declaration
- 121 F-format for real type only
- 122 Error in type of parameter to a standard function
- 123 Error in type of parameter to a standard procedure
- 124 Number of actual parameters does not agree with declaration
- 125 Illegal parameter substitution
- 126 Result type of parametric function does not agree with declaration
- 127 Expression is not of **set** type
- 128 Only tests for equality allowed
- 129 Strict inclusion not allowed

- 130 Comparison of file variables not allowed
- 131 Illegal type of operand(s)
- 132 Operand type must be **boolean**
- 133 Set element type must be scalar or subrange
- 134 Set element types not compatible
- 135 Type of variable is not **array** or **string**
- 136 Index type is not compatible with declaration
- 137 Type of variable is not **record**
- 138 Type of variable must be file or pointer
- 139 Illegal type of loop control variable

- 140 Illegal Expression type
- 141 Assignment of files not allowed
- 142 Case selector incompatible with selecting expression
- 143 Subrange bounds must be scalar
- 144 Operand type conflict
- 145 Assignment to standard function is not allowed
- 146 Assignment to formal function is not allowed
- 147 No such field in this record
- 148 Type error in read
- 149 Actual parameter must be a variable

- 150 Multiply defined case selector
- 151 Missing corresponding variant declaration
- 152 **real** or **string** tagfields not allowed in variant record
- 153 Previous declaration was not **forward**
- 154 Substitution of standard procedure or function not allowed
- 155 Multiple defined label
- 156 Multiple declared label
- 157 Undefined label
- 158 Undeclared label
- 159 Value parameter expected

- 160 Multiple defined record variant
- 161 **File** not allowed here
- 162 Unknown compiler directive (not **external** or **forward**)

- 163 Variable cannot be a packed field
- 164 Set of real is not allowed
- 165 A field of a packed record cannot be a var parameter
- 166 Case selector expression must be a scalar or a subrange
- 167 String sizes must be equal
- 168 String too long
- 169 Value out of range

- 170 Cannot take the address of a standard procedure or function
- 171 Assignment to function result must be done inside that function
- 172 Control variable of a for statement must be local
- 173 BUFFERED or UNBUFFERED expected
- 174 NORMAL, LOCK, PURGE, or CRUNCH expected
- 175 File variable expected
- 176 Must be within the procedure or function being exited.

- 190 No such unit in this file

A.4 Specific Limitations of the Compiler

- 300 Too many nested record scopes
- 301 Set limits out of range (maximum sized set is 0 .. 2031)
- 302 String limits out of range
- 303 Too many nested procedures or functions
- 304 Too many nested include or uses files
- 305 Include not allowed in interface section
- 306 Pack and unpack are not implemented
- 307 Too many units
- 308 Set constant out of range
- 309 Maximum comparable packed array of char is of size 255 characters

- 310 Too many nested with statements
- 311 Too many nested function references
- 312 Record too big (maximum size is 32766 bytes)
- 313 Too many elements in an array, or array too big (maximum size of an array is 32766 bytes, or maximum number of elements is 32766 elements)
- 314 Too many variables in one scope (the maximum allowed is 32766 bytes in any one scope, including the global level)
- 315 Too many bytes of value parameters (maximum allowed is 32766 bytes in any one scope).

- 350 Procedure too large
- 351 File name in option too long

A.5 Input Output Errors

400 Not enough room for code file
401 Error in rereading code file
402 Error in reopening text file
403 Unable to open uses file
404 Error in reading uses file
405 Error in opening include file
406 Error in rereading previously read text block
407 Not enough room for intermediate code file
408 Error in writing code file
409 Error in reading intermediate code file

410 Unable to open listing file

A.6 Code Generation Errors

1000+ Code generator errors - in theory should never happen

A.7 IORESULT Error Codes

The codes listed below are those that the IORESULT function returns.

0 No Error - indicates a good result
1 Parity error or CRC error
2 Invalid device number
3 Invalid input-output request
4 Nebulous Hardware Error
5 Volume went off-line
6 File lost in directory
7 Bad file name
8 No room on volume
9 Volume not found
10 File not found

11 Duplicate directory entry
12 File already open

- 13 File not open
- 14 Bad input information
- 15 Ring buffer overflow
- 16 Write protect
- 17 Invalid seek 64 Device error of unknown origin

A.8 Codes Returned From the HALT Procedure

The codes listed below are those that the HALT procedure returns either to the operating system, or to the CALL function.

- 0 No Error - indicates a good result
- 1 No room in memory for code
- 2 Cannot read the executable code file
- 3 File is not a code file
- 4 File must be linked before it can be executed
- 5 Cannot open the code file
- 6 Too many processes
- 7 Not enough space for data (stack space)

If the HALT procedure returns a code of less than zero, the shell halts. This feature is for use in shell scripts.

If the HALT procedure returns a code of greater than 7, the shell simply prints the error number, but continues. Such error codes are available for user programs to convey information to other user programs.

Appendix B
Pascal Language Summary

.... "what is the use of repeating all that stuff",
said the Mock Turtle, "if you don't explain it as you
go along. It's by far the most confusing thing I ever
heard!"

Lewis Carroll. Through the Looking Glass

B.1 Predefined Identifiers

Constants

maxint	TRUE	FALSE
--------	------	-------

Types

Boolean	interactive	longint	text
char	integer	real	double

Variables

Argc	Argv	Input	Output
Stderr			

Procedures

CLOSE	HALT	PUT	UNITCLEAR
DELETE	INSERT	READ	UNITREAD
DISPOSE	MARK	READLN	UNITSTATUS
EXIT	MOVELEFT	RELEASE	UNITWRITE
FILLCHAR	MOVERIGHT	RESET	WRITE
GET	NEW	REWRITE	WRITELN
GOTOXY	PAGE	SEEK	

Functions

ABS	EOF	ORD	SCANNE
ARCTAN	EOLN	ORD4	SIN
BLOCKREAD	EXP	POINTER	SIZEOF
BLOCKWRITE	IORESULT	POS	SQR
CHR	LENGTH	PRED	SQRT
CONCAT	LN	PWROFTEN	SUCC
COPY	MEMAVAIL	ROUND	TRUNC
COS	ODD	SCANEQ	UNITBUSY

B.2 Pascal Syntax Definitions

Syntactic constructs enclosed between "angle brackets" < and > define the basic language elements. Every language construct should eventually be defined in terms of basic lexical constructs defined in the remainder of this appendix.

A construct appearing outside the angle brackets stands for itself, that is, it is supposed to be self denoting. Such a construct is known as a terminal symbol. Terminal symbols and reserved words appear in **bold face text** throughout this manual.

The symbol ::= is to be read "defined as".

The symbol .. means "through", indicating an ordered sequence of things where only the start and end elements are specified. (The reader is left to infer the middle elements). For example, the notation 'a' .. 'z' means "the ordered collection starting with the letter 'a', ending with the letter 'z', and containing the letters 'b', 'c'....'x', 'y' in between". In other words, all the lower case letters.

The "vertical bar" symbol | is read as "or". It separates sequences of elements that represent a choice of one out of many.

The metalanguage construct {...} (elements inside braces) enclose elements which are to be repeated "zero to many times". Although the braces are also used as one of the forms of comment delimiters in Pascal, this should not cause any ambiguity. The one case where ambiguity would occur is in the definition of comments, and this is explicitly pointed out at that time.

The Pascal compiler recognizes the following alphabet or character set:

```

<letter> ::= 'A' .. 'Z', 'a' .. 'z', and '_'
<digit>  ::= '0' .. '9'
<hex digit> ::= <digit> | 'a' .. 'f' | 'A' .. 'F'
<ASCII graphic characters> ::= ! " # $ % & ' ( ) * =
                               + - | ~ < > ? \ [
                               @ ^ | ~ { } ; : ]
<identifier> ::= <letter> { <letter> | <digit> }
<unsigned integer> ::= <digit> {<digit>}
<unsigned real> ::=
    <unsigned integer>.<unsigned integer>
    | <unsigned integer>.<unsigned integer>E<scale factor>
    | <unsigned integer>E<scale factor>
    | <unsigned integer>.<unsigned integer>D<scale factor>
    | <unsigned integer>D<scale factor>
<unsigned number> ::= <unsigned integer> | <unsigned real>
<scale factor> ::= <unsigned integer> | <sign><unsigned integer>
<sign> ::= + | -
<hex number> ::= $<hex digit> {<hex digit>}
<string> ::= '<character> {<character>}'
<character value> ::= \<two digit hexadecimal number>
<label> ::= <unsigned integer>
<comment> ::= { <any printable characters except "> }
              | (* <any printable characters except "*" ) *
<any printable character> includes carriage-return, line-feed,
                             tab, and so on.
<constant identifier> ::= <identifier>
<constant> ::= <unsigned number>
              | <sign> <unsigned number>
              | <constant identifier>
              | <sign> <constant identifier>
              | <string>

```

```

<constant definition> ::= <identifier> = <constant>

<type declaration> ::= type <type spec> {;<type spec>}
  <type spec> ::= <type identifier> = <Pascal type>

<simple type> ::= <scalar type>
  | <standard type>
  | <subrange type>
  | <type identifier>

<scalar type> ::= (<identifier> {,<identifier>})

<subrange type> ::=
  <subrange type identifier> | <lower> .. <upper>
  <lower> ::= <signed scalar constant>
  <upper> ::= <signed scalar constant>
  <structured type> ::= <unpacked structured type>
  | packed <unpacked structured type>

<unpacked structured type> ::= <array type>
  | <string type>
  | <record type>
  | <set type>
  | <file type>

  <array type> ::= array [<index list>] of <type>
  <index list> ::= <simple type> {, <simple type>}

<component type> ::= <type>

  <string type> ::= string[<static length>]
  <static length> ::= integer constant in the range 1 .. 255

  <record type> ::= record <field list> end;
  <field list> ::= <fixed part>
  | <fixed part> ; <variant part>
  | <variant part>

  <fixed part> ::= <record section> {;<record section>}
  <record section> ::= <field identifier list> : <type>

```

```

<field identifier list> ::= <field identifier> {,<field identifier>}

<variant part> ::=
    case {<tag field>} <type identifier> of <variant list>
<variant list> ::= <variant> {; <variant>}
<variant> ::= <case label list> : (<field list>)
<case label list> ::= <case label> {, <case label>}
<case label> ::= <constant>
<tag field> ::= <identifier>

<set type> ::= set of <simple type>

<file type> ::= file of <type>
                |
                file

<pointer type> ::= ^<type identifier>
<variable declaration> ::=
    <identifier> {,<identifier>}; <data type>;

<variable> ::= <entire variable>
                |
                <component variable>
                |
                <referenced variable>

<entire variable> ::= <variable identifier>

<component variable> ::= <indexed variable>
                |
                <field designator>
                |
                <file buffer>

<indexed variable> ::= <array variable> <subscript list>
<subscript list> ::= [ <expression> {,<expression>} ]
                | [ <expression> ] [ [ <expression> ] ]

<field designator> ::= <record variable>.<field identifier>

<file buffer> ::= <file variable>^
<file variable> ::= <variable>

<referenced variable> ::= <pointer variable>^

```

```

<pointer variable> ::= <variable>
<unsigned constant> ::= <unsigned number>
                        | <string>
                        | <constant identifier>
                        | nil
<factor> ::= <variable>
            | <unsigned constant>
            | <function designator>
            | <set constructor>
              (<expression>)
            | not <factor>
<set constructor> ::= [ <element> {,<element>} ]
<element> ::= <expression>
            | <expression> .. <expression>
<term> ::= <factor>
          | <term> <multiplying operator> <factor>
<simple expr> ::= <term>
                | <simple expr> <adding operator> <term>
                | <adding operator> <term>
<expression> ::=
    <simple expr>
    | <simple expr> <relational operator> <simple expr>
<multiplying operator> ::= * | / | div | mod | and
<adding operator> ::= + | - | or
<sign operator> ::= + | -
<relational operator> ::= = | <> | > | < | >= | <= | in
<assignment statement> ::=
    <variable> := <expression>
    | <function identifier> := <expression>
<procedure call statement> ::=
    <procedure identifier><actual parameter list>
    | <procedure identifier>
<actual parameter list> ::=
    (<actual parameter> {,<actual parameter>})

```

```

<actual parameter> ::= <expression>
                    | <procedure identifier>
                    | <function identifier>

<structured statement> ::= <begin statement>
                          | <if statement>
                          | <while statement>
                          | <repeat statement>
                          | <for statement>
                          | <case statement>

<begin statement> ::= begin <statement list> end
<statement list> ::= <statement> { ; <statement> }

<if statement> ::=
    if <Boolean expression> then <statement>
  | if <Boolean expression> then <statement> else <statement>

<case statement> ::= case <expression> of <cases>
                    { otherwise: <statement> } end
    <cases> ::= <a case> { ; <a case> }
    <a case> ::=
    <selection spec> { , <selection spec> } : <statement>

<selection spec> ::= <simple constant scalar expression>

<while statement> ::= while <expression> do <statement>

<repeat statement> ::= repeat <statement> until <expression>

<for statement> ::=
    for <control variable> := <for list> do <statement>
    <for list> ::= <initial value> to <final value>
                | <initial value> downto <final value>

<control variable> ::= <identifier>
<initial value> ::= <expression>
<final value> ::= <expression>

```

```

<with statement> ::=
    with <record variable> {,<record variable>}
        do <statement>

<goto statement> ::= goto <label>

    <unit> ::= unit <identifier>;
            <interface part>
            <impementation part>
    end.

<interface part> ::= interface
    <uses clause>
    <constant definition part>
    <type definition part>
    <variable definition part>
    <procedure and function declaration part>

<implementation part> ::= implementation
    <label declaration part>
    <constant definition part>
    <type definition part>
    <variable definition part>
    <procedure and function declaration part>

    <uses clause> ::= uses <unit name> {,<unit name>}

<declaration> ::= <constant declaration>
                <type declaration>
                <variable declaration>
                <procedure or function declaration>

<program> ::= <program heading> <block>.

<program heading> ::=
    program <identifier> (<program parameters>);

<program parameters> ::= <identifier> {,<identifier>}

<label declaration part> ::= label <label> {,<label>};

<constant definition part> ::= const <constant definition list>;

```

```

<constant definition list> ::=
    <constant definition> {; <constant definition>}

<type definition part> ::= type <type definition list>;
<type definition list> ::= <type definition> {; <type definition>}

<variable declaration part> ::= var <variable declaration list>
<variable declaration list> ::=
    <variable declaration> {;<variable declaration>}

<procedure declaration> ::= <procedure heading> <block>
<function declaration> ::= <function heading> <block>

<block> ::= <label definition part>
    <constant definition part>
    <type definition part>
    <variable declaration part>
    <procedure and function declaration part>
    <statement part>

<statement part> ::= begin <statement list> end
<statement list> ::= <statement> {; <statement>}

<procedure heading> ::=
    procedure <identifier>; {<attribute>;}
    | procedure <identifier> (<formal parameters>;
    {<attribute>;}

<function heading> ::=
function <identifier>;<result type>; {<attribute>;}
| function <identifier> (<formal parameters>;
    <result type>; {<attribute>;}

<formal parameters> ::= <formal parameter> {;<formal parameter>}

<formal parameter> ::= <parameter group>
    | var <parameter group>
    | <procedure heading>
    | <function heading>

<parameter group> ::=
    <identifier> {,<identifier>}<type identifier>

<attribute> ::= external | forward | cexternal

```


`<result type> ::= <simple type>`

Appendix C
Relationships to ISO Pascal

Myself when young did eagerly frequent
 Doctor and Saint, and heard great argument
 About it and about: but evermore
 Came out by the same door as in I went.
 Omar Khayam, The Rubaiyat

The International Standards Organization (ISO) and the American National Standards Institute (ANSI) are engaged in a joint effort to define a Pascal Standard.

In general, SVS Pascal conforms to the (proposed) ISO Pascal standard as defined in Pascal User Group News, Number 20, December 1980. There are however some differences that are spelled out here.

In SVS Pascal, only eight characters are significant in identifiers.

The Pascal standard procedures PACK and UNPACK are not supplied.

Conformant arrays are not implemented in accordance with the level 0 (U.S) standard.

There is a small difference in the way that a text file is handled if the text file is associated with an interactive terminal.

There is a **string** basic data type implemented.

There is a **double** basic data type implemented. The **double** data type is a double precision **real** data type.

There is an **otherwise** clause in the **case** statement. This provides for a "what to do if the case selector matches none of the cases". Standard Pascal considers this situation an error.

SVS Pascal implements a `longint` data type, which occupies four bytes instead of the two bytes of the standard `integer` data type.

The `and`, `or`, and `not` operators can be applied to operands of type `integer` as well as operands of type `Boolean`. When applied to operands of type `integer`, these operators perform bitwise logical `and`, logical `or`, and logical `not` operations on their operands.

SVS Pascal supports many extensions. These mainly derive from the UCSD P-System.

Appendix D

Relationships to UCSD Pascal

The University of California at San Diego (UCSD) implemented a widely used Pascal system, oriented towards small, personal computer systems. This implementation is known as UCSD Pascal.

SVS Pascal uses a number of ideas from UCSD Pascal. The main areas where SVS Pascal conforms to UCSD Pascal are:

1. Independent compilation is supported through the unit concept of UCSD Pascal. The interface, **implementation** and **uses** statements are implemented.
2. There is an include capability.
3. Many of the UCSD Pascal compatible standard procedures and functions are implemented the same as UCSD Pascal.

D.1 Differences from UCSD Pascal

In SVS Pascal, the underline character is significant in identifiers. In UCSD Pascal it is ignored so that the identifiers "Space_Out" and "SpaceOut" are identical. In SVS Pascal they are considered two different identifiers.

SVS Pascal supports a long integer type, with the predefined type name **longint**. The UCSD construct **integer[nn]** is not implemented.

There is a **double** basic data type implemented. The **double** data type is a double precision real data type.

Fields of **packed records** and elements of **packed arrays** can never be passed as reference parameters to procedures, even in those places where UCSD Pascal allows.

The SVS Pascal string type `packed array[low..high] of char` must have a lower bound of 1 to be compatible with literal strings, or to be used in array comparisons. UCSD Pascal allows any lower bound.

SVS Pascal does not have the reserved word `segment`. Consequently there is no `segment procedure` or `segment function`. To segment a SVS Pascal program, use the `$S` compiler option, which directs the compiler to place generated object code in a named segment. See the Chapter on "Running the Compiler". That Chapter contains a section on compiler options.

SVS Pascal does not implement unit initialization code.

SVS Pascal does not supply special units such as `APPLESTUFF` or `TURTLEGRAPHICS`.

SVS Pascal does not have any default `string` length. Instead of the declaration

```
var x: string;
```

use the declaration

```
var x: string[80];
```

SVS Pascal does not have a predefined file called "keyboard".

SVS Pascal implements sets with elements 0 thru 4095, whereas UCSD Pascal implements 0 thru 511.

Packing algorithms for arrays and records are different.

Internal storage for sets is different.

SVS Pascal does not support comparison of arrays and records, with the single exception that `packed array[1..n] of char` can be compared.

Predefined `string` procedures and functions must have `string` variable or `string` literal parameters. That is, not `packed array of char` or `char` variable parameters.

SVS Pascal does not implement the procedure `STR`, since there is no `integer[nn]` type.

The file procedures `RESET` and `REWRITE` require two parameters, namely (file,string).

End-of-file character from the keyboard is Control-D instead of Control-C.

SVS Pascal text files must be declared as packed file of char.

SVS Pascal text file reads allow additional parameters of packed array of char.

SVS Pascal text file writes allow additional parameters of packed array of char and Boolean.

SVS Pascal does not implement the UNITWAIT intrinsic.

SVS Pascal implements the procedure

```
UNITSTATUS (UnitNumber, Address, Integer)
```

SVS Pascal does not implement TREERESEARCH.

SVS Pascal limits the EXIT procedure to exiting statically compiled procedures or functions or the main-program. The argument to EXIT must be the name of the routine to exit. That is, EXIT(PROGRAM) is not allowed.

The MEMAVAIL procedure returns the number of bytes of available memory. The return parameter is of the type longint. See the Section on "Memory Management".

SVS Pascal implements two procedures SCANEQ (scan equal) and SCANNE (scan not equal), whereas UCSD Pascal implements a single SCAN procedure with a = or <> parameter.

SVS Pascal does not have any INTRINSIC units.

SVS Pascal does not implement the unit initialization section in units.

SVS Pascal implements an optional **otherwise** clause in **case** statements. If the **otherwise** clause is present, it must be the last statement. For example:

```
case huh of
  1: do_this;
  3,5: do_that;
otherwise:
  do_the_other;
end;
```

SVS Pascal implements true global goto statements. The UCSD Pascal {G+} compiler option is not needed in order to use goto statements.

SVS Pascal has predeclared variables ARGV and ARGV that describe the number and value of any parameters passed from the

command line to a running program.

Procedures and functions may be passed as parameters. The implementation is consistent with the proposed ISO standard Pascal.

ORD(**Boolean Expression**) works properly in SVS Pascal.

The mod operator works properly in SVS Pascal.

SVS Pascal has added the unary operator @, which stands for "address of". Placing the @ in front of a variable, function, or procedure, generates the address of that entity. The type returned is the type of nil, that is, it can be assigned to any pointer variable. The @ operator does not work with most of the predefined procedures and functions such as ORD or READLN.

SVS Pascal has added the function ORD4. It is the same as ORD except that it returns a 32-bit integer.

All **integer** arithmetic operations are done at a precision of either 16 or 32 bits, depending on the maximum size of any arguments. The rules are similar to FORTRAN's single and double precision reals.

SVS Pascal statement labels are restricted to the range 0 thru 9999, as in the ISO Pascal standard.

SVS Pascal provides for hexadecimal integer constants. A hexadecimal constant is prefixed with a \$ sign. Hexadecimal numbers must be 32 bits long to be considered signed numbers, that is, \$FFFF represents 65536, not -1. To represent -1, code the hexadecimal constant \$FFFFFFFF.

The **and**, **or**, and **not** operators can be applied to operands of type **integer** as well as operands of type **Boolean**. When applied to operands of type **integer**, these operators perform bitwise logical and, logical or, and logical not operations on their operands.

Appendix E

Data Representations

This appendix describes the ways that SVS Pascal represents data in storage, how that data is packed for data objects that have the **packed** storage attribute, and the mechanisms for passing parameters to procedures and functions. This appendix is intended as a guide to those programmers who wish to write modules in languages other than Pascal and have those modules interface to Pascal.

E.1 Storage Allocation

This section describes the way in which storage is allocated to variables of various types. The storage allocation described here is for unpacked items.

In general, any **word** value is always aligned on a word boundary. Anything **larger** than a word is also aligned on a word boundary. Values that can fit into a single byte are aligned on a byte boundary.

A Boolean variable

occupies one byte of storage, aligned on a byte boundary. A value of 0 represents the value **false**. A value of 1 represents the value **true**. Any other value is an "undefined" Boolean value.

A scalar (ordinal) type

of 128 elements or less, occupies one byte of storage, aligned on a byte boundary. If there are more than 128 elements in the scalar types, it then occupies a word. Scalar types are assigned the values 0, 1, 2,, n-1, where "n" is the cardinal number of elements in the scalar.

Subrange elements

in the range -128 .. 127 occupy one byte, aligned on a byte boundary. A subrange element in the range -32768 .. 32767 occupies one word, aligned on a word boundary. A subrange element greater than that occupies two words, aligned on a word boundary.

An unpacked char element

is considered to be a subrange of 0 .. 255. This means that it occupies a word.

An integer element

occupies one word, aligned on a word boundary.

A longint element

occupies two words, aligned on a word boundary.

real elements


occupy two words, aligned on a word boundary. A real element has a sign bit, an 8-bit exponent and a 23-bit mantissa. SVS Pascal real elements conform to the IEEE standard for reals as defined in the March 1981 Computer magazine. The layout of a real element is shown below. The range of real numbers is approximately $-3.4E-38$.. $+3.4E38$, with a precision of approximately seven decimal places. Normal arithmetic operations upon real data types can result in the "extreme values" of plus infinity, minus infinity, or Not a Number (NaN). These are described below.

double elements

occupy four words, aligned on a word boundary. A double element has a sign bit, an 11-bit exponent and a 52-bit mantissa. SVS Pascal double elements conform to the IEEE standard for double precision as defined in the March 1981 Computer magazine. The layout of a double element is shown below. The range of double numbers is approximately $-1.8D-308$.. $+1.8D308$, with a precision of approximately 15 decimal places. Normal arithmetic operations upon double data types can result in the "extreme values" of plus infinity, minus infinity, or Not a Number (NaN). These are described below.


Whatever the size of the data element in question, the most significant bit of the data element is always in the lowest numbered byte of however many bytes are required to represent that object. The diagrams below should clarify this.

E.2 Representation of Integers



E.3 Representation of Reals and Doubles


real and double data elements are represented according to the proposed IEEE standard as defined in Computer magazine of March, 1981. The diagrams below illustrate the representation.



real Data Representation

The format for a real or single-precision floating-point number is as shown above. The three field of a real are as follows:

- . a one-bit sign bit designated by "S" in the diagram above. The sign bit is a 1 if, and only if, the number is negative.
- . an 8-bit biased exponent. The values of all ones and all zeros are reserved values for the exponent.
- . a 23-bit mantissa.



double Data Representation

The parts of **double** numbers are as follows:

- a one-bit sign bit designated by "S" in the diagrams above. The sign bit is a 1 if, and only if, the number is negative.
- an 11 bit biased exponent. The values of all zeros and all ones are reserved values for the exponent.
- a normalized 52-bit mantissa, with the high-order 1 bit "hidden".

A **real** or **double** number is represented by the form:

$$2^{\text{exponent-bias}} * 1.f$$

where 'f' is the bits in the mantissa.

Normalized **real** and **double** numbers are said to contain a "hidden" bit, providing for one more bit of precision than would normally be the case.

E.4 Representation of Extreme Numbers

When **real** or **double** data elements are stored in the system, there arises the question of how to represent "values" such as positive and negative infinity. The discussion below describes the representations of these extreme numbers, and their behavior in expression evaluation.

zero (signed) is represented by an exponent of zero, and a mantissa of zero.

denormalized numbers

are a product of "gradual underflow". They are non-zero numbers with an exponent of zero. The form of a denormalized number is:

$$2^{\text{exponent-bias}+1} * 0.f$$

where 'f' is the bits in the mantissa.

signed infinity (that is, affine infinity) is represented by the largest value that the exponent can assume (all ones), and a zero mantissa.

Not-a-Number (NaN)

is represented by the largest value that the exponent can assume (all ones), and a non-zero mantissa. The sign is usually ignored.

Normalized real and double numbers are said to contain a "hidden" bit, providing for one more bit of precision than would normally be the case.

Hexadecimal Representation of Selected Numbers

Value	real	double
+0	00000000	0000000000000000
-0	80000000	8000000000000000
+1.0	3F800000	3FF0000000000000
-1.0	BF800000	BFF0000000000000
+2.0	40000000	4000000000000000
+3.0	40400000	4008000000000000
+Infinity	7F800000	7FF0000000000000
-Infinity	FF800000	FFF0000000000000
NaN	7F8xxxxx	7FFxxxxxxxxxxxxxxx

Deviations from the Proposed IEEE Standard

Deviations from the proposed IEEE standard in this implementation are as follows:

- . affine mapping for infinities,
- . normalizing mode for denormalized numbers,
- . rounds approximately to nearest - 7 or more guard bits are computed, but the "sticky" bit is not,
- . exception flags are not implemented,
- . conversion between binary and decimal is not implemented.

Arithmetic Operations on Extreme Values

This subsection describes the results derived from applying the basic arithmetic operations on combinations of extreme values and ordinary values.

No traps or any other exception actions are taken.

All inputs are assumed to be positive. Overflow, underflow, and cancellation are assumed not to happen.

In all the tables below, the abbreviations have the following meanings:

Abbreviation	Meaning
Den	Denormalized Number
Num	Normalized Number
Inf	Infinity (positive or negative)
NaN	Not a Number
Uno	Unordered

Addition and Subtraction					
Left Operand	0	Den	Num	Inf	NaN
0	0	Den	Num	Inf	NaN
Den	Den	Den	Num	Inf	NaN
Num	Num	Num	Num	Inf	NaN
Inf	Inf	Inf	Inf	Note 1	NaN
Nan	NaN	NaN	NaN	NaN	NaN

Note 1: $\text{Inf} + \text{Inf} = \text{Inf}$; $\text{Inf} - \text{Inf} = \text{NaN}$

Multiplication					
Left Operand	0	Den	Num	Inf	NaN
0	0	0	0	NaN	NaN
Den	0	0	Num	Inf	NaN
Num	0	Num	Num	Inf	NaN
Inf	NaN	Inf	Inf	Inf	NaN
Nan	NaN	NaN	NaN	NaN	NaN

Division					
Left Operand	0	Right Operand		Inf	NaN
		Den	Num		
0	NaN	0	0	0	NaN
Den	Inf	Num	Num	0	NaN
Num	Inf	Num	Num	0	NaN
Inf	Inf	Inf	Inf	NaN	NaN
Nan	NaN	NaN	NaN	NaN	NaN

Comparison					
Left Operand	0	Right Operand		Inf	NaN
		Den	Num		
0	=	<	<	<	Uno
Den	>		<	<	Uno
Num	>	>		<	Uno
Inf	>	>	>		Uno
Nan	Uno	Uno	Uno	Uno	Uno

Notes:

NaN compared with NaN is Unordered, and also results in inequality.

+0 compares equal to -0.

Max					
Left Operand	0	Right Operand		Inf	NaN
		Den	Num		
0	0	Den	Num	Inf	NaN
Den	Den	Den	Num	Inf	NaN
Num	Num	Num	Num	Inf	NaN
Inf	Inf	Inf	Inf	Inf	NaN
Nan	NaN	NaN	NaN	NaN	NaN

Min					
Left Operand	0	Right Operand		Inf	NaN
		Den	Num		
0	0	0	0	0	NaN
Den	0	Den	Den	Den	NaN
Num	0	Den	Num	Num	NaN
Inf	0	Den	Num	Inf	NaN
Nan	NaN	NaN	NaN	NaN	NaN

E.5 Representation of Sets


SVS Pascal represents a set like a "giant integer". The zero'th element of a set is always present in the set. Suppose that a type and a variable are defined as in this example.

```

type
  days_in_year = set of 1 .. 366;
var
  blarg: days_in_year;

```

The representation for the variable "blarg" is as in the diagram below:



The number of bytes required to contain this a set of 1 .. 366 is 366/8 which is 46 bytes. The storage is allocated accordingly as shown in the above diagram. The value 366 mod 8 is 6, and there is one unfilled bit in the least significant byte of the set.

E.6 Representation of Arrays

Components of unpacked arrays and records are allocated contiguously as defined above. There is no attempt made to conserve space in units smaller than bytes.

Arrays are stored in row order, that is, the last index varies fastest. This follows from the strict definition that a multi-dimensional array in Pascal is actually an:

```

array[first index] of array[second index] .....
                    of array[n'th index] of whatever type;
    
```

Representation of Pointers

Pointers always occupy four bytes. The nil pointer is represented by a value of zero (0).

E.7 Packing Methods


Packed records are expensive in terms of the amount of generated code needed to reference a field of a packed record. In general, avoid packing records unless there are many more instances of a particular records than there are references to it.

Components of a **packed record** are allocated in the order in which they appear. Components never cross word boundaries. The allocator never backtracks to fill in holes in the structure.


Within a word, components are allocated on bit boundaries. The allocation proceeds from the least significant end of the word towards the most significant end. If there is not enough room in the current word for a component, a hole is left in the current word, and the next word is started.

After allocation, it is possible that the allocator might shift and expand fields in a word. For example, a signed field might be expanded to use the remainder of a word for faster access, or two 5-bit fields might be allocated a full byte each. The diagrams below provide graphic illustrations of the packing methods. In each case, a **type** definition is given, followed by a diagram of how that type is allocated.


```
packed record
  a: 0 .. 7;
  b: char;
  c: 0 .. 3;
  d: Boolean;
  e: 0 .. 3;
end;
```




```
packed record
  a: 0 .. 4095;
  b: char;
end;
```




```
packed record
  a: 0 .. 63;
  b: 0 .. 63;
end;
```



The record above is allocated as in the above picture, but will be re-allocated as shown below.



```
packed record
  a: -1024 .. +1023;
  b: 0 .. 7;
end;
```





In the last example above, the signed subrange field was moved up to the left hand end of the word and sign extended for faster access.

Packed arrays are also code consuming, with one exception: **packed array of char** is treated as a special case, and the generated code is compact.



Elements of **packed arrays** are stored with multiple values in a byte whenever more than one value can fit in a byte. Elements are allocated on 1, 2, 4 or 8-bit boundaries. This only happens when the value requires 4 bits or less. 3-bit values are stored in 4 bits.

The first value in a **packed array** is stored in the lowest numbered bit position of the lowest addressed (that is, the most significant) byte. Subsequent values are stored in the next available higher numbered bit positions in that byte. When the first byte is full, the same positions are used in the next higher addressed byte. Consider the following examples:


```
var
  a: packed array[1 .. 12] of boolean;
```



```
var
  b: packed array[3 .. 8] of 0 .. 3;
```



```
var
  c: packed array[0 .. 2] of 0 .. 7;
    or
  c: packed array[0 .. 2] of 0 .. 15;
```



E.8 Parameter Passing Mechanism

This Section describes the way in which parameters are passed in SVS Pascal.

Parameters are passed on the stack. Parameters are pushed onto the stack in order in which they are declared in **procedure** and **function** declarations.

If the callee is a **function**, room for the **function** result is allocated on the stack before any parameters are pushed.

If the callee is not a **procedure** or **function** at the global level, the static link is the last thing pushed onto the stack before the routine is called.

Upon return from a routine, all parameters are discarded from the stack. The only thing that should be on the stack upon return, is a **function** result.

var parameters (call by reference) always have a four-byte pointer to the variable pushed onto the stack.

Value parameters are divided into the three categories of **sets**, **doubles**, and everything else.

The caller always pushes **sets** onto the stack. A **set** which occupies one byte is pushed with a `move.b` instruction. A **set** which occupies more storage than one byte is pushed with the least significant element in the most significant word. Thus the representation of a **set** on the stack is the same as the representation in memory.

The caller always pushes **doubles** onto the stack as well. This is usually accomplished by two `move.l` instructions in such a manner that the representation a **double** on the stack is the same as the representation in memory (that is, with the sign bit in the lowest addressed byte).

Other value parameters are pushed as follows:

- . a one-byte value is pushed with a `move.b` instruction.
- . a two-byte value is pushed with a `move.w` instruction.

- . a four-byte value is pushed with a `move.l` instruction.
- . if a value is longer than four bytes, and not a **double**, the address of the data is pushed onto the stack and the called **procedure** or **function** copies the data into local storage.

Procedure and function parameters are pushed as follows:

- . the address of the **procedure** or **function** is pushed onto the stack.
- . the static link is then pushed onto the stack if the **procedure** or **function** is not at the global (outermost) level. If the **procedure** or **function** is global (at the outermost level), the value `nil(0)` is pushed onto the stack instead of the static link.

E.9 Limitations On Size of Variables

There is no limitation on the number of bytes allocatable for variables. However, a maximum of 30K bytes of value parameters cannot be exceeded. Furthermore, when more than 30K bytes of variables exist in either the main program's global scope, or in any local scope of a **procedure** or **function** (but not **unit** globals), the largest values will be accessed via a pointer, resulting in somewhat slower code. This mechanism is transparent to the user, so that no changes to source code are required.

Global variables in **units** are accessed via 32-bit absolute addressing modes. Therefore the pointer mechanism does not apply to **units** with more than 30K bytes of globals.

The maximum size of a **record** variable is 32K bytes.

There is no limitation on the size of variables which can be allocated by the NEW procedure.

E.10 Compiler Generated Linker Names

This section describes the manner in which the Pascal compiler generates names of local and global procedures so that the Linker can resolve external references at link time.

Procedures which are global (or external) are given the names which the user assigns to them. The compiler converts all such names to upper case, and truncates them to eight characters in length.

Procedures which are local (not visible in the global scope) are assigned names of the form:

\$nnn

where 'nnn' is a decimal number. The numbers may possibly have trailing spaces. Procedures of the same name but in different scopes have different names. In other words, all local names in a given compilation unit are unique.

When the linker or librarian sees a collection of compiled units, the local names may be renumbered, but the actual name that the user assigned to the procedures are carried along with the number.

Appendix F
Bibliography

This appendix is a short bibliography of Pascal related literature.

The Programming Language Pascal. By Niklaus Wirth.
Acta Informatica, 1, pp 35-63. 1971.

Pascal User Manual and Report. Kathleen Jensen and Niklaus Wirth.
Springer-Verlag. 1974.

Beginner's Guide to the UCSD Pascal System. Kenneth Bowles.
Byte Books. 1980.

Software Tools in Pascal. Kernighan and Plauger.
Addison Wesley. 1981.

ISO Standard for Pascal appeared in the Pascal Newsletter, number 20, December 1980, published by the Pascal User's Group, and in SIGPLAN Notices, April 1980, Published by ACM.

In addition to the references above, there is a Pascal Users' Group (known as PUG) which publishes a newsletter relating to all things Pascal.

Appendix G

Pascal on the UNIX System

This appendix describes the specific details of using the SVS Pascal compiler on the UNIX¹ Operating System. Later sections cover specific dependencies and features of SVS Pascal on the UNIX system.

G.1 Running Pascal On the UNIX System

The Pascal compiler, `pc`, compiles programs written in the Pascal language, and optionally links (or binds) the result with intermediate files generated by `pc` or other language processors.

The description below covers the UNIX system interface to the compiler. At the end of this section can be found a description on how to run the individual phases separately.

NAME

`pc` - Pascal Compiler

SYNOPSIS

`pc [-o ofile] [-i] [-c] [-u] [-v] file ...`

DESCRIPTION

`pc`, the Pascal compiler, accepts a list of Pascal source files and various intermediate texts contained in the list of files specified by `file`. The resulting executable object-module is placed in the file `a.out`, unless the `-o` option was specified (see below).

To understand the use of `pc`, the reader should be aware of the steps through which the compiler goes in order to turn a Pascal

1. UNIX is a trademark of Bell Laboratories

source program into an executable object-file. `pc` goes through several separate phases (or passes) when compiling a program.

`pc` source files must have a `.pas` suffix. `pc` generates three intermediate files (`.i`, `.obj`, and `.o`) on the way to generating the final executable binary file. The first phase of the compiler generates intermediate files with the same names as the source files, but with a `.i` suffix. These intermediate files are destined for processing by the code generator.

Code generation is the second phase of the process. The code generator produces files of the same name as the source files, but with a `.obj` suffix. The `*.obj` files are the input to the next phase, called `ulinker`.

The `ulinker` phase of the process performs two functions: it links the `.obj` files, resolving external references to the Pascal run-time library; then it converts the `.obj` file format into a UNIX-style object file, with a `.o` suffix. This means that one file in the list of files specified on the `pc` command line must contain a main program. This `.o` file can then be processed by `ld` - the UNIX system loader utility.

The final stage of the process is when the `ld` utility generates the final executable object code file.

When using `pc`, any combination of Pascal source files (each with a `.pas` suffix) can be combined with Pascal (or SVS FORTRAN) intermediate files (each with a `.i` suffix), Pascal or FORTRAN object-code files (each with a `.obj` suffix), and UNIX system object-code files (having `.o` suffixes). When the compilation completes successfully, the result of the combination of all those files is placed in the file `a.out`, or in the file specified by the `-o` option.

The `-o` option, if used, specifies that the file `ofile` (runnable file) whose name follows the `-o` option is the file to receive the final executable code. If the `-o` option is not specified, the resultant executable code is placed in the file `a.out`.

If the `-i` option is used, the Pascal intermediate code (the result of running `/lib/pascal`) is placed in a file of the same name as the source file, but with a suffix of `.i` appended. The compilation then terminates.

If the `-c` option is used, the Pascal unlinked object-code (the result of running `/lib/code`) is placed in a file of the same name as the source file, but with a suffix of `.obj` appended. The compilation then terminates.

If the `-u` option is used, the linked object-code (the result of running `/lib/ulinker`) is placed in a file of the same name as the source file, but with a suffix of `.o` appended. The compilation then terminates at that point.

The `-v` (for verbose) option tells `pc` to display a running progress report as it goes through each of the compilation and linking phases. If the `-v` option is specified, the compiler also generates a listing file, of the same name as the source file, but with a suffix of `.lst` appended.

If only one `file` argument is supplied on the command line, then all the intermediate files (`*.i`, `*.obj`, `*.o`) are removed at the end of the compilation. If multiple `file` arguments are specified on the command line, any existing intermediate files are not removed.

EXAMPLES

```
pc prog1.pas
```

compiles `prog1.pas` and places the resulting executable file in `a.out`.

```
pc -o frammis prog2.pas prog3.obj
```

compiles the Pascal program called `prog2.pas` and links the result with the object-file `prog3.obj`. The resulting executable binary is placed in the output file called `frammis`.

FILES

<code>*.pas</code>	Pascal source,
<code>*.i</code>	Intermediate code,
<code>*.obj</code>	Compiled but unlinked <code>pc</code> object-code,
<code>*.o</code>	Compiled but unlinked UNIX object-code,
<code>/lib/paslib.obj</code>	Pascal run-time library,
<code>/lib/pascal</code>	Pascal compiler,
<code>/lib/code</code>	Code generator,
<code>/lib/ulinker</code>	SVS to UNIX object-file converter,
<code>/lib/pascterrs</code>	Pascal compile-time error message file.
<code>/lib/wraplib</code>	Interfaces for calling C routines.

Note that all the files appearing in `/lib` above can alternatively reside in `/usr/lib`.

Running The Compiler Phases Separately

The separate parts of the Pascal Language system can be run independently if required. The separate phases are:

- The Pascal compiler (front end) is in /lib/pascal (or /usr/lib/pascal). The compiler turns Pascal source text into an intermediate form suitable for processing by the code generator.
- The Code Generator is in /lib/code (or /usr/lib/code). It converts the intermediate file into a form which will be processed by ulinker.
- ulinker is in /lib/ulinker (or /usr/lib/ulinker). It links the output of the code generator, and converts the resulting linked file into UNIX compatible .o file format, ready for processing by the UNIX link-editor (ld) utility.

Examples shown in the following subsections assume that there is a program called 'hello.pas', which is to be compiled, code-generated, linked, and link-edited, ready for execution.

Running the Pascal Compiler Independently

The Pascal compiler (front end) is run with a command line like this:

```
/lib/pascal [+q] [-p] sfile -llfile -iifile -eefile
or,
/usr/lib/pascal [+q] [-p] sfile -llfile -iifile -eefile
```

where 'sfile' is the name of a file containing the Pascal source program. The source is expected to be on a file with a .pas suffix.

Other files (such as listing or error files) are introduced by the options described below. Note that there must not be any spaces between an option letter and its corresponding filename.

```
-llfile      'lfile' is the optional name of the file to
              receive the compiler generated listing. No
```

suffix is appended to the list filename. If the -l option is omitted, no listing is generated.

-iifile 'ifile' is the optional name of the intermediate file destined for processing by the code generator. If the 'ifile' is not specified on the command line, the intermediate output is placed on a file with the same name as the source file (minus the .pas suffix) with a .i suffix appended.

-eefile 'efile' is the optional name of a file to receive the compiler error summary. No suffix is appended to the error summary filename. An error summary file is not generated unless it is requested by the -e option.

The +q (for quiet)

option makes the compiler print less. The -q option increases the amount of data displayed. The default is +q (quiet).

In the pc UNIX command, the -q option is called up via the -v (for verbose) option on the command line.

The +p (for prompt)

option makes the compiler display each error on the standard output, and prompt for a user response from the standard input. The user has the option to continue or abort the compilation at that point. If the -p option is used, the compiler automatically continues processing and searching for more errors after an error is found. The normal default for this option is -p (continue automatically).

Example of Running the Pascal Compiler

pascal hello.pas

In this example, the Pascal compiler compiles the source in the file 'hello.pas'. The intermediate text is placed in the 'hello.i' file.

Running the Code Generator

The code generator is the second phase of a Pascal compilation. The code generator processes the intermediate file from the compiler and generates a .obj file ready for processing by the ulinker utility. The code generator is run simply by typing the command:

```
/lib/code file  
or,  
/usr/lib/code file
```

where 'file' is the name of the intermediate file to process. The intermediate file must have a .i suffix. The output of the code generator is a file ready for processing by ulinker. The output filename is the same as the input filename, minus the .i suffix, and with a .obj suffix appended.

Example of Running the Code Generator

```
/lib/code hello.i
```

In this example, the code generator is generating code for the file 'hello.i'. The result of the code generation appears on a file called 'hello.obj'.

Running the Ulinker Utility

The ulinker utility links the output of the code generator, resolves external references to run-time routines, and converts the output of the code generator into a form that can be processed by the UNIX link-editor. The ulinker utility is run like this:

```
/lib/ulinker [-l] ofile objfile...  
or,  
/usr/lib/ulinker [-l] ofile objfile...
```

`-l` if supplied, suppresses link map information. If the `-l` option is omitted, the first filename on the ulinker command line must be the name of a file to receive the listing.

`'ofile'` is the name of the file to receive the final `.o` file.

`'objfile'` is a list of `.obj` files (and libraries) to process.

The output of ulinker is a file ready for processing by the UNIX link-editor.

The `-l` option, if typed on the command line, tells ulinker to display progress information on the standard output.

Example of Running ulinker

```
/lib/ulinker -l hello.o hello.obj /lib/paslib.obj
```

This example links the 'hello.obj' file generated by the code generator, resolves external references to the Pascal run-time library, then converts the code format to a form acceptable to `ld`, the UNIX link-editor. The result appears in the 'hello.o' file shown on the command line.

The Pascal run-time routines make calls upon certain C library routines. The interface between these is supplied by a `.o` file called 'wraplib.o', which resides either in the `/lib` or `/usr/lib` directories. 'wraplib.o' must be included in the link-edit process, after the user's `.o` files, and before the C library. A description of the interface between Pascal and C routines can be found later in this appendix.

The final stage in the process of obtaining an executable binary file is to run the UNIX link-editor:

```
ld /lib/crt0.o hello.o /lib/wraplib.o -lc
```

This example links the 'hello.o' file with the run-time routines from 'wraplib.o', and the C run-time library indicated by the `-lc` option on the `ld` command line. The 'crt0.o' file must come first in the link sequence, so as to get the run-time startup routines in the correct place. The resulting executable binary appears on the file 'a.out'.

G.2 UNIX System Dependencies

This section covers specific features of the SVS Pascal compiler on the UNIX operating system.

Unimplemented Language Features

On the UNIX operating system, these procedures are not implemented:

```
unitread,  
unitwrite,  
unitclear,  
unitstatus,  
memavail.
```

Return Values from Pascal Programs

A Pascal program can issue the call:

```
halt(0)
```

to generate a UNIX system error return code, and:

```
halt(1)
```

to generate a normal termination code.

This feature is provided for use with programs which are used in Shell scripts containing commands to test the error flag.

Action on Closing Files

Contrary to what is said in chapter 6 - "Input and Output" about the actions taken on closing a file, on the UNIX system, all files are closed with the 'lock' option, regardless of what option was actually specified in the CLOSE statement.

English Error Messages

The Pascal system now can display English style error messages by accessing the error message file which resides in the file /lib/pascterrs or in /usr/lib/pascterrs (pascal compile time errors).

G.3 Interfacing Pascal to UNIX C Programs

This part of the appendix is intended to give the user some clues in how to link programs written in SVS Pascal with external routines written in C on the UNIX system.

Because the interfaces and calling conventions differ between Pascal and C, Pascal routines are linked with C routines via a small assembler language routine called a "wrapper". The purpose of the "wrapper" is to make the interface between Pascal and C compatible with each other.

The user must be aware of the following relationships between Pascal and C:

- All C parameters expect four bytes on the stack for each argument, regardless of what they are. Pascal programs which will call C routines should declare all their parameters of type `longint` in order to maintain the four-byte parameter convention.
- C parameters are pushed onto the stack in the reverse order from those of Pascal. So the Pascal call:

```
_func(a, b, c)
```

is seen by the C routine as

```
func(c, b, a)
```

- The C language returns function results in register D0. Pascal returns function results on the stack. The interface routine must be aware of this and act accordingly. If a value is to be returned, a Pascal-style **external function** should be declared, otherwise just declare the routine as an **external procedure**.
- If the called C routine is to alter any of the parameters passed, the parameters should be declared as **var** parameters in the Pascal **procedure** or **function** declaration. The C routine should then treat such parameters as pointers.
- The representation of real data in Pascal is incompatible with the **float** and **double** data types of C, so the user should avoid passing these data types.

- . SVS Pascal does not support a double-precision floating point data type.

Examples

The four sets of declarations below are representative samples of some C routines and the Pascal declarations to provide the interface to those routines. Following the declarations, are the "wrappers" to interface those C routines with the Pascal programs.

Pascal Declaration:

```
function _add(a, b: longint): longint; external;
```

C Function:

```
add(b, a)          /* add two numbers */
{
  int *a, *b;
  return (*a + *b);
}
```

Pascal Declaration:

```
procedure _hello; external;
```

C Function:

```
hello()           /* print the word 'HELLO' */
{
  printf ("HELLO!\n");
}
```

Pascal Declaration:

```
procedure _swap(var a, b: longint) external;
```

C Function:

```
swap(b, a)          /* swap two numbers */
int *a, *b;
{
    int temp;

    temp = *a;
    *a = *b;
    *b = temp;
}
```

Note that in the declarations above we have one **function** and two **procedures**. One of the **procedures** has no parameters. The other **procedure** and the **function** have parameters. In the discussions to follow, these differences will illustrate the different pieces of assembler coding necessary for the interface.

Connecting the Pieces

Unless the C program segments are already in the C library (that is, they are standard C functions), they should be compiled and left as .o files (using the cc -c compiler call).

An assembly language interface routine must be provided for each C routine to be called. This interface routine is called a "wrapper".

The external reference passed from the Pascal program will be in upper case. The wrapper must call the corresponding lower-case routine (the C routine), and then clean up the stack on return. For every parameter that the Pascal program passes, four bytes must be removed from the stack.

The wrapper must also ensure that the function return value (if there is one) must be pushed onto the stack from register D0.

Examples of Wrapper Routines

The assembly language fragments below are the wrappers to interface the three Pascal and C routines shown in the examples above. There is a common theme throughout each routine.

- Each wrapper declares as global (the `.globl` declaration) both the upper case name (which Pascal generates) and the corresponding lower case name (which C generates).
- In all cases, Pascal places its return address on the stack. The wrapper pops that stack entry into register A3, which is guaranteed not to be clobbered by any C routines which are called (user written assembler codes must also honor this convention to avoid disaster).
- Upon return from the C routine, the wrapper pops four bytes for every parameter that was passed from the Pascal program.
- Lastly, if the calling Pascal routine is a function which expects a result, the wrapper must push the C function's return value onto the stack from register D0.

First there is the wrapper for the 'add' function:

<pre> _ADD: .globl _ADD, _add movl sp@+, a3 jsr _add addl #8, sp movl d0, sp@ jmp a3@ </pre>	<pre> declare _ADD global save Pascal return address call the C _add routine remove 8 bytes from stack put return value on stack return to Pascal. </pre>
---	---

The 'add' function passes two parameters, so after the C routine returns it pops eight bytes from the stack. The caller is a Pascal function, so the return value is pushed onto the stack.

Then there is the wrapper for the 'hello' procedure, which does not have any parameters:

<pre> _HELLO: .globl _HELLO, _hello movl sp@+, a3 jsr _hello jmp a3@ </pre>	<pre> declare _HELLO global save Pascal return address call the C _hello routine nothing to remove/return, so just jump to Pascal. </pre>
---	---

This routine has no parameters, and the caller expects no return value, so there is nothing to do except return to the caller.

Lastly there is the wrapper for the 'swap' procedure which has two parameters:

<pre> .globl _SWAP, _swap _Swap: movl sp@+, a3 jsr _swap addl #8, sp jmp a3@ </pre>	<pre> declare _SWAP global save Pascal return address call the C routine remove 8 bytes from stack nothing to return, so just jump to Pascal </pre>
---	---

The wrapper should be assembled into a .o module using the assembler. Now, all the pieces must be presented to the loader (which may be done by calling the compiler).

In addition to any "wrapper" routines that the user writes, there is also a file in /lib/wraplib (or /usr/lib/wraplib) which contains some predefined interfaces to the C run-time library.

For example, if the pieces of the C program are in the file called 'zork.o', and the wrapper is in 'wrp.o', and the Pascal program is in 'prog.o', the pieces can be linked by typing:

```
pc prog.o wrp.o zork.o
```

or (more complicated):

```
cc prog.o wrp.o zork.o /lib/wraplib.o
```

or (even more complicated):

```
ld /lib/crt0.o prog.o wrp.o zork.o /lib/wraplib.o -lc
```

The file /lib/wraplib (or /usr/lib/wraplib) already contains wrappers for the C language routines:

```

_CLOSE
_CREAT
_LSEEK
_OPEN
_READ
_SBRK
_WRITE

```

These routines are recognized specially by the system.