➤ attached to an 8100/DPPX or DPCX system, the Host Command Facility gives the operator at a central System/370 site the capability to operate and control remote SDLC-connected 8100 systems. Nearly all maintenance, service, and control functions become available at the central System/370 site for problem determination, problem isolation, and remote system control. The System/370 must be running under MVS VTAM/TCAM, VS1 VTAM/TCAM, or DOS/VS VTAM.

#### **PRICING**

POLICY: IBM offers the 8100 Information System for purchase, monthly rental, or on a two-year lease. Rental and lease arrangements include prime-shift maintenance. Purchased components may have a separate maintenance contract.

All 8100 system components listed in the accompanying price table are in maintenance category A, except the 8809 tape drives and the 3289-3 printer, which are in category D. These categories determine the schedule of extended maintenance charges. The two schedules differ for extended Monday-through-Friday maintenance. Prime-shift maintenance is provided for any consecutive nine-hour period between 7 a.m. and 6 p.m., Monday through Friday. The premium for extended maintenance is expressed in the table below as a percentage of the prime-shift maintenance charges, which are shown in the accompanying price list.

	Consecutive Hours					
	<u>9*</u>	12	<u>16</u>	<u>20</u>	24	
Monday-Friday—						
Category A	10%	14%	18%	22%	26%	
Category D	10	12	14	16	18	
Saturday	4	5	7	8	9	
Sunday	5	7	9	11	12	

Consecutive Hours

For users without a maintenance contract, the 8100 is maintained under per-call class 1. Under this class the per-call charge during regular hours is \$74.00 per hour, and during

off hours the charge is \$86.00 per hour. The hourly rate for systems engineering service is \$79.00. Programming service/programming assistance costs \$107 per hour during regular hours and \$123 per hour outside regular hours.

The current Agreement for Lease or Rental of IBM Machines provides users with a single contract on which they can specify mixtures of rental and leased equipment, each with various terms. CPU's rented under the plan can be terminated or downgraded on 90 days' notice, and all other rented equipment can be terminated or downgraded on 30 days' notice. Base terms and extension terms are specified for each piece of equipment through a leasing agreement.

The termination charge for the two-year lease arrangement is the lower of 5 months' charges or 25 percent of the remaining value of the lease. The lease arrangement also guarantees a maximum rate of increases for extended leasing periods; the rate for all 8100 components is five percent per year beginning in the second year.

All 8100 components qualify for unlimited usage. Purchase credits can be accrued up to a maximum of 55 percent. All components except the 8809 tape drives and 3289-3 printer are classified as Customer Set-Up, which permits (or requires) users to install the components themselves.

EQUIPMENT: The following are representative 8100 Information System configurations.

SIX-TERMINAL 8100 SYSTEM: Includes an 8130 processor with 384K bytes of memory, 58 million bytes of disk storage, three 3287 printers, six 3277 display terminals, and one 8101 Storage and I/O Unit with display/printer attachment. The purchase price is \$65,125. The same system can be leased for \$2,051 per month under a two-year lease agreement or rented for \$2,402 per month.

EIGHTEEN-TERMINAL 8100 SYSTEM: Includes an 8140 processor with 512K bytes of memory, 58 million bytes of disk storage, one 8809 magnetic tape drive, five 3287 printers, 18 8775 display terminals, and a communications loop. The purchase price is \$150,915. The same system can be leased for \$4,510 per month on a two-year lease or rented for \$5,297 per month.■

		Purchase Price	Monthly Maint.	Monthly Rental*	2-Year Lease*
PROCES	SORS AND MAIN MEMORY				
8130	Basic processor; includes 256K bytes of main memory, up to 1-megabyte removable diskette storage, one disk module, disk storage as indicated, instruction set, up to eight I/O hardware interrupt levels, provisions for up to two communications ports:				
A21	29 megabytes disk storage	\$26,460	\$154.00	\$ 846	\$ 721
A22	23 megabytes disk storage, 131K fixed-head capacity	27,240	163.00	870	741
A23	64 megabytes disk storage	28,020	163.00	894	761
A24	58 megabytes disk storage, 131K fixed-head capacity	28,800	173.00	917	781
8140	Basic processor; includes main memory as indicated, 4K bytes non-programmable ROM, up to 64 megabytes disk storage with movable heads or up to 58 megabytes disk storage with removable and fixed heads, instruction set, eight I/O interrupt levels:				
A31	256K bytes of main memory, 29 megabytes disk storage	36,440	190.00	1,351	1,150
A32	256K bytes of main memory, 23 megabytes disk storage, 131K fixed-head capacity	37,220	200.00	1,374	1,170
A33	256K bytes of main memory, 64 megabytes disk storage	38,000	200.00	1,398	1,190
A34	256K bytes of main memory, 58 megabytes disk storage, 131K fixed-head capacity	38,780	208.00	1,421	1,210
A41	320K bytes of main memory, 29 megabytes disk storage, floating-point arithmetic	44,380	233.00	1,686	1,435
A42	320K bytes of main memory, 23 megabytes disk storage, 131K fixed-head capacity, floating- point arithmetic	45,160	243.00	1,709	1,455
A43	320K bytes of main memory, 64 megabytes disk storage, floating-point arithmetic	45,940	243.00	1,733	1,475
A44	320K bytes of main memory, 58 megabytes disk storage, 131K fixed-head capacity, floating- point arithmetic	46,720	251.00	1,756	1,495

<sup>\*</sup>Includes maintenance.

<sup>\*</sup>For periods outside the basic 7 a.m. to 6 p.m. prime shift.

		Purchase Price	Monthly Maint.	Monthly Rental*	2-Year Lease*
PROCESS	ORS AND MAIN MEMORY (Continued)				
A51	512K bytes of main memory, 29 megabytes disk storage	50,200	256.00	2,079	1,770
A52	512K bytes of main memory, 23 megabytes disk storage, 131K fixed-head capacity	50,980	266.00	2,103	1,790
A53	512K bytes of main memory, 64 megabytes disk storage	51,760	266.00	2,126	1,810
A54	512K bytes of main memory, 58 megabytes disk storage, 131K fixed-head capacity	52,540	274.00	2,150	1,830
A61	Processor with 768K bytes of memory and 29 megabytes of nonremovable disk	60,750	189.00	2,203	1,875
A62	Processor with 768K bytes of memory, 23 megabytes of nonremovable disk, and 131K bytes of fixed	61,530	198.00	2,226	1,895
A63	Processor with 768K bytes of memory and 64 megabytes of nonremovable disk	62,310	198.00	2,250	1,915
A64	Processor with 768K bytes of memory, 58 megabytes of nonremovable disk, and 131K bytes of fixed head disk	63,090	207.00	2,273	1,935
A71	Processor with 1024K bytes of memory and 29 megabytes of nonremovable disk	67,080	201.00	2.420	2,060
A72	Processor with 1024K bytes of memory, 23 megabytes of nonremovable fixed disk, and	67,860	209.00	2,444	2,080
470	131K bytes of fixed head disk	00.040	202.00	0.467	0.400
A73	Processor with 1024K bytes of memory and 64 megabytes of nonremovable fixed disk	68,640	209.00	2,467	2,100
A74	Processor with 1024K bytes of memory, 58 megabytes of nonremovable fixed disk, and 131K bytes of fixed head disk	69,420	217.00	2,491	2,120
B51	Processor with 512K bytes of memory and 58 megabytes of nonremovable fixed disk, and 131K bytes of fixed head disk	56,890	228.00	2,079	1,770
B52	Processor with 512K bytes of memory and 123 megabytes of nonremovable fixed disk, and 131K bytes of fixed head disk	67,780	278.00	2,449	2,085
B61	Processor with 768K bytes of memory and 58 megabytes of nonremovable fixed disk, and	63,220	238.00	2,297	1,955
B62	131K bytes of fixed head disk Processor with 768K bytes of memory and 123 megabytes of nonremovable fixed disk, and	74,110	290.00	2,667	2,270
B71	131K bytes of fixed head disk Processor with 1024K bytes of memory, 58 megabytes of nonremovable fixed disk, and	69,550	250.00	2,514	2,140
	131K bytes of fixed head disk			•	
B72	Processor with 1024K bytes of memory, 123 megabytes of nonremovable fixed disk, and 131K bytes of fixed head disk	80,440	300.00	2,884	2,455
1710	128K bytes additional storage for 8130 processor; maximum one per person (cannot be used if 1720 storage is used)	2,475	9.00	98	83
1720	256K bytes additional storage for 8130 processor; maximum three per processor (cannot be used if 1710 storage is used)	4.950	18.00	195	166
1490	128K-byte storage increment for 8140 processor, models A31 through A34; maximum one per processor	6,540	33.00	324	276
8101	Storage and Input/Output Unit; provides additional disk storage and device attachment capability for 8130/40 processors; maximum two per 8130 processor, four per 8140 processor:				
A10	Device attachment capability	7,150	19.50	235	200
A11	Provides 29 megabytes disk storage with movable heads	16,480	64.00	558	475
A13	Provides 64 megabytes disk storage with movable heads	18,040	73.50	605	515
A20	Device attachment capability	6,170	14.00	205	175
A23	Provides 64 megabytes disk storage with movable heads	18,040	73.50	605	515
A25	Provides 129 megabytes disk storage with movable heads	28,930	127.00	975	830
PROCESSO	OR OPTIONS AND FEATURES				
	3130 Processors:				
1 6010165 101 6	7100 11000330/3.				
1520	Feature Expansion, Type I; allows four additional communications ports to be attached to	425	0.50	14	12
	8130 processor for a maximum of six ports; required for attachment of two lobe loops or communications features requiring 5200 multi-speed clock; maximum one per processor				
1530	System Expansion; provides additional interrupt levels; required for attachment of up to two 8101 Storage and Input/Output Units or one 8101 and one 8809 Magnetic Tape	2,645	12.00	83	71
EEOO	Unit, Model 1B, to processor; maximum one per processor	736	5 50	21	10
5500	Non-Switched Intergated Modem, 600/1200 bps; requires 1601 SDLC Communications Adapter with Clock or 1603 BSC/SS Communications with Clock	730	5.50	21	18
Features for 8	1140 B Model Processors:				
1701	Communications Adapter	440	0.50	14	12
3220	Display and Printer Attachment	2,975	18.00	105	89
3750	Floating Point Feature	4,490	25.50	160	136
3901	Feature Expansion Prerequisite; required for 1701	540	4.00	15	13
4901	Magnetic Tape Attachment	2,425	11.50	85	72
Features for 8	1130 and 8140 Processors Via The 8101 Storage and I/O Unit:				
1501	Display and Printer Attachment, Type I; provides attachment of 3277 display, 3287 printer, and 3284, 3286, or 3288 printers (8101 A11 and A13 units only); requires 1505/06 adapters	992	4.50	32	27
1502	Display and Printer Attachment, Type II; same as 1501 but requires 1503	441	1.00	14	12
1503	Communications Attachment, Type I; provides attachment of loops and communication ports (8101 A11 and A13 units only)	992	4.00	32	27
*Includes mai	intenance.				

PROCESSOR OPTIONS AND FEATURES (Continued)   160			Purchase Price	Monthly Maint.	Monthly Rental*	2-Year Lease*
1505	PROCESS	OR OPTIONS AND FEATURES (Continued)				
1807   Diskers Driver/Tape Attachment   1807   1807   1808   18						
Second Diskette Drive for 8101 Storage and Input/Output Unit 1 megabyte   3.170   31.50   112   98   102   102   102   103						
Magnetic Topio Attachment for 1015 Storage and Input/Output Unit   1,980   10,000   69   59   59   59   50   50   50   50   5	INPUT/OU	TPUT UNITS AND FEATURES				
Magnetic Tapp Attachment for B101 Storage and Input/Output Unit   1,980   10,000   69   59   59   59   50   50   51   52   52   52   52   52   52   52	4520	Second Diskette Drive for 8101 Storage and Input/Output Unit; 1 megabyte	3,170	31.50	112	.95
BOSE    C.u. of Reader Attachment for 3782/3520   14   12   12   18   150   14   12   18   150   16   16   18   18   18   18   18   18		Diskette Drive and Magnetic Tape Attachment for Model A10; required for attachment of one 4520 diskette drive and one 4521 magnetic tape attachment to 8101 Storage and				
STATE   STAT						
8150         Card Punch Astachment for 3782/3821         705         3.50         21         18           3262.2/3         Band Printer; 560 Ipm with 48-character set         16,200         180,00         491         418           3282-12/33         Band Printer; 550 Ipm with 48-character set         11,570         132,00         344         283           3284-1         Matrix Printer, 60 cps; 480-char, buffer         2,845         65,00         174         148           3286-1         Matrix Printer, 60 cps; 1820-char, buffer         3,385         78,00         220         179           3287-1         Table-top Printer; 80 cps         5,960         49,00         208         179           3287-1         Table-top Printer; 80 cps         6,430         555.0         257         279           3287-1         Table-top Printer; 120 cps         6,355         60.50         253         215           3287-17         Table-top Printer; 120 cps         6,355         60.00         223         227           2287-2C         Calcer Printer; 120 cps         6,355         60.00         223         225           3287-17         Printer; 30 cps         6,165         540.00         222         220           3287-17         Printer; 1						
3282-12   Martix Printer; 30 cps; 480-char buffer   2.535   6.00   174   148   3284-1   Martix Printer; 40 cps; 480-char buffer   2.845   6.00   174   148   3286-1   Martix Printer; 40 cps; 1920-char buffer   2.845   6.00   177   159   3286-1   Martix Printer; 60 cps; 1920-char buffer   3.755   7.900   223   179   3287-1   Martix Printer; 60 cps; 1920-char buffer   3.755   7.900   220   179   3287-1   Table-top Printer; 80 cps   6.450   6.650   6.550   257   219   3287-2   Table-top Printer; 120 cps   6.355   6.050   253   215   3287-2   Table-top Printer; 120 cps   6.355   6.050   253   215   3287-2   Table-top Printer; 120 cps   6.165   6.000   227   206   227   227   2287-11   Printer; 80 cps   6.165   6.000   247   206   2287-2   2287-12			705	3.50		
3284-2   Matrix Printer, 60 cps, 1490-char, buffer   3.385   78.00   210   179   3286-2   Matrix Printer, 66 cps, 1490-char, buffer   3.375   78.00   223   190   3286-2   Matrix Printer, 66 cps, 1490-char, buffer   3.3755   78.00   223   190   3287-10   179   3287-10   179   3287-10   179   3287-10   179   3287-10   179   3287-10   179   3287-10   179   3287-10   189   3287-20   189   3287-20   189   3287-20   189   3287-20   189   3287-20   189   3287-21   189   3287-20   189   3287-11						
3286-1						
3287-10         Color Printer; 80 cps         6.430         55.55         257         219           3287-20         Table-top Printer; 120 cps         6.825         6.700         302         257           3287-11         Printer; 120 cps         6.825         6.700         302         257           3287-12         Printer; 120 cps         6.560         6.560         6.560         242         206           3287-12         Printer; 120 cps         6.560         6.560         6.560         287         244           1120         ARI-Text Capability for 3287         183         0.50         6         5           3880         Extended Character Set Adapter         477         400         16         14           4110         Friction Feed Paper Handling Feature         188         0.50         7         6           4110         Friction Feed Paper Handling Feature         188         0.50         6         1         22         0.50         7         6         4         1         1         1         1         1         1         1         1         1         2         2         2         2         2         2         2         2         2         2						
3287-1   Color Printer; 80 cps   6.430   55.50   257   219   3287-20   3287-20   3287-20   3287-20   3287-120   3287-20   3287-120   3287-20   3287-120   3287-20   3287-120   3287-20   3287-120   3287-20   3287-120   3287-20   3287-120   3287-20   3287-120   3287-20   3287-120   3287-20   3287-120   3287-20   3287-120   3287-20   32	3287-1	Table-top Printer; 80 cps	5,960	49.00	208	177
2827-20   Color Printer; 120 cps   6.825   67.00   302   257   2827-112   Printer; 80 cps   6.660   65.50   242   206   2287-12   Printer; 120 cps   6.660   65.50   287   244   206   2287-12   2287   244   266   2287   244   266   2287   244   266   2287   244   266   2287   244   266   2287   244   266   2287   245   24		Color Printer; 80 cps				
120						
3610         Extended Character Set Adapter         477         400         16         14           3880         Extended Prints Biffer         220         0.50         7         6           4110         Firciton Feed Paper Handling Feature         188         0.50         6         5           5781         Programmed Symbols PS-2         918         5.50         28         24           5782         Programmed Symbols PS-4A         1.650         15.00         61         52           8700         Variable width forms tractor         168         0.50         6         5           3288-2         Line Printer; 120 lpm         6.325         115.00         461         392           3289-1         Line Printer; 500 lpm         14.600         205.00         698         594           3289-2         Line Printer Good lpm         14.600         205.00         698         594           1090         Audible Alarm for 3289-1 or 3289-2 line printer         192         -         6         5           1130         Text Print Feature for 3289-1 or 3289-2 line printer         192         -         6         5           1130         Text Print Feature for 3289-1 or 3289-2 line printer         192         -		Printer; 120 cps				
3880         Extended Print Buffer         220         0.50         7         6           5781         Priction Feed Paper Handling Feature         168         0.50         6         5           5782         Programmed Symbols PS-4         735         3.50         28         24           5783         Programmed Symbols PS-4A         1.650         1.60         61         52           5780         Programmed Symbols PS-4A         1.680         1.500         61         52           3288-2         Line Printer; 120 lpm         6.325         115,00         461         392           3288-1         Line Printer; 155 lpm         9,810         121,00         461         392           3288-2         Line Printer; 600 lpm         14600         205,00         698         594           1090         Audible Alarm for 3289-1 or 3289-2 line printer         231         -         6         5           8809         Magnetic Tape Units:         1.7         6         5           18         First drive that attaches to 8101 Storage and I/O Unit         1.1         1.500         58.00         408         347           4920         8100 System Multi-Drive feature; required for 8809, Model 18, if Model 2 or 3 is attached						
4110         Friction Feed Paper Handling Feature         168         050         6         5           5781         Programmed Symbols PS-2         918         550         28         24           5782         Programmed Symbols PS-4         1,650         15.00         61         52           8700         Programmed Symbols PS-4A         1,650         15.00         61         52           8700         Variable width forms tractor         168         0,50         6         5           3288-2         Line Printer; 120 lpm         6,325         115.00         483         411           3288-1         Line Printer; 400 lpm         14,600         205.00         688         594           3288-2         Line Printer; 500 lpm         14,600         205.00         688         594           3289-3         Line Printer; 500 lpm         192         6         5           1130         Text Print Feature for 3289-1 or 3289-2 line printer         192         6         5           1130         Magnetic Tape Linits:         1         15.00         488         594           18809         Magnetic Tape Linits:         1         11.50         58.00         408         437           1						
5782         Programmed Symbols PS-4A         1,650         150.0         61         52           8700         Programmed Symbols PS-4A         1,660         150.0         61         52           8700         Programmed Symbols PS-4A         1,660         150.0         61         52           3288-2         Line Printer; 120 lpm         6,325         115.00         461         392           3289-1         Line Printer; 400 lpm         14,600         205.00         698         594           13289-2         Line Printer; 500 lpm         14,600         205.00         698         594           1090         Audible Alarm for 3289-1 or 3289-2 line printer         192         6         5           1130         Text Print Feature for 3289-1 or 3289-2 line printer         231         7         7         6           8809         Magnetic Tape Units:         1A First drive that attaches to 8101 Storage and I/O Unit         11,500         58.00         408         347           48 First drive that attaches to 8101 Storage and I/O Unit in the strate of the st						
Programmed Symbols PS-4A   Variable width forms tractor   1.650   15.00   61   52   62   6325   115.00   63   6325   115.00   63   6328-2   1.660   61   6325   115.00   63   63   63   63   63   63   63				-		
Second or fourth drive that attaches to 8101 Storage and I/O Unit 18 First drive that attaches to 18/18 or 3 section or 18 first drive that attaches to 18						-
1						
2389-2   Line Printer; 400 lpm   14,600   205.00   698   594   3289-3   Line Printer; 500 lpm   14,600   205.00   698   594   3289-3   Line Printer; 500 lpm   14,600   205.00   698   594   3289-3   Line Printer; 500 lpm   14,600   205.00   698   594   3289-3   Line Printer for 3289-1 or 3289-2 line printer   192	3288-2	Line Printer; 120 lpm	6,325	115.00	483	411
14,600	3289-1	Line Printer, 155 lpm	9,810	121.00	461	392
1090						
1130   Text Print Feature for 3289-1 or 3289-2 line printer   231		, , ,		205.00		
1A First drive that attaches to 8101 Storage and I/O Unit       11,500       58,00       408       347         1B First drive that attaches directly to 8130/40 processor       14,080       76,00       498       424         2 Second or fourth drive that attaches to 1A/1B or 3, respectively       10,210       52,00       363       309         3 Third drive that attaches to Model 2       8100 System Multi-Drive Feature; required for 8809, Model 1B, if Model 2 or 3 is attached       396       1.50       13       11         3101-100       Model 10 Display Terminal; character transmission; RS-232C interface       1,295       70,00       —       —         3101-110       Model 10 Display Terminal; character transmission; RS-232C interface       1,360       70,00       —       —         3101-120       Model 10 Display Terminal; character transmission; RS-232C interface       1,360       70,00       —       —         3101-120       Model 12 Display Terminal; character transmission; RS-232C/P3 and current loop interface       1,320       70,00       —       —         3101-200       Model 20 Display Terminal; switch selectable character and block transmission; RS-232C       1,495       80,00       —       —         3101-210       Model 20 Display Terminal; switch selectable character and block transmission; RS-232C/       1,560       80,00       —				and the second		
18 First drive that attaches directly to 8130/4Q processor       14,080       76,00       498       424         2 Second or fourth drive that attaches to 1A/1B or 3, respectively       10,210       52,00       363       309         3 Third drive that attaches to Model 2       8100 System Multi-Drive Feature; required for 8809, Model 1B, if Model 2 or 3 is attached       396       1.50       13       11         3101-100       Model 10 Display Terminal; character transmission; RS-232C interface       1,295       70.00       —       —         3101-110       Model 10 Display Terminal; character transmission; RS-232C (naterface       1,380       70.00       —       —         3101-120       Model 12 Display Terminal; character transmission; RS-232C/ Om a current loop interface       1,320       70.00       —       —         3101-200       Model 13 Display Terminal; switch selectable character and block transmission; RS-232C       1,495       80.00       —       —         3101-200       Model 20 Display Terminal; switch selectable character and block transmission; RS-232C       1,560       80.00       —       —         3101-210       Model 20 Display Terminal; switch selectable character and block transmission; RS-232C/       1,520       80.00       —       —         3101-220       Model 22 Display Terminal; switch selectable character and block transmission; RS-232C/ </td <td>8809</td> <td>Magnetic Tape Units:</td> <td></td> <td></td> <td></td> <td></td>	8809	Magnetic Tape Units:				
2 Second or fourth drive that attaches to 1A/1B or 3, respectively 3 Third drive that attaches to Model 2 3 Third drive that attaches to Model 1B, if Model 2 or 3 is attached 3 Third drive that attaches to Model 1B, if Model 2 or 3 is attached 3 Third drive that attaches to Model 1B, if Model 2 or 3 is attached 3 Third drive that attaches to Model 1B, if Model 2 or 3 is attached 3 Third drive that attaches to Model 1B, if Model 2 or 3 is attached 3 Third drive that attaches to Model 1B, if Model 2 or 3 is attached 3 Third drive that attaches to Model 2 or 3 is attached 3 Third drive that attaches to Model 1B, if Model 2 or 3 is attached 3 Third drive that attaches to Model 1B, if Model 2 or 3 is attached 3 Third drive that attaches to Model 1B, if Model 2 or 3 is attached 3 Third drive that attaches to Model 2 or 3 is attached 3 Third drive that attaches transmission; RS-232C interface 3 Third Display Terminal; character transmission; RS-232C interface 3 Third Display Terminal; switch selectable character and block transmission; RS-232C and a current loop interface 3 Third drive that attaches to Model 2 Display Terminal; switch selectable character and block transmission; RS-232C and a Sound or Display Terminal; switch selectable character and block transmission; RS-232C and Third Display Terminal; switch selectable character and block transmission; RS-232C and Third Display Station/Control Unit; 960-character display 3 Third Display Station/Control Unit; 960-character displa						
3 Third drive that attaches to Model 2   11,500   58.00   408   347						
3101-100   Model 10 Display Terminal; character transmission; RS-232C interface   1,295   70.00   —   —   3101-110   Model 10 Display Terminal with modem cable; character transmission; RS-232C interface   1,360   70.00   —   —   3101-120   Model 12 Display Terminal; character transmission; RS-232C/20 ma current loop interface   1,320   70.00   —   —   3101-130   Model 13 Display Terminals; character transmission; RS-232C/RS-422A interface   1,320   70.00   —   —   3101-200   Model 20 Display Terminal; switch selectable character and block transmission; RS-232C   1,495   80.00   —   —     3101-210   Model 20 Display Terminal; with modem cable; switch selectable character and block transmission; RS-232C   1,560   80.00   —   —     3101-220   Model 20 Display Terminal; switch selectable character and block transmission; RS-232C   1,520   80.00   —   —     3101-230   Model 23 Display Terminal; switch selectable character and block transmission; RS-232C/   1,520   80.00   —   —     3101-230   Model 23 Display Terminal; switch selectable character and block transmission; RS-232C/   1,520   80.00   —   —     3274-51C   Control Unit   3101   310						
3101-110   Model 10 Display Terminal with modem cable; character transmission; RS-232C interface   1,360   70.00   —   —	4920	8100 System Multi-Drive Feature; required for 8809, Model 1B, if Model 2 or 3 is attached	396	1.50	13	11
3101-120   Model 12 Display Terminal; character transmission; RS-232C/20 ma current loop interface   1,320   70.00   —   —					_	
3101-130   Model 13 Display Terminals; character transmission; RS-232C/RS-422A interface   1,320   70.00   —   —					_	
3101-200   Model 20 Display Terminal; switch selectable character and block transmission; RS-232C   1,495   80.00   —   —						_
3101-210   Model 20 Display Terminal with modem cable; switch selectable character and block transmission; RS-232C interface   3101-220   Model 22 Display Terminal; switch selectable character and block transmission; RS-232C/		Model 20 Display Terminal; switch selectable character and block transmission; RS-232C			-	
3101-220   Model 22 Display Terminal; switch selectable character and block transmission; RS-232C/ 20 ma current loop interface   3101-230   Model 23 Display Terminal; switch selectable character and block transmission; RS-232C/ 1,520   80.00   —   —   3102   Thermal Printer; for attachment to 3101   1,295   130.00   —   —   3274-51C   Control Unit   6,450   57.50   201   171   3276-11   Display Station/Control Unit; 960-character display   6,390   33.00   208   177   3276-12   Display Station/Control Unit; 1920-character display   6,570   33.50   214   182   3276-12	3101-210	Model 20 Display Terminal with modem cable; switch selectable character and block trans-	1,560	80.00	_	
3101-230       Model 23 Display Terminal; switch selectable character and block transmission; RS-232C/ RS-422A interface       1,520       80.00       —       —         3102       Thermal Printer; for attachment to 3101       1,295       130.00       —       —         3274-51C       Control Unit       6,450       57.50       201       171         3276-11       Display Station/Control Unit; 960-character display       6,390       33.00       208       177         3276-12       Display Station/Control Unit; 1920-character display       6,570       33.50       214       182	3101-220	Model 22 Display Terminal; switch selectable character and block transmission; RS-232C/	1,520	80.00	_	
3274-51C       Control Unit       6,450       57.50       201       171         3276-11       Display Station/Control Unit; 960-character display       6,390       33.00       208       177         3276-12       Display Station/Control Unit; 1920-character display       6,570       33.50       214       182	3101-230	Model 23 Display Terminal; switch selectable character and block transmission; RS-232C/	1,520	80.00	_	_
3276-11 Display Station/Control Unit; 960-character display 6,390 33.00 208 177 3276-12 Display Station/Control Unit; 1920-character display 6,570 33.50 214 182	3102	Thermal Printer; for attachment to 3101	1,295	130.00	_	
3276-12 Display Station/Control Unit; 1920-character display 6,570 33.50 214 182	3274-51C	Control Unit	6,450	57.50	201	171
• • • • • • • • • • • • • • • • • • • •					208	177
			6,570	33.50	214	182

		Purchase Price	Monthly Maint.	Monthly Rental*	2-Year Lease*
INPUT/O	UTPUT UNITS AND FEATURES (Continued)				
3276-13	Display Station/Control Unit; 2560-character display	6,750	34.50	217	185
3276-14	Display Station/Control Unit; 3440-character display	6,930	35.00	226	192
3277-1	Display Terminal; 480-character display	1,470 1,905	10.00 21.00	88	75
3277-2	Display Terminal; 1920-character display			128	109
3278-1 3278-2	Display Terminal; 960-character display Display Terminal; 1920-character display	2,205 2,340	13.00 13.50	71 74	60 63
3279-2A	Display Terminal; Four Color, 1920-character Display	3,805	25.50 28.00	122	104
3279-2B 3279-3A	Display Terminal; Seven Color, 1920-character Display Display Terminal; Four Color; 2560-character Display	4,210 4,175	26.50 26.50	134 134	114 114
3279-3B	Display Terminal; Seven Color, 2560-character Display	4,580	29.00	146	124
1720	Switch Control Unit	180	2.50	5	4
4621 4622	75-Key EBCDIC Typewriter Keyboard 75-Key EBCDIC Data Entry Keyboard	495 495	2.50 3.50	14 14	12 12
4623	75-Key EBCDIC keypunch keyboard	495	3.50	14	12
4624	75-Key ASCII Typewriter Keyboard	495	2.50	14	12
4626	87-key EBCDIC Typewriter/APL keyboard	675	3.50	19	16
4627	87-key EBCDIC Typewriter keyboard	675	3.00	19	16
4628 4629	87-key ASCII Typewriter keyboard 87-key EBCDIC Typewriter/Text keyboard	675 675	3.00 3.50	19 19	16 16
4640	87-key EBCDIC Typewriter Overlay Keyboard	675	3.50	19	16
4651	87-key EBCDIC Attribute Select Typewriter keyboard	675	3.50	19	16
4652	87-key EBCDIC Attribute Select Typewriter/APL keyboard	675	3.50	19	16
4690	Keyboard Numeric Lock	NC	NC	NC	NC
4999	Magnetic Reader Control Programmed Symbols DS-2	405	4.50	12	10
5781 5782	Programmed Symbols PS-4	540 900	1.50 4.00	15 26	13 22
6340	Security Keylock	35	NC	35***	_
6350	Selector Light Pen for Models 3A or 3B	585	0.50	16	14
6350	Selector Light Pen for Models 2A or 2B	585	0.50	16	14
8775-1 8775-2	Display Terminal; up to 2560 characters in 9 x 16 matrix Display Terminal; up to 2560 characters in 9 x 16 matrix or 3440 characters in 9 x 12 matrix	2.975 3,350	22.00 22.00	88 98	75 83
1090	Audible Alarm	94	NC	2	2
3622	Feature Storage	756	3.50	21	18
3624 3905	Enhanced Function; requires 3622 feature storage and 3905 feature adapter Feature Adapter; requires 3622 feature storage and 3624 enhanced function	NC 425	NC 2.00	NC 12	NC 10
4621	75-Key Typewriter Keyboard	519	2.50	14	12
4622	75-Key Data Entry Keyboard	519	4.00	14	12
4623	75-Key Data Entry Keyboard with keypunch layout	519	4.00	14	12
4626	87-Key Typewriter; APL	708	3.50	19	16
4627 4850	87-Key Typewriter Loop Adapter	708 330	3.00 2.00	19 8	16 7
4999	Magnetic Reader Control	425	2.50	12	10
6350	Selector Light Pen	614	1.00	16	14
3640 PLA	NT COMMUNICATION DEVICES				
		3,255	13.50		100**
3641-1 3641-2	Reporting Terminal Reporting Terminal	3,255 3,890	15.00		108** 127**
3642-1	Encoder Printer	6,360	31.50	_	228**
3642-2	Encoder Printer	7,520	38.00		270**
3643-2	Keyboard Display	2,700	27.00	_	117**
3643-3	Keyboard Display	3,745	33.50	_	158**
3643-4	Keyboard Display	3,950 5,775	35.50		164**
3644 4905	Automatic Data Unit Manual I/O	1,625	34.00 6.50	_	207** 54**
3645	Receive-Only Printer	5,180	44.00		228**
3646	Scanner Control Unit	2,810	11.00		92**
6351	Magnetic Reader Attachment	694	2.50	MARINE,	21**
3631	Plant Communication Controller:	00000			
	1A 250K-byte diskette 1B 500K-byte diskette	28,990 31,190	224.00	1,187 1,269	1,010 1,080
3632	Plant Communication Controller:	31,130	247.00	1,203	1,000
7	1A 5-megabyte disk	49,160	273.00	1,833	1,560
	1B 9.2-megabyte disk	52,470	281.00	1,939	1,650
*Inaludos	maintananna				

<sup>\*</sup>Includes maintenance.
\*\*5-year lease.
\*\*\*One-time charge.

#### **EQUIPMENT PRICES**

		Purchase Price	Monthly Maint.	Monthly Rental*	2-Year Lease*
3640 PLAN	NT COMMUNICATION DEVICES (Continued)				
1006	Additional Storage Feature	1,225	10.00	63	54
3211	Data Link Adapter	1,320	10.50	40	34
3701	EIA/CCITT Host	445	4.00	13	11
3703	EIA/CCITT Data Link	445	4.00	13	11
4780	Loop Adapter	1,035	17.50	35	30
4502	SDLC Communications Feature without clocking; to 9600 bps	1,200	10.50	36	32
6301	Host Communications Feature with clocking	745	3.00	20	17
6302	Host Communications Feature without clocking	570	2.50	12	10
1010/11	Additional Disk Heads for 3632 Plant Communications Controller	1,130	17.00	34	29
COMMUNI	CATIONS				
4850	Loop Adapter	945	3.50	25	21
3842	Loop Control Unit	6,625	44.50		269**
3843	Loop Control Unit	5,155	28.00	170	145
1051	Alternate Voice	525	2	_	17**
5101	Multipoint Tributary	490	4		19**
6101	Point-to-Point	244	2		10**
7951	Switched Network Back-Up Manual Answer	578	7	_	29**
1550	CCITT V.35 Interface; up to 9600 bps	561	2.00	16	14
1601	SDLC Communications Adapter with Clock	992	8.50	48	41
1602	SDLC Communications Adapter without Clock	926	8.00	39	33
1603	BSC/SS Communications Adapter with Clock	738	3.00	21	18
1604	BSC Communications Adapter without Clock	495	2.50	13	11
3701	EIA RS-232C Interface	441	4.00	13	11
4545	Expanded Function Operator Panel (8140 processor only)	2,645	33.50	96	82
4830	Loop Adapter	666	4.00	22	19
4835	Loop Adapter, Second Lobe	666	4.00	22	19
5200	Multi-Speed Clock	463	1.50	14	12
5501	Switched Integrated Modem	926	7.00	29	25
5660	Digital Data Service Adapter (DDSA)	926	2.00	28	24

<sup>\*</sup>Includes maintenance.

## **SOFTWARE PRICES**

		Monthly License Fee Basic	Monthly License Fee DSLO
5761-DS1	Distributed Processing Control Executive (DPCX)	\$236	-
	Distributed Processing Programming Executive (DPPX):		
5760-010	DPPX/Base	181	\$136
5760-AS1	DPPX/ASSM	48	36
5760-CB1	DPPX/COBOL Compiler	97	73
5760-LB1	DPPX/COBOL Run-Time Library	18	13
5760-FO1	DPPX/FORTRAN Compiler	73	54
5760-LM1	DPPX/FORTRAN Library	36	28
5760-XR1/01	DPPX/DPS Interactive Map Definition	78	58
5760-XR1/02	DPPX/DPS Format Management	30	22
5760-TD1	DPPX/DTMS (Data Base and Transaction Management System)	108	81
5760-RC1	DPPX/DSC (Data Stream Compatibility)	18	13
5760-XC1	DPPX/RJE	24	18
5760-SM1	DPPX/Sort/Merge	24	18
5760-XC2	DMS/DPPX	102	77
5760-ED1	DPPX/GEN3644	18	13
5748-XXG	Distributed Systems Executive (DSX)	192	_
5735-XR1	Host Command Facility for 8100/DPCX systems	73	54
5760-XR5/01	DPPX/PT Monitor	42	
5760-XR5/02	DPPX/PT Reporter Feature	48	_

<sup>\*\*5-</sup>year lease.
\*\*\*One-time charge.